

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 21-May-2012 Revision Date 09-Feb-2024 Revision Number 7

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: <u>Methylmagnesium bromide, 3M solution in diethyl ether</u>

Cat No.: 183540000; 183541000; 183548000

Molecular Formula C H3 Br Mg

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals. Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name

Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids Category 1 (H224)
Substances/mixtures which, in contact with water, emit flammable gases Category 1 (H260)

Health hazards

Acute oral toxicity

Skin Corrosion/Irritation

Category 4 (H302)

Category 1 B (H314)

ACR18354

Methylmagnesium bromide, 3M solution in diethyl ether

Revision Date 09-Feb-2024

Serious Eye Damage/Eye Irritation

Specific target organ toxicity - (single exposure)

Category 1 (H318) Category 3 (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H224 - Extremely flammable liquid and vapor

H260 - In contact with water releases flammable gases which may ignite spontaneously

H314 - Causes severe skin burns and eye damage

H336 - May cause drowsiness or dizziness

H302 - Harmful if swallowed

EUH019 - May form explosive peroxides

EUH014 - Reacts violently with water

Precautionary Statements

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P310 - Immediately call a POISON CENTER or doctor/physician

P223 - Do not allow contact with water

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P302 + P335 + P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water

2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

| Component | CAS No | EC No | Weight % | CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and |
|--------------------------|---------|-------------------|----------|--|
| | | | | UK SI 2020/1567 |
| Methyl magnesium bromide | 75-16-1 | EEC No. 200-844-1 | 35 | Flam. Liq.2 (H225) Water-react. 1 (H260) Skin Corr. 1B (H314) Eye Dam. 1 (H318) (EUH014) |
| Ethyl ether | 60-29-7 | EEC No. 200-467-2 | 65 | Flam. Liq. 1 (H224) |

Methylmagnesium bromide, 3M solution in diethyl ether

| | Acute Tox. 4 (H302) STOT SE 3 (H336) |
|--|---|
| | (EUH019) (EUH066) |

| Components | Reach Registration Number | |
|--------------------------|---------------------------|--|
| Methyl magnesium bromide | 01-2120119138-61 | |
| Ethyl ether | 01-2119535785-29 | |

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If

Revision Date 09-Feb-2024

not breathing, give artificial respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Difficulty in breathing. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water.

5.2. Special hazards arising from the substance or mixture

Extremely flammable. Corrosive material. Reacts violently with water. Contact with water liberates extremely flammable gases.

Methylmagnesium bromide, 3M solution in diethyl ether

Revision Date 09-Feb-2024

Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen halides, Magnesium oxides, Methane.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

6.2. Environmental precautions

Avoid release to the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Do not expose spill to water. Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Store indoors. Keep away from heat, sparks and flame. Keep away from water or moist air. Store under an inert atmosphere. Flammables area. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 4.3 Storage Class (LGK) (Germany)

Revision Date 09-Feb-2024

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

| Component | The United Kingdom | European Union | Ireland |
|-------------|------------------------------------|-------------------------------------|------------------------------------|
| Ethyl ether | STEL: 200 ppm 15 min | TWA: 100 ppm (8h) | TWA: 100 ppm 8 hr. |
| | STEL: 620 mg/m ³ 15 min | TWA: 308 mg/m ³ (8h) | TWA: 308 mg/m ³ 8 hr. |
| | TWA: 100 ppm 8 hr | STEL: 200 ppm (15min) | STEL: 200 ppm 15 min |
| | TWA: 310 mg/m ³ 8 hr | STEL: 616 mg/m ³ (15min) | STEL: 616 mg/m ³ 15 min |

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component | Acute effects local (Dermal) | Acute effects systemic (Dermal) | Chronic effects local (Dermal) | Chronic effects systemic (Dermal) |
|-------------------------------|------------------------------|------------------------------------|--------------------------------|-----------------------------------|
| Ethyl ether 60-29-7 (65) | | | | DNEL = 44mg/kg bw/day |

| Component | Acute effects local (Inhalation) | Acute effects systemic (Inhalation) | Chronic effects local (Inhalation) | Chronic effects systemic (Inhalation) |
|-------------------------------|----------------------------------|-------------------------------------|------------------------------------|---------------------------------------|
| Ethyl ether 60-29-7 (65) | | DNEL = 616mg/m ³ | | DNEL = 308mg/m ³ |

Predicted No Effect Concentration (PNEC)

See values below.

| | Component | Fresh water | 1 | | Microorganisms in | , , |
|---|----------------|--------------|------------------|-----------------|-------------------|------------------|
| L | | | sediment | | sewage treatment | |
| | Ethyl ether | PNEC = 2mg/L | PNEC = 9.14mg/kg | PNEC = 1.65mg/L | PNEC = 4.2mg/L | PNEC = 0.66mg/kg |
| l | 60-29-7 (65) | | sediment dw | | | soil dw |

| Component | Marine water | Marine water sediment | Marine water intermittent | Food chain | Air |
|----------------|----------------|--------------------------|---------------------------|------------|-----|
| Ethyl ether | PNEC = 0.2mg/L | PNEC = | | | |
| 60-29-7 (65) | | 0.914mg/kg | | | |
| | | sediment dw | | | |

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Methylmagnesium bromide, 3M solution in diethyl ether

Revision Date 09-Feb-2024

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material Breakthrough time Glove thickness EU standard Glove comments

Nitrile rubber See manufacturers - EN 374 (minimum requirement)

Viton (R) recommendations

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

On basis of test data

Liquid

141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Brown

Odor
Odor
No information available
No data available
No information available
Flammability (liquid)
Extremely flammable

Flammability (solid,gas) Not applicable

Explosion Limits No data available

Flash Point -40 °C / -40 °F Method - (based on components)

Autoignition Temperature
Decomposition Temperature
PH
No data available
No information available

Viscosity

Water Solubility

Solubility in other solvents

No data available
vigorous reaction
No information available

Partition Coefficient (n-octanol/water)

Componentlog PowEthyl ether0.82

Methylmagnesium bromide, 3M solution in diethyl ether

Vapor Pressure No data available

Density / Specific Gravity

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

1.035

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular FormulaC H3 Br MgMolecular Weight119.26

Explosive Properties Vapors may form explosive mixtures with air

Substances/mixtures which, in Emitted gas ignites spontaneously **contact with water, emit flammable** Gas(es) = Methane

gases

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity Yes

10.2. Chemical stability

Reacts violently with water. Moisture sensitive. Air sensitive. May form explosive peroxides.

Revision Date 09-Feb-2024

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous ReactionsContact with water liberates extremely flammable gases.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or

water. Exposure to air. Incompatible products.

10.5. Incompatible materials

Acids. Bases. Water. Alcohols.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2). Hydrogen halides. Magnesium oxides.

Methane.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Category 4

DermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Toxicology data for the components

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-------------|------------------|-------------------|---------------------|
| Ethyl ether | 1215 mg/kg (Rat) | 20 mL/kg (Rabbit) | 32000 ppm (Rat) 4 h |

(b) skin corrosion/irritation; Category 1 B

Methylmagnesium bromide, 3M solution in diethyl ether

Revision Date 09-Feb-2024

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

No data available Respiratory Skin No data available

No data available (e) germ cell mutagenicity;

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

No data available (g) reproductive toxicity;

(h) STOT-single exposure; Category 3

Central nervous system (CNS). Results / Target organs

No data available (i) STOT-repeated exposure;

No information available. **Target Organs**

(i) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

delayed

Symptoms / effects,both acute and Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness,

nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects This product contains the following substance(s) which are hazardous for the environment. .

| Component | Freshwater Fish | Water Flea | Freshwater Algae |
|-------------|--------------------------------|---------------------|------------------|
| Ethyl ether | LC50: > 10000 mg/L, 96h static | EC50 = 165 mg/L/24h | |
| | (Lepomis macrochirus) | | |
| | LC50: = 2560 mg/L, 96h | | |
| | flow-through (Pimephales | | |
| | promelas) | | |
| | , | | |

| Component | Microtox | M-Factor |
|-------------|-------------------------|----------|
| Ethyl ether | EC50 = 5600 mg/L 15 min | |

12.2. Persistence and degradability

Persistence Soluble in water, Persistence is unlikely, based on information available.

Methylmagnesium bromide, 3M solution in diethyl ether

Revision Date 09-Feb-2024

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component log Pow **Bioconcentration factor (BCF)** Ethyl ether 0.82 No data available

12.4. Mobility in soil The product is water soluble, and may spread in water systems. Will likely be mobile in the

environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Endocrine disrupting

properties

This product does not contain any known or suspected endocrine disruptors **Endocrine Disruptor Information**

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN1928 14.1. UN number

14.2. UN proper shipping name Methylmagnesium bromide in ethyl ether (Mixture)

14.3. Transport hazard class(es) 4.3 3 **Subsidiary Hazard Class** 14.4. Packing group Ι

ADR

14.1. UN number UN1928

Methylmagnesium bromide in ethyl ether (Mixture) 14.2. UN proper shipping name

4.3 14.3. Transport hazard class(es) **Subsidiary Hazard Class** 3 14.4. Packing group Ι

Revision Date 09-Feb-2024

<u>IATA</u>

14.1. UN number UN1928

14.2. UN proper shipping name Methyl magnesium bromide in ethyl ether (Mixture)

14.3. Transport hazard class(es)4.Subsidiary Hazard Class314.4. Packing groupI

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component | CAS No | EINECS | ELINCS | NLP | IECSC | TCSI | KECL | ENCS | ISHL |
|--------------------------|---------|-----------|--------|-----|-------|------|----------|------|------|
| Methyl magnesium bromide | 75-16-1 | 200-844-1 | ı | ı | - | X | - | Χ | X |
| Ethyl ether | 60-29-7 | 200-467-2 | - | - | X | X | KE-27690 | Х | X |

| Component | CAS No | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|--------------------------|---------|------|---|-----|------|------|-------|-------|
| Methyl magnesium bromide | 75-16-1 | X | ACTIVE | - | Х | - | Х | X |
| Ethyl ether | 60-29-7 | Х | ACTIVE | Х | - | Х | Х | Х |

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Not applicable

| Component | CAS No | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|--------------------------|---------|---|---|---|
| Methyl magnesium bromide | 75-16-1 | - | - | - |
| Ethyl ether | 60-29-7 | - | - | - |

Seveso III Directive (2012/18/EC)

| Component | CAS No | Seveso III Directive (2012/18/EC) - | Seveso III Directive (2012/18/EC) - | |
|--------------------------|---------|--|---|--|
| | | Qualifying Quantities for Major Accident | Qualifying Quantities for Safety Report | |
| | | Notification | Requirements | |
| Methyl magnesium bromide | 75-16-1 | Not applicable | Not applicable | |
| Ethyl ether | 60-29-7 | Not applicable | Not applicable | |

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

| Component | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|--------------------------|---------------------------------------|-------------------------|
| Methyl magnesium bromide | WGK1 | |
| Ethyl ether | WGK1 | |

| Component | France - INRS (Tables of occupational diseases) | | |
|-------------|--|--|--|
| Ethyl ether | Tableaux des maladies professionnelles (TMP) - RG 84 | | |

| Component | Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81) | Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC) | Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure |
|-------------------------------|--|---|--|
| Ethyl ether 60-29-7 (65) | | Group I | |

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H224 - Extremely flammable liquid and vapor

H225 - Highly flammable liquid and vapor

H260 - In contact with water releases flammable gases which may ignite spontaneously

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

EUH014 - Reacts violently with water

EUH019 - May form explosive peroxides

EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances Substances List

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

Methylmagnesium bromide, 3M solution in diethyl ether

Revision Date 09-Feb-2024

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

PBT - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARROL International Convention for the Provention of Pollution from the P

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards
Health Hazards
Calculation method
Environmental hazards
Cn basis of test data
Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Creation Date21-May-2012Revision Date09-Feb-2024Revision SummaryNot applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet