

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 27-Jan-2010 Revision Date 22-Sep-2023 Revision Number 13

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description: <u>Dichloromethane</u>

Cat No.: 113460000; 113460010; 113460025; 113460050; 113460051; 113460100; 113460250;

113460251

Synonyms Dichloromethane; DCM

 Index No
 602-004-00-3

 CAS No
 75-09-2

 EC No
 200-838-9

 Molecular Formula
 C H2 Cl2

REACH registration number 01-2119480404-41

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use**Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU5 - Manufacture of textiles, leather, fur

SU8 - Manufacture of bulk, large scale chemicals (including petroleum products)

SU9 - Manufacture of fine chemicals

SU10 - Formulation [mixing] of preparations and/or re-packaging (excluding alloys) SU22 - Professional uses: Public domain (administration, education, entertainment,

services, craftsmen)

SU24 - Scientific research and development

Product category PC21 - Laboratory chemicals

**Process categories** PROC15 - Use as a laboratory reagent

see SECTION 16 for a complete list of uses for which an exposure scenario is provided as

an annex

Environmental release category ERC1 - Manufacture of substances

ERC2 - Formulation of preparations

ERC4 - Industrial use of processing aids in processes and products, not becoming part of

articles

ERC8a - Wide dispersive indoor use of processing aids in open systems

**Uses advised against** SU21 - Consumer uses: Private households (= general public = consumers)

REACH Annex XVII Restriction - refer to SECTION 15

#### 1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name** Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11

ACD11246

Revision Date 22-Sep-2023

Emergency Number **US:**001-201-796-7100 / **Europe:** +32 14 57 52 99 **CHEMTREC** Tel. No. **US:**001-800-424-9300 / **Europe:**001-703-527-3887

## **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

#### CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

#### **Physical hazards**

Based on available data, the classification criteria are not met

#### **Health hazards**

Skin Corrosion/IrritationCategory 2 (H315)Serious Eye Damage/Eye IrritationCategory 2 (H319)CarcinogenicityCategory 2 (H351)Specific target organ toxicity - (single exposure)Category 3 (H336)

#### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16





## **Signal Word**

#### Warning

#### **Hazard Statements**

- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness
- H351 Suspected of causing cancer

#### **Precautionary Statements**

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P337 + P313 - If eye irritation persists: Get medical advice/attention

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 - Call a POISON CENTER or doctor if you feel unwell

P280 - Wear protective gloves/protective clothing/eye protection/face protection

#### 2.3. Other hazards

Dichloromethane Revision Date 22-Sep-2023

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB) Causes formation of carbon monoxide in the blood. Carbon monoxide may cause adverse effects on the cardiovascular system and the central nervous system

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Methylene chloride	75-09-2	EEC No. 200-838-9	>99.5	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H336) Carc. 2 (H351)

#### Note

Stabilised with Amylene (CAS 513-35-9)

REACH registration number 01-2119480404-41
--

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

**General Advice** If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

**Self-Protection of the First Aider** Use personal protective equipment as required.

#### 4.2. Most important symptoms and effects, both acute and delayed

. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression: Continued or high exposures by inhalation will cause anaesthetic effects. This may result in a loss of consciousness and could prove fatal: Causes formation of carbon monoxide in the blood. Carbon monoxide may cause adverse effects on the cardiovascular system and the central nervous system

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Revision Date 22-Sep-2023

### **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

### Extinguishing media which must not be used for safety reasons

No information available.

#### 5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO2), Phosgene, Hydrogen chloride gas.

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Avoid breathing vapors or mists. Wear respiratory protection.

#### 6.2. Environmental precautions

Should not be released into the environment.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

### **SECTION 7: HANDLING AND STORAGE**

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Vapors are heavier than air and may spread along floors. Handle product only in closed system or provide appropriate exhaust ventilation. Reacts with aluminum and its alloys.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

#### 7.2. Conditions for safe storage, including any incompatibilities

\_\_\_\_\_

## Dichloromethane Revision Date 22-Sep-2023

Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store in aluminum containers.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany) Class 6.1D

### 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

#### **Exposure limits**

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methylene chloride	STEL: 200 ppm 15 min	TWA: 353 mg/m <sup>3</sup> (15min)	TWA: 100 ppm 8 hr.
	STEL: 706 mg/m <sup>3</sup> 15 min	TWA: 100 ppm (15min)	TWA: 353 mg/m <sup>3</sup> 8 hr.
	TWA: 353 mg/m <sup>3</sup> 8 hr	STEL: 706 mg/m <sup>3</sup> (8h)	STEL: 200 ppm 15 min
	TWA: 100 ppm 8 hr	STEL: 200 ppm (8h)	STEL: 706 mg/m <sup>3</sup> 15 min
	Skin	Skin	Skin

#### **Biological limit values**

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

	Component	United Kingdom	European Union
Γ	Methylene chloride	Carbon monoxide: 30 ppm end-tidal breath	
1		post shift	

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methylene chloride				DNEL = 12mg/kg
75-09-2 ( >99.5 )				bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methylene chloride 75-09-2 ( >99.5 )		$DMEL = 132.14 mg/m^3$		DNEL = 176mg/m <sup>3</sup>

#### **Predicted No Effect Concentration (PNEC)**

Predicted No Effect Concentration (PNEC). See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methylene chloride	PNEC = 130µg/L	PNEC = 163µg/kg	PNEC = 0.27mg/L	PNEC = 26mg/L	PNEC = 173µg/kg
75-09-2 ( >99.5 )	PNEC = 0.31mg/L	sediment dw			soil dw
	-	PNEC = 2.57mg/kg			PNEC = 0.33mg/kg
		sediment dw			soil dw

	Component	Marine water	Marine water	Marine water	Food chain	Air
--	-----------	--------------	--------------	--------------	------------	-----

Dichloromethane Revision Date 22-Sep-2023

		sediment	intermittent	
Methylene chloride	PNEC = 130µg/L	PNEC = 163µg/kg	PNEC = 0.027mg/L	
75-09-2 ( >99.5 )	PNEC = 0.031 mg/L	sediment dw		
		PNEC = 0.26mg/kg		
		sediment dw		

#### 8.2. Exposure controls

#### **Engineering Measures**

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers	-	EN 374	(minimum requirement)
	recommendations			

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

EN371

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** No information available.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless
Odor sweet

Odor Threshold No data available

Dichloromethane Revision Date 22-Sep-2023

-97 °C / -142.6 °F Melting Point/Range **Softening Point** No data available 39 °C / 102.2 °F **Boiling Point/Range** Flammability (liquid) No data available Flammability (solid,gas)

Not applicable Liquid

**Explosion Limits** Lower 13 vol% Upper 22 vol%

**Flash Point** No information available

Method - No information available 556 - °C / 1032.8 - °F

**Autoignition Temperature** No data available **Decomposition Temperature** No information available Hq Viscosity 0.42 mPas @ 25°C Water Solubility 20 g/L (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow Methylene chloride 1.25

350 mbar @ 20°C **Vapor Pressure** 

**Density / Specific Gravity** 1.33

**Bulk Density** Not applicable Liquid 2.93 (Air = 1.0)(Air = 1.0)Vapor Density **Particle characteristics** Not applicable (liquid)

9.2. Other information

**Molecular Formula** C H2 Cl2 **Molecular Weight** 84.93

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity None known, based on information available

10.2. Chemical stability

Stable under normal conditions. Decomposes on exposure to light.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur. **Hazardous Polymerization Hazardous Reactions** Forms a detonable mixture with nitric acid.

10.4. Conditions to avoid

Excess heat. Protect from direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Amines.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Phosgene. Hydrogen chloride gas.

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

Dichloromethane Revision Date 22-Sep-2023

(a) acute toxicity:

Oral Based on available data, the classification criteria are not met **Dermal** Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met Inhalation

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methylene chloride	> 2000 mg/kg (Rat)	> 2000 mg/kg ( Rat )	53 mg/L ( Rat ) 6 h
			76000 mg/m³ (Rat) 4 h

Category 2 (b) skin corrosion/irritation;

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory Skin

Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Mutagenic effects have occured in microorganisms

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Methylene chloride				Group 2A

Based on available data, the classification criteria are not met (g) reproductive toxicity;

Category 3 (h) STOT-single exposure:

Results / Target organs Central nervous system (CNS).

Based on available data, the classification criteria are not met (i) STOT-repeated exposure;

**Target Organs** None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Other Adverse Effects Tumorigenic effects have been reported in experimental animals.

delayed

Symptoms / effects, both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Causes central nervous system depression. Continued or high exposures by inhalation will cause anaesthetic effects. This may result in a loss of consciousness and could prove fatal. Causes formation of carbon monoxide in the blood. Carbon monoxide may cause adverse effects on the cardiovascular system and the central nervous system.

11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

Dichloromethane Revision Date 22-Sep-2023

# 12.1. Toxicity Ecotoxicity effects

cotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methylene chloride	Pimephales promelas: LC50:193	EC50: 140 mg/L/48h	EC50:>660 mg/L/96h
	mg/L/96h		

Component	Microtox	M-Factor
Methylene chloride	EC50: 1 mg/L/24 h	
·	EC50: 2.88 mg/L/15 min	

#### 12.2. Persistence and degradability

**Persistence** Persistence is unlikely, based on information available.

#### 12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methylene chloride	1.25	6.4 - 40 dimensionless

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** 

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not empty into drains.

## **SECTION 14: TRANSPORT INFORMATION**

Dichloromethane Revision Date 22-Sep-2023

#### IMDG/IMO

**14.1. UN number** UN1593

14.2. UN proper shipping name Dichloromethane

14.3. Transport hazard class(es) 6.1 14.4. Packing group III

#### ADR

**14.1. UN number** UN1593

14.2. UN proper shipping name Dichloromethane

14.3. Transport hazard class(es) 6.1 14.4. Packing group III

### IATA

**14.1. UN number** UN1593

**14.2. UN proper shipping name** Dichloromethane

**14.3. Transport hazard class(es)** 6.1 **14.4. Packing group** III

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk Not applicable, packaged goods

according to IMO instruments

## **SECTION 15: REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **International Inventories**

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methylene chloride	75-09-2	200-838-9	-	-	X	X	KE-23893	Χ	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methylene chloride	75-09-2	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methylene chloride	75-09-2	-	Use restricted. See item 59. (see link for restriction details) Use restricted. See item	-

#### Dichloromethane Revision Date 22-Sep-2023

	75.	
	(see link for restriction	
	details)	

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report
		Notification	Requirements
Methylene chloride	75-09-2	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

#### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methylene chloride	WGK2	Class I: 20 mg/m³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Methylene chloride	Tableaux des maladies professionnelles (TMP) - RG 12

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methylene chloride 75-09-2 ( >99.5 )	Persistent Organic Pollutants (POPs) Prohibited and Restricted Substances	Group I	

#### 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted

SECTION 16: OTHER INFORMATION
-------------------------------

Dichloromethane Revision Date 22-Sep-2023

#### Full text of H-Statements referred to under sections 2 and 3

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

Inventory

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

#### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

**Creation Date** 27-Jan-2010 **Revision Date** 22-Sep-2023 Not applicable. **Revision Summary** 

## This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**

## Annex to the Safety Data Sheet according to Regulation (EC) No 1907/2006 [REACH]

## **Dichloromethane - Exposure Scenarios**

CAS No	REACH registration number	EC No
75-09-2	01-2119480404-41-xxxx	200-838-9

	Exposure	Scenarios Overv	view	
Title	Sector of use	Process category(ies)	Environmental release category	ES Identifier
Manufacture, Recycling and Distribution (Industrial)	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU8 - Manufacture of bulk, large scale chemicals (including petroleum products) SU9 - Manufacture of fine chemicals	1, 2, 3, 4, 8a, 8b, 9	ERC1 - Manufacture of substances	ES1-M1 DCM
Use as a process solvent / extraction medium	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU5 - Manufacture of textiles, leather, fur SU9 - Manufacture of fine chemicals	1, 2, 3, 4, 10, 15	ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles	ES2-M2 DCM
Formulation of preparations and/or re-packaging	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU10 - Formulation [mixing] of preparations and/or re-packaging (excluding alloys)	3, 4, 5, 8a, 8b, 9, 15	ERC2 - Formulation of preparations	ES4-F1 DCM
Laboratory use	SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) SU24 - Scientific research and development	10, 15	ERC8a - Wide dispersive indoor use of processing aids in open systems	ES5-L1 DCM

## **Exposure scenario**

Methylene chloride - ES1-M1 DCM

## Section 1 - Identification of the use

Main user group Industrial use

Type Worker

Processes, tasks, activities covered Manufacture; Includes recycling / recovery; Loading (including marine vessel/barge,

rail/road car and IBC loading) and repacking (including drums and small packs) of

substance, including its sampling, storage, unloading distribution and associated laboratory

activities

Sector(s) of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

ES1-M1 DCM Page 13/32

Methylene chloride Revision Date 19-Sep-2019

SU9 - Manufacture of fine chemicals

PROC1 - Use in closed process, no likelihood of exposure Process category(ies)

PROC2 - Use in closed, continuous process with occasional controlled exposure

SU8 - Manufacture of bulk, large scale chemicals (including petroleum products)

PROC3 - Use in closed batch process (synthesis or formulation)

PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a - Transfer of substance or preparation (charging/discharging) from/to

vessels/large containers at non dedicated facilities

PROC8b - Transfer of substance or preparation (charging/discharging) from/to

vessels/large containers at dedicated facilities

PROC9 - Transfer of substance or preparation into small containers (dedicated filling line,

including weighing)

PROC15 - Use as laboratory reagent

Environmental release category(ies) ERC1 - Manufacture of substances

## Section 2 - Operational Conditions and Risk Management Measures

Product characteristics

**Physical State** Liquid

pН No information available

**Water Solubility** Partially miscible; 13.2 g/L @ 25 °C

**Vapor Pressure** 325 mmHg @ 20°C

Volatility Hiah

Covers concentrations up to 100 %

## Section 2.1 - Control of environmental exposure

#### Environmental release category(ies)

ERC1 - Manufacture of substances

#### Control of environmental exposure

Readily biodegradable

Annual amount used in the EU 103000 t/a Annual amount per site 25700 t/a

### Environmental factors not influenced by risk management

**Emission days** 300

Receiving water dilution (fresh or marine) 18000 m3/d

#### Other operational conditions of use affecting environmental exposure

Emission days 300 (from ESVOC SPERC 1.1.v1)

Release fraction to air from process (initial 0.0000596

release prior to RMM)

Release fraction to wastewater from 0.0000369

process (initial release prior to RMM)

Release fraction to soil from process (initial 0.0

release prior to RMM)

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Negligible air emissions as process operates in a contained system.

Additional good practice advice beyond the REACH Chemical Safety Report

Bund storage facilities to prevent soil and water pollution in the event of spillage. Ensure all waste water is collected and treated via a WWTP.

#### Conditions and measures related to municipal sewage treatment plant

Remarks Manufacturing plants will have on-site waste water treatment facilities and emission to the municipal

STP will not occur.

Waste management

No discharge. No air emission controls required. Air

Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency

of 93.5%

ES1-M1 DCM Page 14/32 Conditions and measures related to external treatment of waste for disposal

Disposal Waste resulting from on-site RMM to be disposed as chemical waste

Waste treatment methods Hazardous waste incineration

## Section 2.2 - Control of worker exposure

#### General information on risk management related to physicochemical hazard

Keep equipment under negative pressure. Segregate work area and mark with appropriate signs in accordance with local/regional/national legislation.

### General information on exposure estimation

Manufactured and processed at industrial sites in closed continuous processes with either no likelihood of exposure or with only occasional opportunity for exposure in contolled conditions e.g. during maintenance, sampling or discharge of the material. Transfer of the substance is conducted at dedicated facilities using a closed-system with vapour return. Respiratory protection is not required except for certain critical activities where respiratory protective equipment is used, for example, cleaning tanks or reactors. Measured dermal exposure data are not available.

#### Control of worker exposure

Process category(ies) PROC1 - Use in closed process, no likelihood of exposure

Covers concentrations up to 100% >1000 t/v Amounts used Exposure duration < 8h hour(s) Use frequency 220 days per year Indoor/Outdoor use Indoor

Assumes process temperature up to

Organisational measures to prevent /limit releases, dispersion and

exposure

Handle substance within a closed system Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop

Technical conditions and measures to Undertake operation under enclosed conditions

<=40°C

control dispersion from source towards

the worker

Conditions and measures related to personal protection, hygiene and

health evaluation

Use eve protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are the REACH Chemical Safety Report well-trained in these procedures as well as good industrial hygiene practices

Process category(ies) PROC2 - Use in closed, continuous process with occasional controlled exposure

Covers concentrations up to 100% Exposure duration < 8h hour(s) Indoor/Outdoor use Indoor Assumes process temperature up to <=40°C

Organisational measures to prevent /limit releases, dispersion and

exposure

Handle substance within a closed system Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize

exposures and to report any skin problems that may develop

Conditions and measures related to personal protection, hygiene and

health evaluation

Wear a respirator providing a minimum efficiency of 90% (APF 10) Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant

gloves (tested to EN374) in combination with specific activity training

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are the REACH Chemical Safety Report well-trained in these procedures as well as good industrial hygiene practices

Process category(ies) PROC3 - Use in closed batch process (synthesis or formulation)

Covers concentrations up to Exposure duration < 8 hour(s) Indoor/Outdoor use Indoor Assumes process temperature up to <=40°C

Organisational measures to prevent Handle substance within a predominantly closed system provided with extract ventilation

ES1-M1 DCM Page 15/32 /limit releases, dispersion and Avoid direct skin contact with product. Identify potential areas for indirect skin contact.

Wear gloves (tested to EN374) if hand contact with substance likely. Clean up exposure

contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin

problems that may develop

Conditions and measures related to Use eve protection according to EN 166, designed to protect against liquid splashes Wear personal protection, hygiene and chemically resistant gloves (tested to EN374) in combination with specific activity training health evaluation Wear a respirator providing a minimum efficiency of 90% (APF 10)

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are the REACH Chemical Safety Report well-trained in these procedures as well as good industrial hygiene practices

Process category(ies) Covers concentrations up to

Exposure duration Indoor/Outdoor use Assumes process temperature up to Organisational measures to prevent

/limit releases, dispersion and exposure

Conditions and measures related to personal protection, hygiene and health evaluation

the REACH Chemical Safety Report

PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises 100%

< 8h hour(s) Indoor <=40°C

Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop

Use eye protection according to EN 166, designed to protect against liquid splashes Wear a respirator providing a minimum efficiency of 90% (APF 10) Wear chemically resistant

gloves (tested to EN374) in combination with specific activity training

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices

Process category(ies)

100% Covers concentrations up to Exposure duration Indoor/Outdoor use Assumes process temperature up to

Organisational measures to prevent /limit releases, dispersion and

exposure

Conditions and measures related to personal protection, hygiene and health evaluation

PROC8a - Transfer of substance or preparation (charging/discharging) from/to

vessels/large containers at non dedicated facilities

< 1 hour(s) Indoor <=40°C

Drain or remove substance from equipment prior to break-in or maintenance Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop Use eve protection according to EN 166, designed to protect against liquid splashes

Wear a respirator providing a minimum efficiency of 95% (APF 20)

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training

Additional good practice advice beyondAssumes a good basic standard of occupational hygiene is implemented the REACH Chemical Safety Report

Process category(ies)

PROC8b - Transfer of substance or preparation (charging/discharging) from/to

vessels/large containers at dedicated facilities

Covers concentrations up to 100% Exposure duration < 8h hour(s) Indoor/Outdoor use Indoor Assumes process temperature up to <=40°C

Organisational measures to prevent /limit releases, dispersion and

Conditions and measures related to

Fill containers/cans at dedicated fill points supplied with local extract ventilation Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training

Additional good practice advice beyondAssumes a good basic standard of occupational hygiene is implemented the REACH Chemical Safety Report

ES1-M1 DCM Page 16/32

exposure

personal protection, hygiene and

health evaluation

PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, Process category(ies)

> including weighing) 100%

< 8h hour(s)

Indoor

<=40°C

Covers concentrations up to Exposure duration

Indoor/Outdoor use Assumes process temperature up to Organisational measures to prevent

/limit releases, dispersion and exposure

Conditions and measures related to

personal protection, hygiene and health evaluation

Wear a respirator providing a minimum efficiency of 90% Additional good practice advice beyondAssumes a good basic standard of occupational hygiene is implemented

the REACH Chemical Safety Report

Process category(ies) PROC15 - Use as laboratory reagent

Covers concentrations up to 100% Exposure duration < 8h hour(s) Indoor/Outdoor use Indoor Assumes process temperature up to <=40°C

Organisational measures to prevent /limit releases, dispersion and

exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact.

Wear gloves (tested to EN374) if hand contact with substance likely. Clean up

contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin

Fill containers/cans at dedicated fill points supplied with local extract ventilation Avoid direct

skin contact with product. Identify potential areas for indirect skin contact. Wear gloves

(tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop Use eye protection according to EN 166, designed to protect against liquid splashes Wear

chemically resistant gloves (tested to EN374) in combination with specific activity training

problems that may develop

Conditions and measures related to personal protection, hygiene and

health evaluation

Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training

Additional good practice advice beyondAssumes a good basic standard of occupational hygiene is implemented the REACH Chemical Safety Report

Control of consumer exposure

Not intended for consumer use

## **Section 3 - Exposure estimation**

**Environment** 

Environmental release category(ies)

ERC1 - Manufacture of substances

#### Predicted No Effect Concentration (PNEC) - See values below

	Fresh water	0.31 mg/l	Marine water	0.031 mg/l
١	Fresh water sediment	2.57 mg/kg dw	Marine water sediment	0.26 mg/kg dw
-	Water Intermittent	0.27 mg/l	Soil (Agriculture)	0.33 mg/kg dw
-	Microorganisms in sewage	25.9 mg/l		

treatment

**Environment** Predicted exposure level Risk characterization ratio (RCR) Freshwater 5.17 x 10<sup>-3</sup> mg/l < 0.01 Marine water 9.3 x 10<sup>-3</sup> mg/l < 0.01 Freshwater sediment 4.16 x 10<sup>-4</sup> mg/kg dw < 0.01 7.49 x 10<sup>-4</sup> mg/kg dw Marine sediment < 0.01 1.26 x 10<sup>-4</sup> mg/kg dw Soil < 0.01

Calculation method - EUSES 2.1

No significant PEC values are indicated for the regional scale even under the conservative assumptions of the Tier 2 EUSES assessment. All derived PECs are below the relevant PNEC and so no further assessment or refinements are required.

ES1-M1 DCM Page 17/32

#### **Health**

Derived No Effect Level (DNEL) - See table for values

Route of exposure	Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
Oral				
Dermal				12 mg/kg bw/d
Inhalation	706 mg/m <sup>3</sup>		353 mg/m <sup>3</sup>	0 0

Process category(ies)	Exposure route	Predicted exposure level	Risk characterization ratio
PROC1 - Use in closed process, no	Worker - inhalative	0.01 ppm	( <b>RCR)</b> <0.01
likelihood of exposure	Worker - dermal	0.07 mg/kg bw/day	< 0.01
PROC2 - Use in closed, continuous process	Worker - inhalative	50 ppm	0.5
with occasional controlled exposure	Worker - dermal	0.27 mg/kg bw/day	< 0.01
PROC3 - Use in closed batch process	Worker - inhalative	10 ppm	0.1
(synthesis or formulation)	Worker - dermal	1.37 mg/kg bw/day	< 0.01
PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises	Worker - inhalative	10 ppm	0.1
	Worker - dermal	1.37 mg/kg bw/day	< 0.01
PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities	Worker - inhalative	50 ppm	0.5
racilities	Worker - dermal	2.74 mg/kg bw/day	< 0.01
PROC15 - Use as laboratory reagent	Worker - inhalative Worker - dermal	50 ppm 0.07 mg/kg bw/d	0.5 < 0.01

#### **Calculation method**

Used ECETOC TRA model

#### Remarks

Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented

## Section 4 - Guidance to check compliance with the exposure scenario

Used EUSES model

Used ECETOC TRA model

Further details on scaling and control technologies are provided in SpERC factsheet

(http://cefic.org/en/reach-for-industries-libraries.html)

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented

ECHA guidance for downstream users

ES1-M1 DCM Page 18/32

Methylene chloride Revision Date 19-Sep-2019

## Annex to the Safety Data Sheet according to Regulation (EC) No 1907/2006 [REACH]

## **Dichloromethane - Exposure Scenarios**

CAS No	REACH registration number	EC No
75-09-2	01-2119480404-41-xxxx	200-838-9

## **Exposure scenario**

Methylene chloride - ES2-M2 DCM

## Section 1 - Identification of the use

Main user group Industrial use

**Type** Worker

Processes, tasks, activities covered Use as a Process Solvent / Extraction Medium (Industrial)

Sector(s) of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU8 - Manufacture of bulk, large scale chemicals (including petroleum products)

SU9 - Manufacture of fine chemicals

Process category(ies) PROC1 - Use in closed process, no likelihood of exposure

PROC2 - Use in closed, continuous process with occasional controlled exposure

PROC3 - Use in closed batch process (synthesis or formulation)

PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises

PROC10 - Roller application or brushing PROC15 - Use as laboratory reagent

Environmental release category(ies) ERC4 - Industrial use of processing aids in processes and products, not becoming part of

articles

## **Section 2 - Operational Conditions and Risk Management Measures**

**Product characteristics** 

Physical State Liquid

**pH** No information available

Water Solubility Partially miscible; 13.2 g/L @ 25 °C

Vapor Pressure 325 mmHg @ 20°C

**Volatility** High

Covers concentrations up to 100 %

## Section 2.1 - Control of environmental exposure

#### Environmental release category(ies)

ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles

#### Control of environmental exposure

Readily biodegradable

Regional use tonnage 2410 t/a Annual amount per site 2410 t/a

ES2-M2 DCM Page 19 / 32

Methylene chloride Revision Date 19-Sep-2019

#### Environmental factors not influenced by risk management

100 **Emission days** 

Receiving water dilution (fresh or marine) 18000 m3/d

## Other operational conditions of use affecting environmental exposure

100 (from ESVOC SPERC 1.1.v1) Emission days

Release fraction to air from process (initial 0.669

release prior to RMM)

Release fraction to wastewater from 0.00154

process (initial release prior to RMM)

Release fraction to soil from process (initial 0.0

release prior to RMM)

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Negligible air emissions as process operates in a contained system.

Additional good practice advice beyond the REACH Chemical Safety Report

Bund storage facilities to prevent soil and water pollution in the event of spillage. Ensure all waste water is collected and treated via a WWTP.

#### Conditions and measures related to municipal sewage treatment plant

Remarks Manufacturing plants will have on-site waste water treatment facilities and emission to the municipal

STP will not occur.

Waste management

No discharge. No air emission controls required.

Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency

of 93.5%

#### Conditions and measures related to external treatment of waste for disposal

Disposal Waste resulting from on-site RMM to be disposed as chemical waste

Waste treatment methods Hazardous waste incineration

## Section 2.2 - Control of worker exposure

#### General information on risk management related to physicochemical hazard

Keep equipment under negative pressure. Segregate work area and mark with appropriate signs in accordance with local/regional/national legislation.

#### General information on exposure estimation

Manufactured and processed at industrial sites in closed continuous processes with either no likelihood of exposure or with only occasional opportunity for exposure in contolled conditions e.g. during maintenance, sampling or discharge of the material. Transfer of the substance is conducted at dedicated facilities using a closed-system with vapour return. Respiratory protection is not required except for certain critical activities where respiratory protective equipment is used, for example, cleaning tanks or reactors.

#### Control of worker exposure

Process category(ies) PROC1 - Use in closed process, no likelihood of exposure

Covers concentrations up to 100% Amounts used >1000 t/v **Exposure duration** < 8h hour(s) Use frequency 100 days per year

Indoor/Outdoor use Indoor Assumes process temperature up to <=40°C

Organisational measures to prevent

/limit releases, dispersion and exposure

Handle substance within a closed system Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize

exposures and to report any skin problems that may develop

Technical conditions and measures to Undertake operation under enclosed conditions

control dispersion from source towards

the worker

ES2-M2 DCM Page 20/32 Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity

the REACH Chemical Safety Report

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are

Use eye protection according to EN 166, designed to protect against liquid splashes

well-trained in these procedures as well as good industrial hygiene practices

PROC2 - Use in closed, continuous process with occasional controlled exposure

Process category(ies) Covers concentrations up to Exposure duration

100% < 8h hour(s) Indoor <=40°C

Indoor/Outdoor use Assumes process temperature up to Organisational measures to prevent /limit releases, dispersion and exposure

Conditions and measures related to personal protection, hygiene and

health evaluation

the REACH Chemical Safety Report

Handle substance within a closed system Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop

Wear a respirator providing a minimum efficiency of 90% (APF 10) Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices

Process category(ies) Covers concentrations up to

Exposure duration Indoor/Outdoor use Assumes process temperature up to

Organisational measures to prevent /limit releases, dispersion and

exposure

PROC3 - Use in closed batch process (synthesis or formulation)

100% < 8 hour(s) Indoor <=40°C

Handle substance within a predominantly closed system provided with extract ventilation Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop

Conditions and measures related to personal protection, hygiene and

health evaluation

Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Wear a respirator providing a minimum efficiency of 90% (APF 10)

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are the REACH Chemical Safety Report well-trained in these procedures as well as good industrial hygiene practices

Process category(ies) Covers concentrations up to Exposure duration Indoor/Outdoor use

Assumes process temperature up to Organisational measures to prevent /limit releases, dispersion and

exposure

health evaluation

Conditions and measures related to personal protection, hygiene and

the REACH Chemical Safety Report

PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises

100% < 8h hour(s) Indoor <=40°C

Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop

Use eye protection according to EN 166, designed to protect against liquid splashes Wear a respirator providing a minimum efficiency of 90% (APF 10) Wear chemically resistant

gloves (tested to EN374) in combination with specific activity training Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are

well-trained in these procedures as well as good industrial hygiene practices

Process category(ies) PROC10 - Roller application or brushing

Covers concentrations up to 100% Exposure duration < 8h hour(s) Indoor/Outdoor use Indoor Assumes process temperature up to

Organisational measures to prevent Provide extract ventilation to points where emissions occur Avoid direct skin contact with

ES2-M2 DCM Page 21/32

/limit releases, dispersion and	product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if
exposure	hand contact with substance likely. Clean up contamination/spills as soon as they occur.
	Wash off any skin contamination immediately. Provide basic employee training to prevent /
	minimize exposures and to report any skin problems that may develop
Technical conditions and measures to control dispersion from source towards	Provide extract ventilation to points where emissions occur
the worker	
Conditions and measures related to personal protection, hygiene and	Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training

health evaluation Additional good practice advice beyondAssumes a good basic standard of occupational hygiene is implemented

the REACH Chemical Safety Report

\_\_\_\_\_

Process category(ies) PROC15 - Use as laboratory reagent Covers concentrations up to 100% Exposure duration < 8h hour(s)

Indoor/Outdoor use Indoor Assumes process temperature up to <=40°C

Organisational measures to prevent /limit releases, dispersion and

exposure

Conditions and measures related to personal protection, hygiene and health evaluation

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up

contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop

Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Wear a respirator providing a minimum efficiency of 90%

Control of consumer exposure

Not intended for consumer use

## Section 3 - Exposure estimation

#### Environment

#### Environmental release category(ies)

ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles

### Predicted No Effect Concentration (PNEC) - See values below

Fresh water	0.31 mg/l	Marine water	0.031 mg/l
Fresh water sediment	2.57 mg/kg dw	Marine water sediment	0.26 mg/kg dw
Water Intermittent	0.27 mg/l	Soil (Agriculture)	0.33 mg/kg dw
Microorganisms in sewage	25.9 mg/l		
treatment			

<u>Environment</u>	Predicted exposure level	Risk characterization ratio (RCR)
Freshwater	5.17 x 10 <sup>-3</sup> mg/l	<0.01
Marine water	9.3 x 10 <sup>-3</sup> mg/l	<0.01
Freshwater sediment	4.16 x 10 <sup>-4</sup> mg/kg dw	<0.01
Marine sediment	7.49 x 10 <sup>-4</sup> mg/kg dw	<0.01
Soil	1.26 x 10 <sup>-4</sup> mg/kg dw	<0.01
Onlandation mothers. FUOTO 0.4	0 0	

Calculation method - EUSES 2.1

#### Remarks

No significant PEC values are indicated for the regional scale even under the conservative assumptions of the Tier 2 EUSES assessment. All derived PECs are below the relevant PNEC and so no further assessment or refinements are required.

#### **Health**

Derived No Effect Level (DNEL) - See table for values

	000 10010 101 10100			
Route of exposure	Acute effects (local)	Acute effects	Chronic effects	Chronic effects
		(systemic)	(local)	(systemic)
Oral				

ES2-M2 DCM Page 22/32

Dermal			12 mg/kg bw/d
Inhalation	706 mg/m <sup>3</sup>	353 mg/m <sup>3</sup>	

Process category(ies)	Exposure route	Predicted exposure level	Risk characterization ratio (RCR)
PROC1 - Use in closed process, no	Worker - inhalative	0.01 ppm	<0.01
likelihood of exposure	Worker - dermal	0.07 mg/kg bw/day	< 0.01
PROC2 - Use in closed, continuous process	Worker - inhalative	50 ppm	0.5
with occasional controlled exposure	Worker - dermal	0.27 mg/kg bw/day	< 0.01
PROC3 - Use in closed batch process	Worker - inhalative	10 ppm	0.1
(synthesis or formulation)	Worker - dermal	1.37 mg/kg bw/day	< 0.01
PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises	Worker - inhalative	10 ppm	0.1
	Worker - dermal	1.37 mg/kg bw/day	< 0.01
PROC10 - Roller application or brushing	Worker - inhalative Worker - dermal	25 ppm 5.49 mg/kg bw/d	0.25 < 0.01
PROC15 - Use as laboratory reagent	Worker - inhalative Worker - dermal	50 ppm 0.07 mg/kg bw/d	0.5 < 0.01

#### **Calculation method**

Used ECETOC TRA model

#### Remarks

Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented

## Section 4 - Guidance to check compliance with the exposure scenario

Used EUSES model

Used ECETOC TRA model

Further details on scaling and control technologies are provided in SpERC factsheet

(http://cefic.org/en/reach-for-industries-libraries.html)

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented

ECHA guidance for downstream users

ES2-M2 DCM Page 23/32

Methylene chloride Revision Date 19-Sep-2019

## Annex to the Safety Data Sheet according to Regulation (EC) No 1907/2006 [REACH]

## **Dichloromethane - Exposure Scenarios**

CAS No	REACH registration number	EC No
75-09-2	01-2119480404-41-xxxx	200-838-9

## **Exposure scenario**

Methylene chloride

- ES3-F1 DCM

## Section 1 - Identification of the use

Main user group Industrial use

**Type** Worker

Processes, tasks, activities covered Use as a Process Solvent / Extraction Medium (Industrial)

Sector(s) of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU10 - Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

PROC3 - Use in closed batch process (synthesis or formulation)

PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises PROC5 - Mixing or blending in batch processes for formulation of preparations and articles

(multistage and/or significant contact)

PROC8a - Transfer of substance or preparation (charging/discharging) from/to

vessels/large containers at non dedicated facilities

PROC8b - Transfer of substance or preparation (charging/discharging) from/to

vessels/large containers at dedicated facilities

PROC9 - Transfer of substance or preparation into small containers (dedicated filling line,

including weighing)

PROC15 - Use as laboratory reagent

Environmental release category(ies) ERC2 - Formulation of preparations (mixtures)

## **Section 2 - Operational Conditions and Risk Management Measures**

Product characteristics

Physical State Liquid

**pH** No information available

Water Solubility Partially miscible; 13.2 g/L @ 25 °C

Vapor Pressure 325 mmHg @ 20°C

**Volatility** High

Covers concentrations up to 100 %

## Section 2.1 - Control of environmental exposure

#### Environmental release category(ies)

ERC2 - Formulation of preparations (mixtures)

Control of environmental exposure

Readily biodegradable

Regional use tonnage 2810 t/a Annual amount per site 239 t/a

ES3-F1 DCM Page 24 / 32

Methylene chloride Revision Date 19-Sep-2019

#### Environmental factors not influenced by risk management

**Emission days** 300

Receiving water dilution (fresh or marine) 18000 m3/d

#### Other operational conditions of use affecting environmental exposure

Emission days 300 (from ESVOC SPERC 1.1.v1)

Release fraction to air from process (initial 0.025

release prior to RMM)

Release fraction to wastewater from 0.02 process (initial release prior to RMM)

Release fraction to soil from process (initial 0.0

release prior to RMM)

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Negligible air emissions as process operates in a contained system.

Additional good practice advice beyond the REACH Chemical Safety Report

Bund storage facilities to prevent soil and water pollution in the event of spillage. Ensure all waste water is collected and treated via a WWTP.

#### Conditions and measures related to municipal sewage treatment plant

Remarks Manufacturing plants will have on-site waste water treatment facilities and emission to the municipal

STP will not occur.

Waste management

Air No discharge. No air emission controls required.

Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency

#### Conditions and measures related to external treatment of waste for disposal

Waste resulting from on-site RMM to be disposed as chemical waste Disposal

Waste treatment methods Hazardous waste incineration

## Section 2.2 - Control of worker exposure

### General information on risk management related to physicochemical hazard

Keep equipment under negative pressure. Segregate work area and mark with appropriate signs in accordance with local/regional/national legislation.

#### General information on exposure estimation

Manufactured and processed at industrial sites in closed continuous processes with either no likelihood of exposure or with only occasional opportunity for exposure in contolled conditions e.g. during maintenance, sampling or discharge of the material. Transfer of the substance is conducted at dedicated facilities using a closed-system with vapour return. Respiratory protection is not required except for certain critical activities where respiratory protective equipment is used, for example, cleaning tanks or reactors. Measured dermal exposure data are not available.

#### Control of worker exposure

Process category(ies) PROC3 - Use in closed batch process (synthesis or formulation)

Covers concentrations up to 100%

Exposure duration >4 hours (default) Use frequency 300 days per year

Indoor/Outdoor use Indoor Assumes process temperature up to <=40°C

Organisational measures to prevent

/limit releases, dispersion and exposure

Conditions and measures related to

personal protection, hygiene and health evaluation

Handle substance within a predominantly closed system provided with extract ventilation Use of closed transfers of liquids from storage to production equipment (e.g. metered piped

or pumped additions) Sample via a closed loop or other system to avoid exposure Use eye protection according to EN 166, designed to protect against liquid splashes Wear

chemically resistant gloves (tested to EN374) in combination with specific activity training Wear a respirator providing a minimum efficiency of 90% (APF 10)

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are the REACH Chemical Safety Report well-trained in these procedures as well as good industrial hygiene practices

ES3-F1 DCM Page 25 / 32 Methylene chloride Revision Date 19-Sep-2019

Process category(ies) PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises

Covers concentrations up to Exposure duration >4 hours (default) Indoor/Outdoor use

Assumes process temperature up to Organisational measures to prevent /limit releases, dispersion and

exposure

Conditions and measures related to

personal protection, hygiene and health evaluation

the REACH Chemical Safety Report

100%

Indoor

<=40°C Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent /

minimize exposures and to report any skin problems that may develop

Use eye protection according to EN 166, designed to protect against liquid splashes Wear a respirator providing a minimum efficiency of 90% (APF 10) Wear chemically resistant

gloves (tested to EN374) in combination with specific activity training

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are well-trained in these procedures as well as good industrial hygiene practices

Process category(ies)

PROC8a - Transfer of substance or preparation (charging/discharging) from/to

vessels/large containers at non dedicated facilities

Covers concentrations up to 100%

Exposure duration >4 hours (default) Indoor/Outdoor use Indoor

Assumes process temperature up to Organisational measures to prevent /limit releases, dispersion and

exposure

<=40°C Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent /

minimize exposures and to report any skin problems that may develop Use eye protection according to EN 166, designed to protect against liquid splashes

Conditions and measures related to personal protection, hygiene and Wear a respirator providing a minimum efficiency of 95% (APF 20)

Wear chemically resistant gloves (tested to EN374) in combination with specific activity

training

health evaluation

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are the REACH Chemical Safety Report well-trained in these procedures as well as good industrial hygiene practices

Process category(ies)

PROC8b - Transfer of substance or preparation (charging/discharging) from/to

vessels/large containers at dedicated facilities

Covers concentrations up to 100%

Exposure duration >4 hours (default) Indoor/Outdoor use Indoor

Assumes process temperature up to Organisational measures to prevent /limit releases, dispersion and

exposure

<=40°C Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop

Process category(ies)

PROC9 - Transfer of substance or preparation into small containers (dedicated filling line,

including weighing) 100%

Covers concentrations up to

Exposure duration

Indoor/Outdoor use Assumes process temperature up to Organisational measures to prevent /limit releases, dispersion and

exposure

>4 hours (default) Indoor

<=40°C

Fill containers/cans at dedicated fill points supplied with local extract ventilation Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin problems that may develop

Technical conditions and measures to Provide extract ventilation to points where emissions occur control dispersion from source towards

the worker

Conditions and measures related to personal protection, hygiene and health evaluation

Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training

ES3-F1 DCM Page 26/32

Additional good practice advice beyondWorkers involved in production, handling, sampling and transfer of materials are the REACH Chemical Safety Report well-trained in these procedures as well as good industrial hygiene practices

.

Process category(ies) PROC15 - Use as laboratory reagent

Covers concentrations up to 100%

Exposure duration >4 hours (default)
Indoor/Outdoor use Indoor
Assumes process temperature up to <=40°C

Assumes process temperature up to Organisational measures to prevent

/limit releases, dispersion and

exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up

contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin

problems that may develop

Conditions and measures related to personal protection, hygiene and

health evaluation

Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training Wear a respirator providing a minimum efficiency of 90%

vvoar a respirator providing a minimum

Control of consumer exposure

Not intended for consumer use

## **Section 3 - Exposure estimation**

#### Environment

#### Environmental release category(ies)

ERC2 - Formulation of preparations (mixtures)

### Predicted No Effect Concentration (PNEC) - See values below

Fresh water	0.31 mg/l	Marine water	0.031 mg/l
Fresh water sediment	2.57 mg/kg dw	Marine water sediment	0.26 mg/kg dw
Water Intermittent	0.27 mg/l	Soil (Agriculture)	0.33 mg/kg dw
Microorganisms in sewage	25.9 mg/l		
treatment	-		

Environment Predicted exposure level Risk characterization ratio (RCR) Freshwater 5.17 x 10<sup>-3</sup> mg/l < 0.01 9.3 x 10<sup>-3</sup> mg/l < 0.01 Marine water Freshwater sediment 4.16 x 10<sup>-4</sup> mg/kg dw < 0.01 Marine sediment 7.49 x 10<sup>-4</sup> mg/kg dw < 0.01 1.26 x 10<sup>-4</sup> mg/kg dw < 0.01 Soil Calculation method - EUSES 2.1

#### Remarks

No significant PEC values are indicated for the regional scale even under the conservative assumptions of the Tier 2 EUSES assessment. All derived PECs are below the relevant PNEC and so no further assessment or refinements are required.

#### **Health**

Derived No Effect Level (DNEL) - See table for values

Route of exposure	Acute effects (local)	Acute effects	Chronic effects	Chronic effects
		(systemic)	(local)	(systemic)
Oral				
Dermal				12 mg/kg bw/d
Inhalation	706 mg/m <sup>3</sup>		353 mg/m <sup>3</sup>	

Process category(ies)	Exposure route	Predicted exposure level	Risk characterization ratio (RCR)
PROC3 - Use in closed batch process (synthesis or formulation)	Worker - inhalative	10 ppm	0.1
(Synthosis of formulation)	Worker - dermal	0.07 mg/kg bw/day	< 0.01
PROC4 - Use in batch and other process	Worker - inhalative	10 ppm	0.1

ES3-F1 DCM Page 27 / 32

(synthesis) where opportunity for exposure arises			
	Worker - dermal	1.37 mg/kg bw/day	< 0.01
PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities	Worker - inhalative	25 ppm	0.3
	Worker - dermal	2.74 mg/kg bw/day	< 0.01
PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities	Worker - inhalative	4.5 mg/m³	0.05
	Worker - dermal	1.37 mg/kg bw/day	< 0.01
PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	Worker - inhalative	20 mg/m³	0.2
3 7 3 3 37	Worker - dermal	1.37 mg/kg bw/day	< 0.01
PROC15 - Use as laboratory reagent	Worker - inhalative	50 ppm	0.5
	Worker - dermal	0.07 mg/kg bw/d	< 0.01

#### **Calculation method**

Used ECETOC TRA model

#### Remarks

Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented

## Section 4 - Guidance to check compliance with the exposure scenario

Used EUSES model

Used ECETOC TRA model

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html)

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented ECHA guidance for downstream users

ES3-F1 DCM Page 28 / 32

Methylene chloride Revision Date 19-Sep-2019

## Annex to the Safety Data Sheet according to Regulation (EC) No 1907/2006 [REACH]

## **Dichloromethane - Exposure Scenarios**

CAS No	REACH registration number	EC No
75-09-2	01-2119480404-41-xxxx	200-838-9

## **Exposure scenario**

Methylene chloride

- ES4-L1 DCM

## Section 1 - Identification of the use

Main user group Industrial use

**Type** Worker

Processes, tasks, activities covered Laboratory use (Professional)

Sector(s) of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU10 - Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

Process category(ies) PROC10 - Roller application or brushing

PROC15 - Use as laboratory reagent

Environmental release category(ies) ERC8a - Wide dispersive indoor use of processing aids in open systems

### Section 2 - Operational Conditions and Risk Management Measures

**Product characteristics** 

Physical State Liquid

**pH** No information available

Water Solubility Partially miscible; 13.2 g/L @ 25 °C

Vapor Pressure 325 mmHg @ 20°C

**Volatility** High

Covers concentrations up to 100 %

## Section 2.1 - Control of environmental exposure

### Environmental release category(ies)

ERC8a - Wide dispersive indoor use of processing aids in open systems

#### Control of environmental exposure

Readily biodegradable

Regional use tonnage 257 t/a Annual amount per site 257 t/a

#### Environmental factors not influenced by risk management

Emission days 300

Receiving water dilution (fresh or marine) 18000 m3/d

### Other operational conditions of use affecting environmental exposure

Emission days 300 (from ESVOC SPERC 1.1.v1)

Release fraction to air from process (initial 0.5

release prior to RMM)

ES4-L1 DCM Page 29 / 32

Release fraction to wastewater from 0.5 process (initial release prior to RMM) Release fraction to soil from process (initial 0.0

release prior to RMM)

## Technical onsite conditions and measures to reduce or limit discharges, air emissions

Technical onsite conditions and measures to reduce or limit discharges, air emissions

Negligible air emissions as process operates in a contained system.

Additional good practice advice beyond the REACH Chemical Safety Report

Bund storage facilities to prevent soil and water pollution in the event of spillage. Ensure all waste water is collected and treated via a WWTP.

#### Conditions and measures related to municipal sewage treatment plant

Manufacturing plants will have on-site waste water treatment facilities and emission to the municipal Remarks

STP will not occur.

Waste management

No discharge. No air emission controls required. Air

Water Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency

of 93.5%

#### Conditions and measures related to external treatment of waste for disposal

Disposal Waste resulting from on-site RMM to be disposed as chemical waste

Waste treatment methods Hazardous waste incineration

## Section 2.2 - Control of worker exposure

#### General information on risk management related to physicochemical hazard

Keep equipment under negative pressure. Segregate work area and mark with appropriate signs in accordance with local/regional/national legislation.

#### General information on exposure estimation

Manufactured and processed at industrial sites in closed continuous processes with either no likelihood of exposure or with only occasional opportunity for exposure in contolled conditions e.g. during maintenance, sampling or discharge of the material. Transfer of the substance is conducted at dedicated facilities using a closed-system with vapour return. Respiratory protection is not required except for certain critical activities where respiratory protective equipment is used, for example, cleaning tanks or reactors. Measured dermal exposure data are not available.

#### Control of worker exposure

Process category(ies) PROC15 - Use as laboratory reagent

Covers concentrations up to 100%

Exposure duration >4 hours (default) Use frequency 300 days per year

Indoor/Outdoor use Indoor Assumes process temperature up to <=40°C

Organisational measures to prevent

/limit releases, dispersion and

exposure

Avoid direct skin contact with product. Identify potential areas for indirect skin contact.

Wear gloves (tested to EN374) if hand contact with substance likely. Clean up

contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimize exposures and to report any skin

problems that may develop

Conditions and measures related to personal protection, hygiene and

health evaluation

Use eye protection according to EN 166, designed to protect against liquid splashes Wear chemically resistant gloves (tested to EN374) in combination with specific activity training

Wear a respirator providing a minimum efficiency of 90%

Process category(ies) PROC10 - Roller application or brushing

Covers concentrations up to

Exposure duration Avoid carrying out activities involving exposure for more than 4 hours

Use frequency

Indoor/Outdoor use Assumes process temperature up to <=40°C

Organisational measures to prevent /limit releases, dispersion and

exposure

300 days per year Indoor

Provide extract ventilation to points where emissions occur Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur.

ES4-L1 DCM Page 30/32 Methylene chloride Revision Date 19-Sep-2019

minimize exposures and to report any skin problems that may develop

Wash off any skin contamination immediately. Provide basic employee training to prevent /

Control of consumer exposure

Not intended for consumer use

## **Section 3 - Exposure estimation**

#### **Environment**

#### Environmental release category(ies)

ERC8a - Wide dispersive indoor use of processing aids in open systems

#### Predicted No Effect Concentration (PNEC) - See values below

	Fresh water	0.31 mg/l	Marine water	0.031 mg/l
	Fresh water sediment	2.57 mg/kg dw	Marine water sediment	0.26 mg/kg dw
	Water Intermittent	0.27 mg/l	Soil (Agriculture)	0.33 mg/kg dw
	Microorganisms in sewage	25.9 mg/l		
L	treatment			

Environment	Predicted exposure level	Risk characterization ratio (RCR)
Freshwater	5.17 x 10 <sup>-3</sup> mg/l	<0.01
Marine water	9.3 x 10 <sup>-3</sup> mg/l	<0.01
Freshwater sediment	4.16 x 10 <sup>-4</sup> mg/kg dw	<0.01
Marine sediment	7.49 x 10 <sup>-4</sup> mg/kg dw	<0.01
Soil	1.26 x 10 <sup>-4</sup> mg/kg dw	<0.01

Calculation method - EUSES 2.1

#### Remarks

No significant PEC values are indicated for the regional scale even under the conservative assumptions of the Tier 2 EUSES assessment. All derived PECs are below the relevant PNEC and so no further assessment or refinements are required.

#### **Health**

Derived No Effect Level (DNEL) - See table for values

Bontoa No Encot Ecter (BNEE)	Ood table for values			
Route of exposure	Acute effects (local)	Acute effects	Chronic effects	Chronic effects
		(systemic)	(local)	(systemic)
Oral				
Dermal				12 mg/kg bw/d
Inhalation	706 mg/m <sup>3</sup>		353 mg/m <sup>3</sup>	

Process category(ies)	Exposure route	Predicted exposure level	Risk characterization ratio (RCR)
PROC10 - Roller application or brushing	Worker - inhalative	60 ppm	0.6
	Worker - dermal	5.49 mg/kg bw/d	< 0.01
PROC15 - Use as laboratory reagent	Worker - inhalative	50 ppm	0.5
	Worker - dermal	0.07 mg/kg bw/d	< 0.01

Calculation method Used ECETOC TRA model

#### Remarks

Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented

## Section 4 - Guidance to check compliance with the exposure scenario

Used EUSES model

Used ECETOC TRA model

Further details on scaling and control technologies are provided in SpERC factsheet

ES4-L1 DCM Page 31 / 32

(http://cefic.org/en/reach-for-industries-libraries.html)

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented ECHA guidance for downstream users

ES4-L1 DCM Page 32/32