

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 25-Jun-2009 Revision Date 22-Sep-2023 Revision Number 9

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Sodium methoxide, 5.4M (30 wt.%) solution in methanol

Cat No.: 168600000; 168600010; 168600025; 168600100; 168600250; 168600251

Synonyms Sodium methylate

Unique Formula Identifier (UFI) WU70-Q3YD-GX0V-3DC5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

**UK entity/business name** Fisher Scientific UK

Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name** Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency information services

y Ireland : National Poisons Information Centre (NPIC) -

01 809 2166 (8am-10pm, 7 days a week)

Malta: +356 2395 2000 Cyprus: +357 2240 5611

## **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

**Physical hazards** 

Flammable liquids Category 3 (H226)

## Sodium methoxide, 5.4M (30 wt.%) solution in methanol

Revision Date 22-Sep-2023

Substances/mixtures corrosive to metal Category 1 (H290)

#### **Health hazards**

Acute oral toxicity

Acute dermal toxicity

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity - (single exposure)

Category 3 (H301)

Category 3 (H331)

Category 1 A (H314)

Category 1 (H318)

Category 1 (H370)

#### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



Signal Word

Danger

#### **Hazard Statements**

H226 - Flammable liquid and vapor

H290 - May be corrosive to metals

H314 - Causes severe skin burns and eye damage

H370 - Causes damage to organs

Optic nerve

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

EUH014 - Reacts violently with water

## **Precautionary Statements**

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

#### 2.3. Other hazards

Water reactive

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

Sodium methoxide, 5.4M (30 wt.%) solution in methanol

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS** 

#### 3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Methyl alcohol	67-56-1	200-659-6	70	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Sodium methoxide	124-41-4	EEC No. 204-699-5	30	Skin Corr. 1A (H314) Eye Dam. 1 (H318) Acute Tox. 4 (H302) Self-heat. 1 (H251) Flam. Sol. 1 (H228) Met. Corr. 1 (H290) EUH014

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methyl alcohol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-

Components	Reach Registration Number	
Methanol	01-2119433307-44	
Sodium methoxide	01-2119519241-51	

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

**General Advice** Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim

ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh

air. Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should

Revision Date 22-Sep-2023

## Sodium methoxide, 5.4M (30 wt.%) solution in methanol

Revision Date 22-Sep-2023

be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat sym

Treat symptomatically. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

## 5.1. Extinguishing media

#### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

## Extinguishing media which must not be used for safety reasons

Water

## 5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Thermal decomposition can lead to release of irritating gases and vapors, Sodium oxides.

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

## 6.2. Environmental precautions

Should not be released into the environment.

## 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

\_\_\_\_\_

## Sodium methoxide, 5.4M (30 wt.%) solution in methanol

Revision Date 22-Sep-2023

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

## **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from water or moist air. Keep away from heat, sparks and flame. Store indoors. Flammables area. Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

#### 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

## **Exposure limits**

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl alcohol	WEL - TWA: 200 ppm TWA;	TWA: 200 ppm 8 hr	TWA: 200 ppm 8 hr.
	266 mg/m³ TWA	TWA: 260 mg/m <sup>3</sup> 8 hr	TWA: 260 mg/m <sup>3</sup> 8 hr.
	WEL - STEL: 250 ppm	Skin	STEL: 600 ppm 15 min
	STEL; 333 mg/m <sup>3</sup> STEL		STEL: 780 mg/m <sup>3</sup> 15 min
	_		Skin

#### **Biological limit values**

List source(s):

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

С	omponent	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
	ethyl alcohol		DNEL = 20mg/kg		DNEL = 20mg/kg
67	7-56-1 ( 70 )		bw/day		bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methyl alcohol 67-56-1 ( 70 )	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>

## Predicted No Effect Concentration (PNEC)

#### Sodium methoxide, 5.4M (30 wt.%) solution in methanol

See values below.

Γ	Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
			sediment		sewage treatment	
Γ	Methyl alcohol	PNEC = 20.8mg/L	PNEC = 77mg/kg	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg
	67-56-1 ( 70 )		sediment dw		-	soil dw
Γ	Sodium methoxide	PNEC = 154mg/L	PNEC =	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 23.5 mg/kg
	124-41-4 ( 30 )		570.4mg/kg		_	soil dw
			sediment dw			

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl alcohol 67-56-1 ( 70 )	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			
Sodium methoxide 124-41-4 ( 30 )	PNEC = 15.4mg/L				

#### 8.2. Exposure controls

#### **Engineering Measures**

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

## Personal protective equipment

**Eye Protection** 

Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

ACR16860

Revision Date 22-Sep-2023

Sodium methoxide, 5.4M (30 wt.%) solution in methanol

\_\_\_\_\_

Revision Date 22-Sep-2023

Page 7/13

**Environmental exposure controls** No information available.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Physical State Liquid

AppearanceLight yellowOdorAlcohol-likeOdor ThresholdNo data available

Melting Point/Range 1 - 5 °C / 33.8 - 41 °F

Softening Point No data available

Boiling Point/Range93 °C / 199.4 °F@ 760 mmHgFlammability (liquid)FlammableOn basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 5.5 vol% Upper 44 vol%

Flash Point 33 °C / 91.4 °F Method - No information available

Autoignition Temperature
Decomposition Temperature
pH
Viscosity
Water Solubility
Solubility in other solvents

240 °C / 464 °F
No data available
Not applicable
No data available
Reacts with water
No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethyl alcohol-0.74Sodium methoxide-0.75

Vapor Pressure 150 hPa @ 50 °C

Density / Specific Gravity 0.97

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

**Explosive Properties** explosive air/vapour mixtures possible

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity Yes

10.2. Chemical stability

Moisture sensitive.

10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization does not occur.

Hazardous Reactions Reacts violently with water.

10.4. Conditions to avoid

Exposure to moist air or water. Keep away from open flames, hot surfaces and sources of

ignition. Exposure to moisture.

10.5. Incompatible materials

Strong oxidizing agents. Acids.

Revision Date 22-Sep-2023

#### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2). Thermal decomposition can lead to release of irritating gases and vapors. Sodium oxides.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity;

Oral Category 3 Category 3 **Dermal** Inhalation Category 3

## Toxicology data for the components

Component		LD50 Oral	LD50 Dermal	LC50 Inhalation	
I	Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L (Rat) 4 h	
ı	Sodium methoxide	1687 mg/kg (Rat)	>2000 mg/kg (Rat)	-	

(b) skin corrosion/irritation; Category 1 A

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

No data available Respiratory No data available Skin

	Component	Test method	Test species	Study result
Γ	Methyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
١	67-56-1 ( 70 )	Guinea Pig Maximisation Test		_
1		(GPMT)		

No data available (e) germ cell mutagenicity;

No data available (f) carcinogenicity;

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Methyl alcohol	OECD Test Guideline 416	Rat / Inhalation	NOAEC =
67-56-1 ( 70 )		2 Generation	1.3 mg/l (air)

**Reproductive Effects** California Proposition 65. Reproductive toxicity.

(h) STOT-single exposure; Category 1

Results / Target organs Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

**Target Organs** No information available.

Sodium methoxide, 5.4M (30 wt.%) solution in methanol

(j) aspiration hazard; No data available

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

Revision Date 22-Sep-2023

#### 11.2. Information on other hazards

**Endocrine Disrupting Properties** 

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1. Toxicity

**Ecotoxicity effects** 

Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methyl alcohol	Pimephales promelas: LC50 >	EC50 > 10000 mg/L 24h	
	10000 mg/L 96h	_	

Component	Microtox	M-Factor
Methyl alcohol	EC50 = 39000 mg/L 25 min	
	EC50 = 40000 mg/L 15 min	
	EC50 = 43000 mg/L 5 min	

## 12.2. Persistence and degradability No information available

**Persistence** Persistence is unlikely, based on information available.

Degradability Reacts with water, No information available.

Component	Degradability	
Methyl alcohol	DT50 ~ 17.2d	
67-56-1 ( 70 )	>94% after 20d	

Degradation in sewage treatment plant

Water reactive. No information available.

## 12.3. Bioaccumulative potential

Product does not bioaccumulate due to reaction with water

	Component	log Pow	Bioconcentration factor (BCF)
Г	Methyl alcohol	-0.74	<10 dimensionless
Г	Sodium methoxide	-0.75	No data available

12.4. Mobility in soil Reacts with water . Is not likely mobile in the environment.

#### 12.5. Results of PBT and vPvB

assessment

Water reactive.

#### 12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

#### 12.7. Other adverse effects

**Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

13.1. Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives

Revision Date 22-Sep-2023

on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic

organisms.

## **SECTION 14: TRANSPORT INFORMATION**

#### IMDG/IMO

**14.1. UN number** UN1289

14.2. UN proper shipping name SODIUM METHYLATE SOLUTION

14.3. Transport hazard class(es)3Subsidiary Hazard Class814.4. Packing groupIII

ADR

**14.1. UN number** UN1289

14.2. UN proper shipping name SODIUM METHYLATE SOLUTION

14.3. Transport hazard class(es)3Subsidiary Hazard Class814.4. Packing groupIII

IATA

**14.1. UN number** UN1289

14.2. UN proper shipping name SODIUM METHYLATE SOLUTION

14.3. Transport hazard class(es)3Subsidiary Hazard Class814.4. Packing groupIII

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk Not applicable, packaged goods according to IMO instruments

## **SECTION 15: REGULATORY INFORMATION**

Revision Date 22-Sep-2023

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **International Inventories**

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl alcohol	67-56-1	200-659-6	-	-	X	X	KE-23193	Χ	X
Sodium methoxide	124-41-4	204-699-5	-	-	X	X	KE-23196	Χ	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl alcohol	67-56-1	X	ACTIVE	X	Ī	Х	Х	X
Sodium methoxide	124-41-4	X	ACTIVE	X	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	67-56-1	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Sodium methoxide	124-41-4	-	Use restricted. See item 75. (see link for restriction details)	-

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report
		Notification	Requirements
Methyl alcohol	67-56-1	500 tonne	5000 tonne
Sodium methoxide	124-41-4	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

#### Sodium methoxide, 5.4M (30 wt.%) solution in methanol

Revision Date 22-Sep-2023

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

#### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

#### **WGK Classification**

Water endangering class = 2 (self classification)

	Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
	Methyl alcohol	WGK 2	Class I: 20 mg/m³ (Massenkonzentration)
Γ	Sodium methoxide	WGK2	

Component	France - INRS (Tables of occupational diseases)
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methyl alcohol 67-56-1 ( 70 )	Prohibited and Restricted Substances	Group I	

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H290 - May be corrosive to metals

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H370 - Causes damage to organs

EUH014 - Reacts violently with water

H225 - Highly flammable liquid and vapor

H228 - Flammable solid

H251 - Self-heating; may catch fire

H302 - Harmful if swallowed

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

Inventory

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

#### Sodium methoxide, 5.4M (30 wt.%) solution in methanol

RPE - Respiratory Protective Equipment LD50 - Lethal Dose 50%

LC50 - Lethal Concentration 50% EC50 - Effective Concentration 50% NOEC - No Observed Effect Concentration POW - Partition coefficient Octanol:Water PBT - Persistent, Bioaccumulative, Toxic vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

Revision Date 22-Sep-2023

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

## Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

On basis of test data Physical hazards Calculation method **Health Hazards Environmental hazards** Calculation method

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

**Creation Date** 25-Jun-2009 **Revision Date** 22-Sep-2023 Not applicable. **Revision Summary** 

## This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**