

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 11-Jun-2009 Revision Date 29-Sep-2023 Revision Number 13

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description: <u>Toluene</u>

Cat No.: 332070000; 332070010; 332070025

 Synonyms
 Tol; Methylbenzene

 Index No
 601-021-00-3

 CAS No
 108-88-3

 EC No
 203-625-9

Molecular Formula C7 H8

REACH registration number 01-2119471310-51

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use**Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals

**Process categories** PROC15 - Use as a laboratory reagent

**Environmental release category** ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

## 1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road.

Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name** Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

**E-mail address** begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Toluene Revision Date 29-Sep-2023

Flammable liquids Category 2 (H225)

#### **Health hazards**

Aspiration Toxicity
Skin Corrosion/Irritation
Reproductive Toxicity
Specific target organ toxicity - (single exposure)
Specific target organ toxicity - (repeated exposure)
Specific target organ toxicity - (repeated exposure)
Category 2 (H373)
Category 2 (H373)

**Environmental hazards** 

Chronic aquatic toxicity Category 3 (H412)

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



Signal Word

**Danger** 

## **Hazard Statements**

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure if inhaled

H412 - Harmful to aquatic life with long lasting effects

#### **Precautionary Statements**

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P264 - Wash face, hands and any exposed skin thoroughly after handling

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

#### 2.3. Other hazards

Substance is not considered to be persistent, bioaccumulative and toxic (PBT)

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

**Toluene** Revision Date 29-Sep-2023

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Toluene	108-88-3	203-625-9	<=100	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361d) STOT RE 2 (H373) Aquatic Chronic 3 (H412)

REACH registration number	01-2119471310-51

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

**General Advice** If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call Ingestion

a physician or poison control center immediately. If vomiting occurs naturally, have victim

lean forward.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur. Risk of serious damage to the lungs (by aspiration).

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

## 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomitina

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Smallest quantities reaching the lungs through swallowing or Notes to Physician

subsequent vomiting may result in lung edema or pneumonia. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

Toluene Revision Date 29-Sep-2023

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

Do not use water jetstream.

#### 5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO2).

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3

Toluene Revision Date 29-Sep-2023

Storage Class (LGK) (Germany)

## 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

#### **Exposure limits**

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Toluene	STEL: 100 ppm 15 min	TWA: 50 ppm (8hr)	TWA: 192 mg/m <sup>3</sup> 8 hr.
	STEL: 384 mg/m <sup>3</sup> 15 min	TWA: 192 mg/m³ (8hr)	TWA: 50 ppm 8 hr.
	TWA: 50 ppm 8 hr	STEL: 100 ppm (15min)	STEL: 384 mg/m <sup>3</sup> 15 min
	TWA: 191 mg/m <sup>3</sup> 8 hr	STEL: 384 mg/m <sup>3</sup> (15min)	STEL: 100 ppm 15 min
	Skin	Skin	Skin

#### **Biological limit values**

List source(s):

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Toluene 108-88-3 ( <=100 )				8.13 mg/kg bw/day

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Toluene 108-88-3 ( <=100 )				DNEL = 384mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Toluene 108-88-3 ( <=100 )	DNEL = 384mg/m <sup>3</sup>	DNEL = 384mg/m <sup>3</sup>	DNEL = 192mg/m <sup>3</sup>	DNEL = 192mg/m <sup>3</sup>

## **Predicted No Effect Concentration (PNEC)**

See values below.

Г	Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
			sediment		sewage treatment	
Γ	Toluene	PNEC = 0.68mg/L		PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg
	108-88-3 ( <=100 )		16.39mg/kg			soil dw
L			sediment dw			

Component	Marine water	Marine water	Marine water	Food chain	Air

Toluene Revision Date 29-Sep-2023

		sediment	intermittent	
Toluene	PNEC = 0.68mg/L	PNEC =		
108-88-3 ( <=100 )		16.39mg/kg		
		sediment dw		

#### 8.2. Exposure controls

#### **Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

**Eye Protection** Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection Protective gloves

Γ	Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
	Viton (R)	< 240 minutes	0.30 mm	Level 4	Permeation rate 68 µg/cm2/min
				EN 374	As tested under EN374-3 Determination of
					Resistance to Permeation by Chemicals
1	Viton (R)	> 480 minutes	0.70 mm		·

**Skin and body protection** Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains. Do not allow material to contaminate ground water

system.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless

Toluene Revision Date 29-Sep-2023

Odor aromatic
Odor Threshold 1.74 ppm

Melting Point/Range-95 °C / -139 °FSoftening PointNo data availableBoiling Point/Range111 °C / 231.8 °F

Boiling Point/Range111 °C / 231.8 °F@ 760 mmHgFlammability (liquid)Highly flammableOn basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits

Lower 1.2 vol%
Upper 7 vol%

Flash Point 4 °C / 39.2 °F Method - No information available

Autoignition Temperature535 °C / 995 °FDecomposition TemperatureNo data availablepHNo information availableViscosity0.6 mPa.s @ 20 °C

Water Solubility practically insoluble 0.5 g/L @ 20°C

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowToluene2.73

Vapor Pressure 29 mbar @ 20 °C

**Density / Specific Gravity** 0.866

Bulk DensityNot applicableLiquidVapor Density3.1(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C7 H8 Molecular Weight 92.14

**Explosive Properties**Not explosive Vapors may form explosive mixtures with air

Oxidizing Properties Not oxidising

**Evaporation Rate** 2.4 (Butyl acetate = 1.0)

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Halogenated compounds.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Toluene Revision Date 29-Sep-2023

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

(b) skin corrosion/irritation; Category 2
Test method OECD 404
Test species rabbit

Observational endpoint Irritating to skin

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Not mutagenic in AMES Test

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Category 2

**Reproductive Effects** Experiments have shown reproductive toxicity effects on laboratory animals.

**Developmental Effects** Developmental effects have occurred in experimental animals.

**Teratogenicity** Possible risk of harm to the unborn child.

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Category 2

Target Organs Liver, Kidney, Central nervous system (CNS), Blood, spleen, Neuropsychological effects,

Eyes, Ears.

(j) aspiration hazard; Category 1

Symptoms / effects,both acute and Causes central nervous system depression. Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

\_\_\_\_\_

delayed

Toluene SAILII DAIA SIILL

known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

## **12.1. Toxicity**

**Ecotoxicity effects** 

The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms.

Revision Date 29-Sep-2023

Component	Freshwater Fish	Water Flea	Freshwater Algae
Toluene	50-70 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h	EC50: = 12.5 mg/L, 72h static
	5-7 mg/L LC50 96 h	(Daphnia magna)	(Pseudokirchneriella subcapitata)
	15-19 mg/L LC50 96 h	EC50: 5.46 - 9.83 mg/L, 48h	EC50: > 433 mg/L, 96h
	28 mg/L LC50 96 h	Static (Daphnia magna)	(Pseudokirchneriella subcapitata)
	12 mg/L LC50 96 h		]

Component	Microtox	M-Factor
Toluene	EC50 = 19.7 mg/L 30 min	

## 12.2. Persistence and degradability Readily biodegradable

Persistence Persistence is unlikely.

Component	Degradability
Toluene	86% (20d)
108-88-3 ( <=100 )	

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

## 12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Toluene	2.73	90

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Spillage unlikely to penetrate soil The product is insoluble and floats on water Is

not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB

<u>assessment</u>

Substance is not considered to be persistent, bioaccumulative and toxic (PBT). Substance is not considered persistent, bioaccumulative and toxic (PBT) / yery persistent and very

bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** 

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Toluene Revision Date 29-Sep-2023

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not

empty into drains.

## **SECTION 14: TRANSPORT INFORMATION**

#### IMDG/IMO

**14.1. UN number 14.2. UN proper shipping name**UN1294
TOLUENE

14.3. Transport hazard class(es) 3 14.4. Packing group II

#### ADR

14.1. UN numberUN129414.2. UN proper shipping nameTOLUENE

14.3. Transport hazard class(es) 3 14.4. Packing group II

#### **IATA**

**14.1. UN number** UN1294 TOLUENE

14.3. Transport hazard class(es) 3 14.4. Packing group II

14.5. Environmental hazards No hazards identified

**14.6. Special precautions for user** No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

## **SECTION 15: REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **International Inventories**

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Toluene	108-88-3	203-625-9	i	-	X	X	KE-33936	Χ	X
Component	CAS No	TSCA	TSCA In	ventory	DSL	NDSL	AICS	NZIoC	PICCS

\_\_\_\_\_

## Toluene Revision Date 29-Sep-2023

			notification - Active-Inactive					
Toluene	108-88-3	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	108-88-3	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
		Qualifying Quantities for Major Accident Notification	Requirements
Toluene	108-88-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

#### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class		
Toluene	WGK3			

Component	France - INRS (Tables of occupational diseases)
Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis,RG 84

Page 11 / 13

Toluene Revision Date 29-Sep-2023

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Toluene 108-88-3 ( <=100 )	Prohibited and Restricted Substances	Group I	

#### 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

#### **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

H225 - Highly flammable liquid and vapor

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

#### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eve wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Toluene Revision Date 29-Sep-2023

Creation Date11-Jun-2009Revision Date29-Sep-2023Revision SummaryNot applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**