

Creation Date 07-Oct-2010

Revision Date 25-Sep-2023

Revision Number 11

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	<u>Methyl vinyl ketone, stabilized</u>
Cat No. :	128000000; 128000010; 128000025; 128000050
Synonyms	3-Buten-2-one; MVK
CAS No	78-94-4
EC No	201-160-6
Molecular Formula	C4 H6 O
REACH registration number	01-2120090431-63

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road,
Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

Flammable liquids	Category 2 (H225)
<u>Health hazards</u>	
Acute oral toxicity	Category 2 (H300)
Acute dermal toxicity	Category 1 (H310)
Acute Inhalation Toxicity - Vapors	Category 1 (H330)
Skin Corrosion/Irritation	Category 1 (H314) B
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Skin Sensitization	Category 1 (H317)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)
<u>Environmental hazards</u>	
Acute aquatic toxicity	Category 1 (H400)
Chronic aquatic toxicity	Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H373 - May cause damage to organs through prolonged or repeated exposure
H410 - Very toxic to aquatic life with long lasting effects
H300 + H310 + H330 - Fatal if swallowed, in contact with skin or if inhaled

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P310 - Immediately call a POISON CENTER or doctor/physician
P361 + P364 - Take off immediately all contaminated clothing and wash it before reuse
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Methyl vinyl ketone	78-94-4	EEC No. 201-160-6	95	Flam. Liq. 2 (H225) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Acute Tox. 2 (H300) Acute Tox. 1 (H310) Acute Tox. 1 (H330) Skin Sens. 1 (H317) STOT RE 2 (H373) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Acetic acid	64-19-7	200-580-7	0.4-1	Flam. Liq. 3 (H226) Skin Corr. 1A (H314) Eye Dam. 1 (H318)
Acetonitrile	75-05-8	200-835-2	< 0.7	Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Acute Tox. 4 (H312) Eye Irrit. 2 (H319) Acute Tox. 4 (H332)
Hydroquinone	123-31-9	EEC No. 204-617-8	0.3-0.5	Acute Tox. 4 (H302) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Muta. 2 (H341) Carc. 2 (H351) Aquatic Acute 1 (H400)
Water	7732-18-5	231-791-2	3	-

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methyl vinyl ketone	-	1	-
Acetic acid	Skin Corr. 1A (H314) :: C>=90% Skin Corr. 1B (H314) :: 25%<=C<90% Eye Irrit. 2 (H319) :: 10%<=C<25% Skin Irrit. 2 (H315) :: 10%<=C<25%	-	-
Hydroquinone	-	10	-

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Acetonitrile	ATE = 617 mg/kg	-	-

ECHA (RAC) - Committee for Risk Assessment - European Chemicals Agency
ATE - Acute Toxicity Estimate; mg/kg bw - milligrams per kilogram of body weight

REACH registration number	01-2120090431-63
---------------------------	------------------

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

	the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Thermal decomposition can lead to release of irritating gases and vapors.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. To maintain product quality: Keep refrigerated. Keep at temperatures below 10°C.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3
Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl vinyl ketone			STEL: 0.2 ppm 15 min Skin
Acetic acid	STEL: 37 mg/m ³ STEL: 15 ppm	TWA: 25 mg/m ³ (15min) TWA: 10 ppm (15min)	TWA: 20 ppm 8 hr. TWA: 50 mg/m ³ 8 hr.

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

	TWA: 10 ppm TWA: 25 mg/m ³	STEL: 50 mg/m ³ (8h) STEL: 20 ppm (8h)	STEL: 20 ppm 15 min STEL: 50 mg/m ³ 15 min
Acetonitrile	STEL: 60 ppm 15 min STEL: 102 mg/m ³ 15 min TWA: 40 ppm 8 hr TWA: 68 mg/m ³ 8 hr	TWA: 40 ppm (8hr) TWA: 70 mg/m ³ (8hr) Skin	TWA: 40 ppm 8 hr. TWA: 70 mg/m ³ 8 hr. STEL: 120 ppm 15 min STEL: 310 mg/m ³ 15 min Skin
Hydroquinone	STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr		TWA: 0.5 mg/m ³ 8 hr. STEL: 1.5 mg/m ³ 15 min

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Acetonitrile 75-05-8 (< 0.7)				DNEL = 32.2mg/kg bw/day
Hydroquinone 123-31-9 (0.3-0.5)				DNEL = 3.33mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Acetic acid 64-19-7 (0.4-1)	DNEL = 25mg/m ³		DNEL = 25mg/m ³	
Acetonitrile 75-05-8 (< 0.7)	DNEL = 40.6 ppm (68 mg/m ³)	DNEL = 40.6 ppm (68 mg/m ³)	DNEL = 40.6 ppm (68 mg/m ³)	DNEL = 40.6 ppm (68 mg/m ³)
Hydroquinone 123-31-9 (0.3-0.5)				DNEL = 2.1mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Acetic acid 64-19-7 (0.4-1)	PNEC = 3.058mg/L	PNEC = 11.36mg/kg sediment dw	PNEC = 30.58mg/L	PNEC = 85mg/L	PNEC = 0.47mg/kg soil dw
Acetonitrile 75-05-8 (< 0.7)	PNEC = 10mg/L	PNEC = 7.53mg/kg sediment dw	PNEC = 10mg/L	PNEC = 32mg/L	PNEC = 2.41mg/kg soil dw
Hydroquinone 123-31-9 (0.3-0.5)	PNEC = 0.57µg/L	PNEC = 4.9µg/kg sediment dw	PNEC = 1.34µg/L	PNEC = 0.71mg/L	PNEC = 0.64µg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Acetic acid 64-19-7 (0.4-1)	PNEC = 0.3058mg/L	PNEC = 1.136mg/kg sediment dw			
Acetonitrile 75-05-8 (< 0.7)	PNEC = 1mg/L				
Hydroquinone 123-31-9 (0.3-0.5)	PNEC = 0.057µg/L	PNEC = 0.49µg/kg sediment dw			

8.2. Exposure controls

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber Neoprene Natural rubber PVC	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State

Liquid

Appearance

Light yellow

Odor

Irritating pungent

Odor Threshold

0.2 ppm

Melting Point/Range

No data available

Softening Point

No data available

Boiling Point/Range

80 °C / 176 °F

@ 760 mmHg

Flammability (liquid)

Highly flammable

On basis of test data

Flammability (solid,gas)

Not applicable

Liquid

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

Explosion Limits	Lower 2.1 vol%	
	Upper 15.6 vol%	
Flash Point	-7 °C / 19.4 °F	Method - No information available
Autoignition Temperature	370 °C / 698 °F	
Decomposition Temperature	No data available	
pH	Not applicable	
Viscosity	Dynamic 0.81 mPa.s (70 °C)	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Acetic acid	-0.2	
Acetonitrile	-0.34	
Hydroquinone	0.59	
Vapor Pressure	130 mbar @ 28 °C	
Density / Specific Gravity	0.864 g/cm3 @20°C	
Bulk Density	Not applicable	Liquid
Vapor Density	2.4	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C4 H6 O
Molecular Weight	70.09
Explosive Properties	Vapors may form explosive mixtures with air
Self-accelerating polymerisation temperature (SAPT)	>50°C (all packages)
Surface tension	24 mN/m

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Light sensitive. heat sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	Polymerization can occur.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Excess heat. Exposure to light. Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

10.5. Incompatible materials

Oxidizing agent. Reducing Agent. oxygen. Bases. Amines. Ammonia.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

Product Information

(a) acute toxicity;

Oral Category 2
Dermal Category 1
Inhalation Category 1

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl vinyl ketone	LD50 = 23.1 mg/kg (Rat)	LD50 = 35 mg/kg (Rat)	LC50 = 7 mg/m ³ (Rat) 4 h
Acetic acid	3310 mg/kg (Rat)	-	> 40 mg/L (Rat) 4 h
Acetonitrile	450-787 mg/kg (Rat) 2460 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	LC50 = 3587 ppm (6.022 mg/l) (Mouse) 4h LC50 = 16,000 ppm (26.8 mg/l) (Rat) 4h
Hydroquinone	LD50 = 298 mg/kg (Rat)	LD50 = 74800 mg/kg (Rabbit)	-
Water	-	-	-

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Acetonitrile	ATE = 617 mg/kg	-	-

ECHA (RAC) - Committee for Risk Assessment - European CHemicals Agency
ATE - Acute Toxicity Estimate; mg/kg bw - milligrams per kilogram of body weight

(b) skin corrosion/irritation; Category 1 B Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 1 Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met
Skin Category 1
Based on available data, the classification criteria are not met
May cause sensitization by skin contact

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met
The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Hydroquinone			Cat. 2	

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Based on available data, the classification criteria are not met

(i) STOT-repeated exposure; Category 2
Based on available data, the classification criteria are not met

Target Organs No information available.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Other Adverse Effects The toxicological properties have not been fully investigated.

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Acetic acid	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	EC50 = 95 mg/L/24h	-
Acetonitrile	LC50: = 1850 mg/L, 96h static (Lepomis macrochirus) LC50: = 1000 mg/L, 96h static (Pimephales promelas) LC50: 1600 - 1690 mg/L, 96h flow-through (Pimephales promelas) LC50: = 1650 mg/L, 96h static (Poecilia reticulata)		
Hydroquinone	LC50: 0.1 - 0.18 mg/L, 96h static (Pimephales promelas) LC50: = 0.17 mg/L, 96h (Brachydanio rerio) LC50: = 0.044 mg/L, 96h flow-through (Pimephales promelas) LC50: = 0.044 mg/L, 96h flow-through (Oncorhynchus mykiss)	EC50: = 0.29 mg/L, 48h (Daphnia magna)	EC50: = 0.335 mg/L, 72h (Pseudokirchneriella subcapitata)

Component	Microtox	M-Factor
Methyl vinyl ketone		1
Acetic acid	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min	
Acetonitrile	EC50 = 28000 mg/L 48 h EC50 = 73 mg/L 24 h EC50 = 7500 mg/L 15 h	
Hydroquinone	EC50 = 0.038 mg/L 15 min	10

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

	EC50 = 0.0382 mg/L 30 min EC50 = 0.042 mg/L 5 min EC50 = 23.75 mg/L 60 min	
--	--	--

12.2. Persistence and degradability	Not readily biodegradable
Persistence	Persistence is unlikely, based on information available.
Degradation in sewage treatment plant	Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential	Bioaccumulation is unlikely
--	-----------------------------

Component	log Pow	Bioconcentration factor (BCF)
Acetic acid	-0.2	No data available
Acetonitrile	-0.34	No data available
Hydroquinone	0.59	40 dimensionless

12.4. Mobility in soil	The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.
Surface tension	24 mN/m

12.5. Results of PBT and vPvB assessment	No data available for assessment.
---	-----------------------------------

12.6. Endocrine disrupting properties	
Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects	
Persistent Organic Pollutant	This product does not contain any known or suspected substance
Ozone Depletion Potential	This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

SECTION 14: TRANSPORT INFORMATION

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

IMDG/IMO

14.1. UN number UN1251
14.2. UN proper shipping name METHYL VINYL KETONE, STABILIZED
14.3. Transport hazard class(es) 6.1
Subsidiary Hazard Class 3, 8
14.4. Packing group I

ADR

14.1. UN number UN1251
14.2. UN proper shipping name METHYL VINYL KETONE, STABILIZED
14.3. Transport hazard class(es) 6.1
Subsidiary Hazard Class 3, 8
14.4. Packing group I

IATA

FORBIDDEN FOR IATA TRANSPORT

14.1. UN number UN1251
14.2. UN proper shipping name METHYL VINYL KETONE, STABILIZED FORBIDDEN FOR IATA TRANSPORT
14.3. Transport hazard class(es) 6.1
Subsidiary Hazard Class 3, 8
14.4. Packing group I

14.5. Environmental hazards Dangerous for the environment
 Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user Storage conditions in Section 7 should also be met during transportation. Cooled transportation <10°C is recommended to ensure shelf-life. Inhibitors have been added to stabilize this product. Inhibitor levels should be maintained. Hazardous polymerization may occur upon depletion of inhibitor.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl vinyl ketone	78-94-4	201-160-6	-	-	X	X	KE-04112	X	X
Acetic acid	64-19-7	200-580-7	-	-	X	X	X	X	X
Acetonitrile	75-05-8	200-835-2	-	-	X	X	KE-00067	X	X
Hydroquinone	123-31-9	204-617-8	-	-	X	X	KE-35112	X	X
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDL	AICS	NZIoC	PICCS
Methyl vinyl ketone	78-94-4	X	ACTIVE	-	X	X	X	X
Acetic acid	64-19-7	X	ACTIVE	X	-	X	X	X
Acetonitrile	75-05-8	X	ACTIVE	X	-	X	X	X
Hydroquinone	123-31-9	X	ACTIVE	X	-	X	X	X

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

Water	7732-18-5	X	ACTIVE	X	-	X	X	X
-------	-----------	---	--------	---	---	---	---	---

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl vinyl ketone	78-94-4	-	-	-
Acetic acid	64-19-7	-	Use restricted. See item 75. (see link for restriction details)	-
Acetonitrile	75-05-8	-	Use restricted. See item 75. (see link for restriction details)	-
Hydroquinone	123-31-9	-	Use restricted. See item 75. (see link for restriction details)	-
Water	7732-18-5	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methyl vinyl ketone	78-94-4	Not applicable	Not applicable
Acetic acid	64-19-7	Not applicable	Not applicable
Acetonitrile	75-05-8	Not applicable	Not applicable
Hydroquinone	123-31-9	Not applicable	Not applicable
Water	7732-18-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl vinyl ketone	WGK3	
Acetic acid	WGK1	Class II : 0.10 g/m ³ (Massenkonzentration)

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

Acetonitrile	WGK2	
Hydroquinone	WGK3	Class I : 20 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Acetonitrile	Tableaux des maladies professionnelles (TMP) - RG 84
Hydroquinone	Tableaux des maladies professionnelles (TMP) - RG 65

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Acetic acid 64-19-7 (0.4-1)	Prohibited and Restricted Substances	Group I	
Hydroquinone 123-31-9 (0.3-0.5)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H300 - Fatal if swallowed
H310 - Fatal in contact with skin
H330 - Fatal if inhaled
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H225 - Highly flammable liquid and vapor
H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H312 - Harmful in contact with skin
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H341 - Suspected of causing genetic defects
H351 - Suspected of causing cancer

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 25-Sep-2023

NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Creation Date 07-Oct-2010

Revision Date 25-Sep-2023

Revision Summary SDS sections updated.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet