

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

<b>Product Description:</b>	<b><u>3-Methyl-1-butanol</u></b>
<b>Cat No. :</b>	<b>36716</b>
<b>Synonyms</b>	Isoamyl alcohol; Isopentyl alcohol
<b>CAS No</b>	123-51-3
<b>EC No</b>	204-633-5
<b>Molecular Formula</b>	C5 H12 O
<b>REACH registration number</b>	-

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Recommended Use</b>	Laboratory chemicals
<b>Sector of use</b>	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
<b>Product category</b>	PC21 - Laboratory chemicals
<b>Process categories</b>	PROC15 - Use as a laboratory reagent
<b>Environmental release category</b>	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
<b>Uses advised against</b>	No Information available

### 1.3. Details of the supplier of the safety data sheet

<b>Company</b>	Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific) Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608
----------------	--

**E-mail address** begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

**GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567**

**Physical hazards**

Flammable liquids

Category 3 (H226)

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

## Health hazards

Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Specific target organ toxicity - (single exposure)	Category 3 (H335)

## Environmental hazards

Chronic aquatic toxicity	Category 3 (H412)
--------------------------	-------------------

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

## Hazard Statements

H226 - Flammable liquid and vapor  
H332 - Harmful if inhaled  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H335 - May cause respiratory irritation  
H412 - Harmful to aquatic life with long lasting effects  
EUH066 - Repeated exposure may cause skin dryness or cracking

## Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor/physician  
P280 - Wear protective gloves/protective clothing/eye protection/face protection

## 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

## 3.1. Substances

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Isoamyl alcohol	123-51-3	EEC No. 204-633-5	<=100	Flam Liq. 3 (H226) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 1 (H318) STOT SE 3 (H335) Aquatic Chronic 3 (H412) (EUH066)

REACH registration number	-
---------------------------	---

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	If symptoms persist, call a physician.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
<b>Self-Protection of the First Aider</b>	Use personal protective equipment as required.

### 4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. Causes severe eye damage. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically. Symptoms may be delayed.
---------------------------	---

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

ALFAA36716

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors.

## **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### **5.3. Advice for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

### **6.2. Environmental precautions**

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

**Technical Rules for Hazardous Substances (TRGS) 510**      Class 3  
**Storage Class (LGK) (Germany)**

### **7.3. Specific end use(s)**

Use in laboratories

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Isoamyl alcohol	STEL: 125 ppm 15 min STEL: 458 mg/m <sup>3</sup> 15 min TWA: 100 ppm 8 hr TWA: 366 mg/m <sup>3</sup> 8 hr		TWA: 5 ppm 8 hr. TWA: 18 mg/m <sup>3</sup> 8 hr. STEL: 10 mg/m <sup>3</sup> 15 min STEL: 37 ppm 15 min

#### Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Isoamyl alcohol 123-51-3 (<=100)	DNEL = 292mg/m <sup>3</sup>		DNEL = 73.16mg/m <sup>3</sup>	

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Isoamyl alcohol 123-51-3 (<=100)	PNEC = 0.12mg/L	PNEC = 0.496mg/kg sediment dw	PNEC = 1.2mg/L	PNEC = 37mg/L	PNEC = 0.0287mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Isoamyl alcohol 123-51-3 (<=100)	PNEC = 0.012mg/L	PNEC = 0.0496mg/kg sediment dw			

### 8.2. Exposure controls

#### Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

##### Eye Protection

Goggles (European standard - EN 166)

##### Hand Protection

Protective gloves

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

**Skin and body protection** Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Large scale/emergency use**

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

**Small scale/Laboratory use**

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**9.1. Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid	
<b>Appearance</b>	Clear	
<b>Odor</b>	Characteristic	
<b>Odor Threshold</b>	No data available	
<b>Melting Point/Range</b>	-117 °C / -178.6 °F	
<b>Softening Point</b>	No data available	
<b>Boiling Point/Range</b>	130 - 132 °C / 266 - 269.6 °F	760 mm HG
<b>Flammability (liquid)</b>	Flammable	On basis of test data
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	<b>Lower</b> 1.0 Vol%	
	<b>Upper</b> 8 Vol%	
<b>Flash Point</b>	45 °C / 113 °F	<b>Method</b> - No information available
<b>Autoignition Temperature</b>	365 - °C / 689 - °F	
<b>Decomposition Temperature</b>	335 °C	
<b>pH</b>	6.5	25 g/l aq.sol
<b>Viscosity</b>	4.3 mPa s at 20 °C	
<b>Water Solubility</b>	25 g/L (20°C)	
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
Isoamyl alcohol	1.35	
<b>Vapor Pressure</b>	4 hPa @ 20 °C	
<b>Density / Specific Gravity</b>	0.807-0.811	
<b>Bulk Density</b>	Not applicable	Liquid

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Vapor Density 3.04 (Air = 1.0) (Air = 1.0)  
Particle characteristics Not applicable (liquid)

## 9.2. Other information

Molecular Formula C5 H12 O  
Molecular Weight 88.15  
Explosive Properties explosive air/vapour mixtures possible

## SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity** None known, based on information available

**10.2. Chemical stability** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization does not occur.  
**Hazardous Reactions** None under normal processing.

**10.4. Conditions to avoid** Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

**10.5. Incompatible materials** Strong oxidizing agents. Metals. Alkali metals. Halogens. Acids. Acid anhydrides. Acid chlorides. Isocyanates.

**10.6. Hazardous decomposition products** Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

(a) acute toxicity;  
Oral Based on available data, the classification criteria are not met  
Dermal Based on available data, the classification criteria are not met  
Inhalation Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isoamyl alcohol	LD50 = 5770 mg/kg ( Rat )	LD50 = 3250 mg/kg ( Rabbit )	LC50 > 2000 ppm ( Rat ) 8 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;  
Respiratory Based on available data, the classification criteria are not met

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

<b>Skin</b>	Based on available data, the classification criteria are not met
<b>(e) germ cell mutagenicity;</b>	Based on available data, the classification criteria are not met
<b>(f) carcinogenicity;</b>	Based on available data, the classification criteria are not met There are no known carcinogenic chemicals in this product.
<b>(g) reproductive toxicity;</b>	Based on available data, the classification criteria are not met
<b>(h) STOT-single exposure;</b>	Category 3
<b>Results / Target organs</b>	Respiratory system.
<b>(i) STOT-repeated exposure;</b>	Based on available data, the classification criteria are not met
<b>Target Organs</b>	None known.
<b>(j) aspiration hazard;</b>	Based on available data, the classification criteria are not met
<b>Symptoms / effects, both acute and delayed</b>	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**11.2. Information on other hazards**

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

**12.1. Toxicity**

**Ecotoxicity effects**

This product contains the following substance(s) which are hazardous for the environment. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Isoamyl alcohol	LC50 96 h 700 mg/L (rainbow trout)	EC50: = 260 mg/L, 48h (Daphnia magna)	EC50: = 181 mg/L, 96h (Desmodesmus subspicatus) EC50: = 493 mg/L, 72h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
Isoamyl alcohol	EC50 = 2500 mg/L 17 h	

**12.2. Persistence and degradability**

**Persistence**  
**Degradation in sewage treatment plant**

Readily biodegradable  
Persistence is unlikely.  
Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

**12.3. Bioaccumulative potential**

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Isoamyl alcohol	1.35	No data available
-----------------	------	-------------------

## 12.4. Mobility in soil

The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

## 12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

## 12.6. Endocrine disrupting properties

### **Endocrine Disruptor Information**

This product does not contain any known or suspected endocrine disruptors

## 12.7. Other adverse effects

### **Persistent Organic Pollutant Ozone Depletion Potential**

This product does not contain any known or suspected substance

This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### **Waste from Residues/Unused Products**

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

#### **Contaminated Packaging**

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

#### **European Waste Catalogue (EWC)**

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

#### **Other Information**

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Do not let this chemical enter the environment.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

#### 14.1. UN number

UN1105

#### 14.2. UN proper shipping name

PENTANOLS

#### 14.3. Transport hazard class(es)

3

#### 14.4. Packing group

III

### ADR

#### 14.1. UN number

UN1105

#### 14.2. UN proper shipping name

PENTANOLS

#### 14.3. Transport hazard class(es)

3

#### 14.4. Packing group

III

### IATA

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

<b>14.1. UN number</b>	UN1105
<b>14.2. UN proper shipping name</b>	PENTANOLS
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	III
<b>14.5. Environmental hazards</b>	No hazards identified
<b>14.6. Special precautions for user</b>	No special precautions required.
<b>14.7. Maritime transport in bulk according to IMO instruments</b>	Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Isoamyl alcohol	123-51-3	204-633-5	-	-	X	X	KE-23575	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Isoamyl alcohol	123-51-3	X	ACTIVE	X	-	X	X	X

**Legend:** X - Listed '-' - Not Listed      **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

**Authorisation/Restrictions according to EU REACH**      Not applicable

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Isoamyl alcohol	123-51-3	-	-	-

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Isoamyl alcohol	123-51-3	Not applicable	Not applicable

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Basel Convention (Hazardous Waste)
Isoamyl alcohol	123-51-3	Listed	Not applicable	Not applicable

**Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals**

Not applicable

**Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?**

Not applicable

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Isoamyl alcohol	WGK1	

Component	France - INRS (Tables of occupational diseases)
Isoamyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H332 - Harmful if inhaled  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H335 - May cause respiratory irritation  
H412 - Harmful to aquatic life with long lasting effects  
EUH066 - Repeated exposure may cause skin dryness or cracking  
H226 - Flammable liquid and vapor

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer  
Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

# SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Dangerous Goods Code

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**OECD** - Organisation for Economic Co-operation and Development

**ATE** - Acute Toxicity Estimate

**BCF** - Bioconcentration factor

**VOC** - (Volatile Organic Compound)

## Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

## Prepared By

Health, Safety and Environmental Department

## Creation Date

13-Sep-2010

## Revision Date

09-Feb-2024

## Revision Summary

SDS sections updated.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**