

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 22-Jan-2009 Revision Date 09-Feb-2024 Revision Number 3

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description: <u>Isobutanol</u>
Cat No.: <u>Isobutanol</u>
22908

Synonyms Isobutanol; Isobutyl alcohol

 Index No
 603-108-00-1

 CAS No
 78-83-1

 EC No
 201-148-0

 Molecular Formula
 C4 H10 O

REACH registration number -

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

**Product category** PC21 - Laboratory chemicals

Process categories PROC15 - Use as a laboratory reagent

**Environmental release category** ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

#### 1.3. Details of the supplier of the safety data sheet

Company

Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

**Physical hazards** 

Isobutanol Revision Date 09-Feb-2024

Flammable liquids Category 3 (H226)

#### **Health hazards**

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity - (single exposure)

Category 2 (H315)

Category 1 (H318)

Category 3 (H335) (H336)

#### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



Signal Word

Danger

#### **Hazard Statements**

H226 - Flammable liquid and vapor

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

#### **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

#### 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to
				GB-CLP Regulations UK SI 2019/720 and
				UK SI 2020/1567

#### Isobutanol Revision Date 09-Feb-2024

Isobutyl alcohol	78-83-1	EEC No. 201-148-0	99	Flam. Liq. 3 (H226)
				Skin Irrit. 2 (H315) Eye Dam. 1 (H318)
				STOT SE 3 (H335)
				STOT SE 3 (H336)

REACH registration number -

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

**General Advice** If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

#### 4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. Causes severe eye damage. Symptoms of overexposure

may be headache, dizziness, tiredness, nausea and vomiting

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

#### 5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO2).

Isobutanol Revision Date 09-Feb-2024

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Should not be released into the environment.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

## 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

Isobutanol Revision Date 09-Feb-2024

#### **Exposure limits**

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Isobutyl alcohol	STEL: 75 ppm 15 min		TWA: 150 mg/m <sup>3</sup> 8 hr. NCO
	STEL: 231 mg/m <sup>3</sup> 15 min		TWA: 50 ppm 8 hr.
	TWA: 50 ppm 8 hr		STEL: 225 mg/m <sup>3</sup> 15 min
	TWA: 154 mg/m <sup>3</sup> 8 hr		STEL: 75 ppm 15 min

## **Biological limit values**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

	Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ī	Isobutyl alcohol 78-83-1 ( 99 )			DNEL = 310mg/m <sup>3</sup>	

#### **Predicted No Effect Concentration (PNEC)**

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Isobutyl alcohol	PNEC = 0.4mg/L	PNEC = 1.56mg/kg	PNEC = 11mg/L	PNEC = 10mg/L	PNEC =
78-83-1 ( 99 )		sediment dw		-	0.0765mg/kg soil
					dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Isobutyl alcohol	PNEC = 0.04mg/L	PNEC =			
78-83-1 ( 99 )		0.156mg/kg			
		sediment dw			

#### 8.2. Exposure controls

#### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	> 480 minutes	0.38 mm	EN 374	As tested under EN374-3 Determination of
Butyl rubber	> 480 minutes	0.35 mm	Level 6	Resistance to Permeation by Chemicals
Neoprene gloves	> 480 minutes	0.45 mm		
Viton (R)	> 480 minutes	0.70 mm		

Isobutanol Revision Date 09-Feb-2024

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

When workers are facing concentrations above the exposure limit they must use **Respiratory Protection** 

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits Large scale/emergency use

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure Small scale/Laboratory use

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

When RPE is used a face piece Fit Test should be conducted

No information available. **Environmental exposure controls** 

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

**Physical State** Liquid

Colorless **Appearance** aromatic Odor

No data available **Odor Threshold** -108 °C / -162.4 °F **Melting Point/Range Softening Point** No data available **Boiling Point/Range** 108 °C / 226.4 °F Flammable

Flammability (liquid) On basis of test data

Flammability (solid,gas) Not applicable Liquid

Lower 1.6 Vol% **Explosion Limits** Upper 10.9 Vol%

28 °C / 82.4 °F Flash Point

Method - No information available **Autoignition Temperature** 430 °C / 806 °F

**Decomposition Temperature** No data available No information available Hq

**Viscosity** No data available

Water Solubility Soluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow

Isobutyl alcohol

**Vapor Pressure** 11.7 mbar @ 20°C

**Density / Specific Gravity** 0.800

**Bulk Density** Not applicable Liquid **Vapor Density** (Air = 1.0)2.6

Particle characteristics Not applicable (liquid)

Isobutanol Revision Date 09-Feb-2024

9.2. Other information

Molecular FormulaC4 H10 OMolecular Weight74.12VOC Content(%)100 %

**Explosive Properties**Not explosive explosive air/vapour mixtures possible

Oxidizing Properties Not oxidising (based on the chemical structure of the substance and oxidation states of the

constituent elements)

**Evaporation Rate** 0.6 - (Butyl Acetate = 1.0)

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Acid anhydrides. Acid chlorides.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Product Information** See actual entry in RTECS for complete information.

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isobutyl alcohol	LD50 = 2460 mg/kg (Rat)	LD50 = 3400 mg/kg (Rabbit)	LC50 > 18.18 mg/L (Rat) 6 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

**Respiratory**Skin
Based on available data, the classification criteria are not met
Based on available data, the classification criteria are not met

A1 FA A22000

Isobutanol Revision Date 09-Feb-2024

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. delayed

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

12.1. Toxicity
Ecotoxicity effects

Do not empty into drains. .

Component	Freshwater Fish	Water Flea	Freshwater Algae
Isobutyl alcohol	LC50: 1370 - 1670 mg/L, 96h flow-through (Pimephales promelas)  LC50: = 375 mg/L, 96h static (Pimephales promelas)  LC50: 1120 - 1520 mg/L, 96h flow-through (Oncorhynchus mykiss)  LC50: 1480 - 1730 mg/L, 96h flow-through (Lepomis macrochirus)	EC50: = 1300 mg/L, 48h (Daphnia magna) EC50: 1070 - 1933 mg/L, 48h Static (Daphnia magna)	1799 mg/l EC50 = 72 h 230 mg/L EC50 = 48 h

	Component	Microtox	M-Factor
ĺ	Isobutyl alcohol	EC50 = 1224.6 mg/L 15 min	

## 12.2. Persistence and degradability Readily biodegradable

Persistence Soluble in water, Persistence is unlikely, based on information available.

Component	Degradability
Isobutyl alcohol	90% (14d)
78-83-1 (99)	

Degradation in sewage Contains no substances known to be hazardous to the environment or not degradable in

Isobutanol Revision Date 09-Feb-2024

treatment plant

waste water treatment plants.

12.3. Bioaccumulative potential Product has a low potential to bioconcentrate; Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Isobutyl alcohol	1	< 100

12.4. Mobility in soil

The product is water soluble, and may spread in water systems. Will likely be mobile in the

environment due to its water solubility. Disperses rapidly in air: Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

13.1. Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations. Do not empty into drains.

## **SECTION 14: TRANSPORT INFORMATION**

#### IMDG/IMO

**14.1. UN number** UN1212

14.2. UN proper shipping name ISOBUTANOL

14.3. Transport hazard class(es) 3 14.4. Packing group III

ADR

**14.1. UN number** UN1212

14.2. UN proper shipping name ISOBUTANOL

Isobutanol Revision Date 09-Feb-2024

14.3. Transport hazard class(es) 3 14.4. Packing group III

IATA

14.1. UN numberUN121214.2. UN proper shipping nameISOBUTANOL

14.3. Transport hazard class(es) 3 14.4. Packing group III

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

## **SECTION 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **International Inventories**

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Isobutyl alcohol	78-83-1	201-148-0	-	-	Х	Χ	KE-24894	Χ	Χ
Component	CAS No	TSCA	TSCA Ir	ventory	DSL	NDSL	AICS	NZIoC	PICCS

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIOC	PICCS
Isobutyl alcohol	78-83-1	Х	ACTIVE	X	-	X	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Isobutyl alcohol	78-83-1	-	Use restricted. See item 75. (see link for restriction details)	-

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report
		Notification	Requirements
Isobutyl alcohol	78-83-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Isobutanol Revision Date 09-Feb-2024

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

#### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class		
Isobutyl alcohol	WGK1			

Γ	Component	France - INRS (Tables of occupational diseases)
	Isobutyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure	
Isobutyl alcohol 78-83-1 ( 99 )		Group I		

#### 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

## **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H226 - Flammable liquid and vapor

## Legend

CAS - Chemical Abstracts Service TSCA - United States Toxic Substances Control Act Section 8(b)

Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances **ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit TWA - Time Weighted Average

IARC - International Agency for Research on Cancer **ACGIH** - American Conference of Governmental Industrial Hygienists

Isobutanol Revision Date 09-Feb-2024

**Transport Association** 

ATE - Acute Toxicity Estimate
VOC - (Volatile Organic Compound)

ICAO/IATA - International Civil Aviation Organization/International Air

MARPOL - International Convention for the Prevention of Pollution from

DNEL - Derived No Effect Level Predicted No Effect Concentration (PNEC)

RPE - Respiratory Protective Equipment
LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**Training Advice** 

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Ships

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By Health, Safety and Environmental Department

Creation Date22-Jan-2009Revision Date09-Feb-2024

**Revision Summary** New emergency telephone response service provider.

# This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**