

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane
 Cat No. : **40038**
 Molecular Formula C15 H35 O5 Ta

Unique Formula Identifier (UFI) **E3AP-06VU-SX0R-5EKP**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
 Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Avocado Research Chemicals Ltd.
 (Part of Thermo Fisher Scientific)
 Shore Road, Heysham
 Lancashire, LA3 2XY,
 United Kingdom
 Office Tel: +44 (0) 1524 850506
 Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency information services **Ireland** : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids	Category 2 (H225)
Substances/mixtures which, in contact with water, emit flammable gases	Category 1 (H260)

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

Health hazards

Aspiration Toxicity	Category 1 (H304)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Reproductive Toxicity	Category 2 (H361f)
Specific target organ toxicity - (single exposure)	Category 3 (H336)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)

Environmental hazards

Chronic aquatic toxicity	Category 2 (H411)
--------------------------	-------------------

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H260 - In contact with water releases flammable gases which may ignite spontaneously
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H336 - May cause drowsiness or dizziness
H361f - Suspected of damaging fertility
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P231 + P232 - Handle and store contents under inert gas. Protect from moisture
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to
-----------	--------	-------	----------	-----------------------------------

ALFAA40038

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

				GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Isopropyl alcohol	67-63-0	200-661-7	45.00	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336)
Hexane	110-54-3	EEC No. 203-777-6	45.00	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361f) STOT RE 2 (H373) Aquatic Chronic 2 (H411)
Tantalum(V) isopropoxide	16761-83-4		10.00	Water-react. 1 (H260) Skin Corr. 1B (H314) Eye Dam. 1 (H318)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Hexane	STOT RE 2 (H373) :: C>=5%	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting; Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

None under normal use conditions.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 Class 4.3
Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Isopropyl alcohol	STEL: 500 ppm 15 min STEL: 1250 mg/m ³ 15 min TWA: 400 ppm 8 hr TWA: 999 mg/m ³ 8 hr		TWA: 200 ppm 8 hr. STEL: 400 ppm 15 min Skin
Hexane	TWA: 72 mg/m ³ TWA: 20 ppm STEL: 60 ppm STEL: 216 mg/m ³	TWA: 20 ppm (8hr) TWA: 72 mg/m ³ (8hr)	TWA: 20 ppm 8 hr. TWA: 72 mg/m ³ 8 hr. STEL: 60 ppm 15 min STEL: 216 mg/m ³ 15 min Skin

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Isopropyl alcohol 67-63-0 (45.00)				DNEL = 888mg/kg bw/day
Hexane 110-54-3 (45.00)				DNEL = 11mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Isopropyl alcohol 67-63-0 (45.00)				DNEL = 500mg/m ³
Hexane				DNEL = 75mg/m ³

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

110-54-3 (45.00)			
--------------------	--	--	--

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Isopropyl alcohol 67-63-0 (45.00)	PNEC = 140.9mg/L	PNEC = 552mg/kg sediment dw	PNEC = 140.9mg/L	PNEC = 2251mg/L	PNEC = 28mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Isopropyl alcohol 67-63-0 (45.00)	PNEC = 140.9mg/L	PNEC = 552mg/kg sediment dw		PNEC = 160mg/kg food	

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Yellow	
Odor	Petroleum distillates	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	-23 °C / -9.4 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Isopropyl alcohol	0.05	
Hexane	4.11	
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C15 H35 O5 Ta
Molecular Weight	476.39
Explosive Properties	Vapors may form explosive mixtures with air
Substances/mixtures which, in contact with water, emit flammable gases	Emitted gas ignites spontaneously

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Yes

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

ALFAA40038

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5045 mg/kg (Rat) 3600 mg/kg (Mouse)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
Hexane	LD50 = 25 g/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 = 48000 ppm (Rat) 4 h

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Category 2

(h) STOT-single exposure; Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure; Category 2

Target Organs

Central nervous system (CNS), Peripheral Nervous System (PNS).

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

delayed tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Isopropyl alcohol	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 10000000 µg/L, 96h (Daphnia)	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)
Hexane	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	EC50: 3.87 mg/L/48h	

Component	Microtox	M-Factor
Isopropyl alcohol	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	

12.2. Persistence and degradability No information available
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential No information available

Component	log Pow	Bioconcentration factor (BCF)
Isopropyl alcohol	0.05	No data available
Hexane	4.11	No data available

12.4. Mobility in soil No information available

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

12.7. Other adverse effects
Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number

UN1993

14.2. UN proper shipping name

Flammable liquid, n.o.s.

Technical Shipping Name

(Tantalum isopropoxide, Isopropanol, Hexanesolution)

14.3. Transport hazard class(es)

3

14.4. Packing group

II

ADR

14.1. UN number

UN1993

14.2. UN proper shipping name

Flammable liquid, n.o.s.

Technical Shipping Name

(Tantalum isopropoxide, Isopropanol, Hexanesolution)

14.3. Transport hazard class(es)

3

14.4. Packing group

II

IATA

14.1. UN number

UN1993

14.2. UN proper shipping name

Flammable liquid, n.o.s.

Technical Shipping Name

(Tantalum isopropoxide, Isopropanol, Hexanesolution)

14.3. Transport hazard class(es)

3

14.4. Packing group

II

14.5. Environmental hazards

Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user

No special precautions required.

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Isopropyl alcohol	67-63-0	200-661-7	-	-	X	X	KE-29363	X	X
Hexane	110-54-3	203-777-6	438-390-3	-	X	X	KE-18626	X	X
Tantalum(V) isopropoxide	16761-83-4	-	-	-	-	X	-	-	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Isopropyl alcohol	67-63-0	X	ACTIVE	X	-	X	X	X
Hexane	110-54-3	X	ACTIVE	X	-	X	X	X
Tantalum(V) isopropoxide	16761-83-4	-	-	-	-	-	-	-

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Isopropyl alcohol	67-63-0	-	Use restricted. See item 75. (see link for restriction details)	-
Hexane	110-54-3	-	Use restricted. See item 75. (see link for restriction details)	-
Tantalum(V) isopropoxide	16761-83-4	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Isopropyl alcohol	67-63-0	Not applicable	Not applicable
Hexane	110-54-3	Not applicable	Not applicable
Tantalum(V) isopropoxide	16761-83-4	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Isopropyl alcohol	WGK1	
Hexane	WGK2	

Component	France - INRS (Tables of occupational diseases)
Isopropyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Hexane	Tableaux des maladies professionnelles (TMP) - RG 59, RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Isopropyl alcohol 67-63-0 (45.00)		Group I	
Hexane 110-54-3 (45.00)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H260 - In contact with water releases flammable gases which may ignite spontaneously

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H361f - Suspected of damaging fertility

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation

H319 - Causes serious eye irritation

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical

SAFETY DATA SHEET

Tantalum(V) isopropoxide, 10% w/v in isopropanol/hexane

Revision Date 23-May-2024

Substances/EU List of Notified Chemical Substances

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

AICS - Australian Inventory of Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

TWA - Time Weighted Average

ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer

DNEL - Derived No Effect Level

Predicted No Effect Concentration (PNEC)

RPE - Respiratory Protective Equipment

LD50 - Lethal Dose 50%

LC50 - Lethal Concentration 50%

EC50 - Effective Concentration 50%

NOEC - No Observed Effect Concentration

POW - Partition coefficient Octanol:Water

PBT - Persistent, Bioaccumulative, Toxic

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from Ships

OECD - Organisation for Economic Co-operation and Development

ATE - Acute Toxicity Estimate

BCF - Bioconcentration factor

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Prepared By Health, Safety and Environmental Department

Creation Date 19-Apr-2018

Revision Date 23-May-2024

Revision Summary New emergency telephone response service provider.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet