

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 24-Nov-2010

Revision Date 18-Oct-2023

**Revision Number** 8

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE **COMPANY/UNDERTAKING**

1.1. Product identifier	
Product Description: Cat No. :	<u>Universal indicator contains methylated spirit</u> U/0020/05, U/0020/07, U/0020/08, U/0020/17, U/0020/PB05, U/0020/PB08, U/0020/PB17
Unique Formula Identifier (UFI)	MW0G-S2MW-8X0U-3KR7
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Recommended Use Uses advised against	Laboratory chemicals. No Information available
1.3. Details of the supplier of the sa	afety data sheet
Company	UK entity/business name   Fisher Scientific UK   Bishop Meadow Road, Loughborough,   Leicestershire LE11 5RG, United Kingdom   EU entity/business name   Thermo Fisher Scientific   Janssen Pharmaceuticalaan 3a   2440 Geel, Belgium
E-mail address	begel.sdsdesk@thermofisher.com
1.4. Emergency telephone number	Tel: 01509 231166 Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887
Poison Centre - Emergency information services	Ireland : National Poisons Information Centre (NPIC) - 01 809 2166 (8am-10pm, 7 days a week) Malta : +356 2395 2000 Cyprus : +357 2240 5611

**SECTION 2: HAZARDS IDENTIFICATION** 

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

## **Physical hazards**

Flammable liquids

Category 2 (H225)

## Universal indicator contains methylated spirit

## Health hazards

Acute oral toxicity Acute dermal toxicity Acute Inhalation Toxicity - Vapors Serious Eye Damage/Eye Irritation Specific target organ toxicity - (single exposure)

## **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

#### **Hazard Statements**

- H225 Highly flammable liquid and vapor
- H319 Causes serious eye irritation
- H371 May cause damage to organs

H302 + H312 + H332 - Harmful if swallowed, in contact with skin or if inhaled

## **Precautionary Statements**

P280 - Wear protective gloves/protective clothing/eye protection/face protection

- P302 + P352 IF ON SKIN: Wash with plenty of soap and water
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P240 Ground and bond container and receiving equipment
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

## 2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Ethyl alcohol	64-17-5	200-578-6	80 - 90	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)
Methyl alcohol	67-56-1	200-659-6	3 - 10	Flam. Liq. 2 (H225)

Category 4 (H302) Category 4 (H312) Category 4 (H332) Category 2 (H319) Category 2 (H371)

## Universal indicator contains methylated spirit

## Revision Date 18-Oct-2023

				Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Methyl Red sodium salt	845-10-3	EEC No. 212-682-9	< 0.5	-
1(3H)-Isobenzofuranone,	518-51-4	EEC No. 208-254-6	< 0.5	-
3,3-bis(4-hydroxyphenyl)-, disodium salt				
Phenol,	34722-90-2	EEC No. 252-169-7	< 0.5	-
4,4'-(3H-2,1-benzoxathiol-3-ylidene)bis[2-br				
omo-3-methyl-6-(1-methylethyl)-,				
S,S-dioxide, monosodium salt				
Water	7732-18-5	231-791-2	1 - 10	-

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Ethyl alcohol	Eye Irrit. 2 :: C>=50%	-	-
Methyl alcohol	STOT Single Exp. 1 :: >= 10	-	-
	STOT Single Exp. 2 :: 3 - < 10		

Components	Reach Registration Number	
Ethanol	01-2119457610-43	
Methanol	01-2119433307-44	

## Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

## 4.1. Description of first aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.					
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.					
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting without medical advice.					
Inhalation	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If not breathing, give artificial respiration.					
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.					
4.2. Most important symptoms and	effects, both acute and delayed					
	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting					
4.3. Indication of any immediate me	4.3. Indication of any immediate medical attention and special treatment needed					
Notes to Physician	Treat symptomatically. Symptoms may be delayed.					

## SECTION 5: FIREFIGHTING MEASURES

## Universal indicator contains methylated spirit

## 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water mist may be used to cool closed containers. Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

#### Extinguishing media which must not be used for safety reasons No information available.

no information available.

## 5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

## Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Formaldehyde.

## 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

## 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

## **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

Class 3

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

## Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE -** 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC

Component	The United Kingdom	European Union	Ireland
Ethyl alcohol	TWA: 1000 ppm TWA; 1920		STEL: 1000 ppm 15 min
	mg/m³ TWA		
	WEL - STEL: 3000 ppm		
	STEL; 5760 mg/m <sup>3</sup> STEL		
Methyl alcohol	WEL - TWA: 200 ppm TWA;	TWA: 200 ppm 8 hr	TWA: 200 ppm 8 hr.
	266 mg/m <sup>3</sup> TWA	TWA: 260 mg/m <sup>3</sup> 8 hr	TWA: 260 mg/m <sup>3</sup> 8 hr.
	WEL - STEL: 250 ppm	Skin	STEL: 600 ppm 15 min
	STEL; 333 mg/m <sup>3</sup> STEL		STEL: 780 mg/m <sup>3</sup> 15 min
	_		Skin

**Biological limit values** 

List source(s):

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local	Acute effects	Chronic effects local	Chronic effects
	(Oral)	systemic (Oral)	(Oral)	systemic (Oral)
Ethyl alcohol 64-17-5 ( 80 - 90 )		DNEL = 87 mg/kg bw/d		

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl alcohol 64-17-5 ( 80 - 90 )				DNEL = 343mg/kg bw/day
Methyl alcohol 67-56-1(3 - 10)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethyl alcohol 64-17-5 ( 80 - 90 )	DNEL = 1900mg/m <sup>3</sup>			DNEL = 950mg/m <sup>3</sup>
Methyl alcohol 67-56-1 ( 3 - 10 )	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>

Predicted No Effect Concentration (PNEC)

See values below.

## Universal indicator contains methylated spirit

Component	Fresh water	Fresh water sediment		Microorganisms in sewage treatment	,
Methyl alcohol	PNEC = 20.8mg/L	PNEC = 77mg/kg	PNEC = 1540mg/L	PNEC = 100mg/L	00
67-56-1 (3 - 10)		sediment dw			soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl alcohol	PNEC = 2.08mg/L	PNEC = 7.7mg/kg			
67-56-1 (3 - 10)		sediment dw			

## 8.2. Exposure controls

## Engineering Measures

**Eye Protection** 

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

## Personal protective equipment

Goggles (European standard - EN 166)

Hand Protection	Protective gloves
-----------------	-------------------

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	> 480 minutes	0.38 mm - 0.56 mm	EN 374	(minimum requirement)
Neoprene	> 480 minutes	0.45 mm		
PVC	< 60 minutes	0.18 mm		
Viton (R)	> 480 minutes	0.7 mm		

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced <b>Recommended Filter type:</b> low boiling organic solvent Type AX Brown conforming to EN371
Small scale/Laboratory use	Maintain adequate ventilation Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. <b>Recommended half mask:-</b> Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
Environmental exposure controls	Prevent product from entering drains. Do not allow material to contaminate ground water

## system.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

## 9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	Alcohol-like	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 3.3 vol %	
	Upper 19 vol %	
Flash Point	12 °C / 53.6 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
рН	No information available	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/wate	er)	
Component	log Pow	
Ethyl alcohol	-0.32	
Methyl alcohol	-0.74	
Vapor Pressure	No information available	
Density / Specific Gravity	0.8	
Bulk Density	Not applicable	Liquid
Vapor Density	No information available	(Air = 1.0)
Particle characteristics	(liquid) Not applicable	

## 9.2. Other information

Explosive Properties Evaporation Rate Vapors may form explosive mixtures with air No information available

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity	None known, based on information available
10.2. Chemical stability	Stable under normal conditions.
10.3. Possibility of hazardous react	ions
Hazardous Polymerization Hazardous Reactions	Hazardous polymerization does not occur. None under normal processing.
10.4. Conditions to avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.
10.5. Incompatible materials	Strong oxidizing agents.

## Universal indicator contains methylated spirit

## 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Formaldehyde.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Product Information** 

(a) acute toxicity;	
Oral	Category 4
Dermal	Category 4
Inhalation	Category 4

## Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg	-	LC50 = 117-125 mg/l (4h)
	OECD 401 (Rat)		OECD 403 (rat)
	3450 mg/kg ( Mouse )		20000 ppm/10H (rat)
Methyl alcohol	LD50 = 1187 - 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L ( Rat ) 4 h
Water	-	-	-

## (b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; Category 2

## (d) respiratory or skin sensitization;

Respiratory Skin No data available No data available

Component	Test method	Test species	Study result
Ethyl alcohol	Mouse Ear Swelling Test (MEST)	mouse	non-sensitising
64-17-5 ( 80 - 90 )			
		mouse	non-sensitising
	OECD Test Guideline 429		
	Local Lymph Node Assay		
Methyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
67-56-1 (3 - 10)	Guinea Pig Maximisation Test		
	(GPMT)		

## (e) germ cell mutagenicity;

## No data available

Component	Test method	Test species	Study result
Ethyl alcohol	AMES test	in vitro	negative
64-17-5 ( 80 - 90 )	OECD Test Guideline 471	Bacteria	-
	Gene cell mutation		
	OECD Test Guideline 476	in vitro	negative
		Mammalian	_

## (f) carcinogenicity;

## No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

(g) reproductive toxicity;	No data available		
Component	Test method	Test species / Duration	Study result
Ethyl alcohol	OECD Test Guideline 416	Oral / mouse	NOAEL = 13.8 g/kg/day

## Universal indicator contains methylated spirit

Revision Date 18-Oct-2023

64-17-5(80 - 90)	OECD Test Guideline 414	2 Generation	
		Inhalation / Rat	NOAEC = 16000 ppm
Methyl alcohol 67-56-1 ( 3 - 10 )	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

(h) STOT-single exposure;	Category 2
Results / Target organs	Optic nerve, Central nervous system (CNS).
(i) STOT-repeated exposure;	No data available
Target Organs	No information available.
(j) aspiration hazard;	No data available
Symptoms / effects,both acute and delayed	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

Endocrine Disrupting Properties	Assess endocrine disrupting properties for human health. This product does not contain any
	known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

## 12.1. Toxicity Ecotoxicity effects

Contains a substance which is:. Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethyl alcohol	Fathead minnow (Pimephales	EC50 = 9268 mg/L/48h	EC50 (72h) = 275 mg/l (Chlorella
	promelas) LC50 = 14200 mg/l/96h	EC50 = 10800 mg/L/24h	vulgaris)
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	

Component	Microtox	M-Factor
Ethyl alcohol	Photobacterium phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min	
Methyl alcohol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

## 12.2. Persistence and degradability

Persistence Persistence is unlikely.

Com	ponent	Degradability
Ethyl	alcohol	OECD 301E = 94%
64-17-5	5 ( 80 - 90 )	
Methy	/l alcohol	DT50 ~ 17.2d
67-56-	1 ( 3 - 10 )	>94% after 20d
Degradation in sewage	Contains substances known to b	e hazardous to the environment or not degradable in waste
treatment plant	water treatment plants.	

#### 12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available
Methyl alcohol	-0.74	<10 dimensionless

12.4. Mobility in soil	The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils
12.5. Results of PBT and vPvB assessment	No data available for assessment.
<u>12.6. Endocrine disrupting</u> properties Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

## **SECTION 14: TRANSPORT INFORMATION**

## IMDG/IMO

14.1. UN number	UN1170
14.2. UN proper shipping name	Ethanol solution
14.3. Transport hazard class(es)	3
14.4. Packing group	II

## <u>ADR</u>

14.1. UN number	UN1170
14.2. UN proper shipping name	Ethanol s
14.3. Transport hazard class(es)	3

solution

Universal indicator contains methylated spirit

14.4. Packing group

<u>14.1. UN number</u> 14.2. UN proper shipping name 14.3. Transport hazard class(es) 14.4. Packing group	UN1170 Ethanol solution 3 II
14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

Π

## **SECTION 15: REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl alcohol	64-17-5	200-578-6	-	-	Х	Х	KE-13217	Х	Х
Methyl alcohol	67-56-1	200-659-6	-	-	Х	Х	KE-23193	Х	Х
Methyl Red sodium salt	845-10-3	212-682-9	-	-	Х	Х	KE-11175	-	-
1(3H)-Isobenzofuranone, 3,3-bis(4-hydroxyphenyl)-, disodium salt	518-51-4	208-254-6	-	-	-	Х	-	-	-
Phenol, 4,4'-(3H-2,1-benzoxathiol-3-yliden e)bis[2-bromo-3-methyl-6-(1-meth ylethyl)-, S,S-dioxide, monosodium salt	34722-90-2	252-169-7	-	-	Х	Х	-	-	-
Water	7732-18-5	231-791-2	-	-	Х	Х	KE-35400	Х	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl alcohol	64-17-5	Х	ACTIVE	Х	-	Х	Х	Х
Methyl alcohol	67-56-1	Х	ACTIVE	Х	-	Х	Х	Х
Methyl Red sodium salt	845-10-3	Х	ACTIVE	Х	-	Х	Х	Х
1(3H)-Isobenzofuranone, 3,3-bis(4-hydroxyphenyl)-, disodium salt	518-51-4	Х	ACTIVE	х	-	-	X	-
Phenol, 4,4'-(3H-2,1-benzoxathiol-3-yliden e)bis[2-bromo-3-methyl-6-(1-meth ylethyl)-, S,S-dioxide, monosodium salt	34722-90-2	Х	ACTIVE	Х	-	Х	Х	Х
Water	7732-18-5	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

## Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	<b>REACH Regulation (EC</b>
-		Annex XIV - Substances	Annex XVII - Restrictions	1907/2006) article 59 -

## Universal indicator contains methylated spirit

#### Revision Date 18-Oct-2023

		Subject to Authorization	on Certain Dangerous Substances	Candidate List of Substances of Very High Concern (SVHC)
Ethyl alcohol	64-17-5	-	-	-
Methyl alcohol	67-56-1	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Methyl Red sodium salt	845-10-3	-	-	-
1(3H)-Isobenzofuranone, 3,3-bis(4-hydroxyphenyl)-, disodium salt	518-51-4	-	-	-
Phenol, 4,4'-(3H-2,1-benzoxathiol-3-ylidene) bis[2-bromo-3-methyl-6-(1-methylet hyl)-, S,S-dioxide, monosodium salt	34722-90-2	-	-	-
Water	7732-18-5	-	-	-

## **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

## Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl alcohol	64-17-5	Not applicable	Not applicable
Methyl alcohol	67-56-1	500 tonne	5000 tonne
Methyl Red sodium salt	845-10-3	Not applicable	Not applicable
1(3H)-Isobenzofuranone, 3,3-bis(4-hydroxyphenyl)-, disodium salt	518-51-4	Not applicable	Not applicable
Phenol, 4,4'-(3H-2,1-benzoxathiol-3- ylidene)bis[2-bromo-3-methy I-6-(1-methylethyl)-, S,S-dioxide, monosodium salt	34722-90-2	Not applicable	Not applicable
Water	7732-18-5	Not applicable	Not applicable

# Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

## Universal indicator contains methylated spirit

## Revision Date 18-Oct-2023

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Ethyl alcohol	WGK1	
Methyl alcohol	WGK 2	Class I : 20 mg/m <sup>3</sup> (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl alcohol 64-17-5(80 - 90)		Group I	
Methyl alcohol 67-56-1(3 - 10)	Prohibited and Restricted Substances	Group I	
Methyl Red sodium salt 845-10-3 ( < 0.5 )	Prohibited and Restricted Substances		
Phenol, 4,4'-(3H-2,1-benzoxathiol-3-ylidene)bis[2-br omo-3-methyl-6-(1-methylethyl)-, S,S-dioxide, monosodium salt 34722-90-2 (<0.5)	Prohibited and Restricted Substances		

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## **SECTION 16: OTHER INFORMATION**

## Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H370 - Causes damage to organs

H319 - Causes serious eye irritation

## Legend

CAS - Chemical Abstracts Service	<b>TSCA</b> - United States Toxic Substances Control Act Section 8(b) Inventory
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances	<b>,</b>
WEL - Workplace Exposure Limit	TWA - Time Weighted Average
ACGIH - American Conference of Governmental Industrial Hygienists	IARC - International Agency for Research on Cancer
DNEL - Derived No Effect Level	Predicted No Effect Concentration (PNEC)
RPE - Respiratory Protective Equipment	LD50 - Lethal Dose 50%
LC50 - Lethal Concentration 50%	EC50 - Effective Concentration 50%
NOEC - No Observed Effect Concentration	<b>POW</b> - Partition coefficient Octanol:Water
PBT - Persistent, Bioaccumulative, Toxic	vPvB - very Persistent, very Bioaccumulative

## Universal indicator contains methylated spirit

ADR - European Agreement Concerning the International Carriage of	ICAO/IATA - International Civil Aviation Organization/International Air
Dangerous Goods by Road	Transport Association
IMO/IMDG - International Maritime Organization/International Maritime	MARPOL - International Convention for the Prevention of Pollution from
Dangerous Goods Code	Ships
OECD - Organisation for Economic Co-operation and Development	ATE - Acute Toxicity Estimate
BCF - Bioconcentration factor	VOC - (Volatile Organic Compound)
Key literature references and sources for data	
https://echa.europa.eu/information-on-chemicals	
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, I	RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:Physical hazardsOn basis of test dataHealth HazardsCalculation methodEnvironmental hazardsCalculation method

## **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date	24-Nov-2010
Revision Date	18-Oct-2023
Revision Summary	Not applicable.

# This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# **End of Safety Data Sheet**