

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 21-Oct-2014 Revision Date 29-Sep-2023 Revision Number 7

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description: <u>3-Methyl-2-butenal</u>

 Cat No. :
 370180000; 370180050; 370180250; 370181000

 Synonyms
 3-Methylcrotonaldehyde; Prenal; 3,3-Dimethylacrolein

 CAS No
 107-86-8

 EC No
 203-527-6

 Molecular Formula
 C5 H8 O

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

#### 1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name

Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

**E-mail address** begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

**Physical hazards** 

Flammable liquids Category 3 (H226)

**Health hazards** 

#### 3-Methyl-2-butenal Revision Date 29-Sep-2023

Category 4 (H302) Acute oral toxicity Acute Inhalation Toxicity - Vapors Category 3 (H331)

Skin Corrosion/Irritation

Category 1 B (H314) Serious Eye Damage/Eye Irritation Category 1 (H318)

Skin Sensitization Category 1 (H317)

#### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



### Signal Word

Danger

#### **Hazard Statements**

H226 - Flammable liquid and vapor

H331 - Toxic if inhaled

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

#### **Precautionary Statements**

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

### 2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
2-Butenal, 3-methyl-	107-86-8	EEC No. 203-527-6	>95	Flam. Liq. 3 (H226) Acute Tox. 4 (H302) Acute Tox. 3 (H331)

3-Methyl-2-butenal Revision Date 29-Sep-2023

	Skin Corr. 1B (H314)
	Eye Dam. 1 (H318)
	Skin Sens. 1 (H317)

Full text of Hazard Statements: see section 16

### **SECTION 4: FIRST AID MEASURES**

### 4.1. Description of first aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact In the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately.

**Inhalation** Do not use mouth-to-mouth method if victim ingested or inhaled the substance: give

artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is

required. If not breathing, give artificial respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. May cause allergic skin reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle

pain or flushing

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

### Extinguishing media which must not be used for safety reasons

No information available.

### 5.2. Special hazards arising from the substance or mixture

#### 3-Methyl-2-butenal

Revision Date 29-Sep-2023

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO2), Thermal decomposition can lead to release of irritating gases and vapors.

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

#### 6.3. Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

### **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

#### 7.2. Conditions for safe storage, including any incompatibilities

Corrosives area. Keep away from heat, sparks and flame. To maintain product quality: Keep refrigerated. Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

### 7.3. Specific end use(s)

Use in laboratories

Revision Date 29-Sep-2023

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### 8.1. Control parameters

#### **Exposure limits**

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

#### **Biological limit values**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
2-Butenal, 3-methyl- 107-86-8 ( >95 )		DNEL = 2mg/kg bw/day		DNEL = 1mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
2-Butenal, 3-methyl- 107-86-8 ( >95 )	DNEL = 3mg/m <sup>3</sup>	DNEL = 3mg/m <sup>3</sup>	DNEL = 3mg/m <sup>3</sup>	DNEL = 3mg/m <sup>3</sup>

#### **Predicted No Effect Concentration (PNEC)**

See values below.

ſ	Component	Fresh water			3	
L			sediment		sewage treatment	
Γ	2-Butenal, 3-methyl-	PNEC =	PNEC =	PNEC =	PNEC = 10mg/L	PNEC =
	107-86-8 ( >95 )	0.00127mg/L	0.00265mg/kg	0.0127mg/L		0.00019mg/kg soil
L			sediment dw			dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
2-Butenal, 3-methyl-	PNEC =				
107-86-8 (>95)	0.00013mg/L				

### 8.2. Exposure controls

### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Goggles (European standard - EN 166) **Eye Protection** 

**Hand Protection** Protective gloves

3-Methyl-2-butenal Revision Date 29-Sep-2023

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Neoprene	recommendations			
Natural rubber				
PVC				

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### 9.1. Information on basic physical and chemical properties

Physical State Liquid

**Appearance** Clear

Odor No information available
Odor Threshold No data available
Melting Point/Range No data available
Softening Point No data available

**Boiling Point/Range** 132 - 133 °C / 269.6 - 271.4 °F

Flammability (liquid) Flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Flash Point 33 °C / 91.4 °F Method - No information available

Autoignition Temperature
Decomposition Temperature
pH
Viscosity
No data available
No information available
No data available
No data available
Soluble

Solubility in other solvents

No information available

Partition Coefficient (n-octanol/water)

**Component** log Pow 2-Butenal, 3-methyl- 0.53

3-Methyl-2-butenal Revision Date 29-Sep-2023

Vapor Pressure No data available

Density / Specific Gravity 0.880

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C5 H8 O Molecular Weight 84.12

**Explosive Properties** explosive air/vapour mixtures possible

### **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Air sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to air.

10.5. Incompatible materials

Strong oxidizing agents. Acids. Bases.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Thermal decomposition can lead to release

of irritating gases and vapors.

### **SECTION 11: TOXICOLOGICAL INFORMATION**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity:

Oral Category 4

**Dermal** Based on available data, the classification criteria are not met

Inhalation Category 3

Component	Component LD50 Oral		LC50 Inhalation		
2-Butenal, 3-methyl-	650 mg/kg (Rat)	LD50 = 3400 mg/kg (Rat)	LC50 = 3.7 mg/L (Rat) 4 h		

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

3-Methyl-2-butenal Revision Date 29-Sep-2023

(d) respiratory or skin sensitization;

Respiratory No data available Skin Category 1

May cause sensitization by skin contact

No data available (e) germ cell mutagenicity;

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

No data available (h) STOT-single exposure;

No data available (i) STOT-repeated exposure;

No information available. **Target Organs** 

(j) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

### 11.2. Information on other hazards

**Endocrine Disrupting Properties** 

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

#### **SECTION 12: ECOLOGICAL INFORMATION**

12.1. Toxicity

Do not empty into drains. Contains a substance which is:. Harmful to aquatic organisms. **Ecotoxicity effects** The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
2-Butenal, 3-methyl-		EC50: = 13.5 mg/L, 48h	EC50: = 22.9 mg/L, 96h
		(Daphnia magna)	(Desmodesmus subspicatus)
			EC50: = 19.9 mg/L, 72h
			(Desmodesmus subspicatus)

Component	Microtox	M-Factor
2-Butenal, 3-methyl-	EC50 = 106 mg/L 30 min	
	EC50 = 148 mg/L 15 min	
	EC50 = 178 mg/L 17 h	

3-Methyl-2-butenal Revision Date 29-Sep-2023

12.2. Persistence and degradability

Persistence

Persistence is unlikely.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
2-Butenal, 3-methyl-	0.53	No data available

12.4. Mobility in soil The product is water soluble, and may spread in water systems . Will likely be mobile in the

environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** 

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

**Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** 

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

**European Waste Catalogue (EWC)** 

According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

## **SECTION 14: TRANSPORT INFORMATION**

#### IMDG/IMO

UN2920 14.1. UN number

14.2. UN proper shipping name Corrosive liquid, flammable, n.o.s.

**Technical Shipping Name** 2-Butenal, 3-methyl-

14.3. Transport hazard class(es) 8 3 **Subsidiary Hazard Class** 

3-Methyl-2-butenal Revision Date 29-Sep-2023

14.4. Packing group II

ADR

14.1. UN number UN2920

14.2. UN proper shipping name Corrosive liquid, flammable, n.o.s.

**Technical Shipping Name** 2-Butenal, 3-methyl-

14.3. Transport hazard class(es) 3 **Subsidiary Hazard Class** 14.4. Packing group II

IATA

UN2920 14.1. UN number

14.2. UN proper shipping name Corrosive liquid, flammable, n.o.s.

**Technical Shipping Name** 2-Butenal, 3-methyl-

14.3. Transport hazard class(es) **Subsidiary Hazard Class** 3 II 14.4. Packing group

No hazards identified 14.5. Environmental hazards

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk

according to IMO instruments

# **SECTION 15: REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable, packaged goods

**International Inventories** 

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
2-Butenal, 3-methyl-	107-86-8	203-527-6	i	ı	X	X	-	X	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
2-Butenal, 3-methyl-	107-86-8	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### Authorisation/Restrictions according to EU REACH Not applicable

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
-		Annex XIV - Substances	Annex XVII - Restrictions	1907/2006) article 59 -
		Subject to Authorization	on Certain Dangerous	Candidate List of
			Substances	Substances of Very High
				Concern (SVHC)
2-Butenal, 3-methyl-	107-86-8	-	-	=

#### Seveso III Directive (2012/18/EC)

Component CAS No Seveso III Directive (2012/18/EC) - Seveso III Directive (2012/18/EC) -
--

#### 3-Methyl-2-butenal

**Qualifying Quantities for Major Accident Qualifying Quantities for Safety Report Notification** Requirements 2-Butenal, 3-methyl-107-86-8 Not applicable Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
2-Butenal, 3-methyl-	WGK1	

#### 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

### **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor

H302 - Harmful if swallowed

H331 - Toxic if inhaled

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

#### Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

Substances List

**ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

**ACR37018** 

Revision Date 29-Sep-2023

#### 3-Methyl-2-butenal Revision Date 29-Sep-2023

**Transport Association** 

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

ICAO/IATA - International Civil Aviation Organization/International Air

MARPOL - International Convention for the Prevention of Pollution from

LC50 - Lethal Concentration 50% EC50 - Effective Concentration 50% NOEC - No Observed Effect Concentration POW - Partition coefficient Octanol:Water PBT - Persistent, Bioaccumulative, Toxic vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code **OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Ships

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

21-Oct-2014 **Creation Date** 29-Sep-2023 **Revision Date Revision Summary** Not applicable.

## This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**