

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 13-Apr-2009 Revision Date 29-Sep-2023 Revision Number 11

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: <u>2-Butanone</u>

Cat No.: 327910000; 327910010; 327910025

Synonyms Methyl ethyl ketone; MEK; Ethyl methyl ketone

 Index No
 606-002-00-3

 CAS No
 78-93-3

 EC No
 201-159-0

 Molecular Formula
 C4 H8 O

REACH registration number -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended UseLaboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals

Process categories PROC15 - Use as a laboratory reagent

Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road.

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name

Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

2-Butanone Revision Date 29-Sep-2023

Flammable liquids Category 2 (H225)

Health hazards

Serious Eye Damage/Eye Irritation Category 2 (H319)
Specific target organ toxicity - (single exposure) Category 3 (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P240 - Ground and bond container and receiving equipment

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Contains a substance on the National Authorities Endocrine Disruptor Lists Contains a known or suspected endocrine disruptor

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

	Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
L	Methyl ethyl ketone	78-93-3	EEC No. 201-159-0	<=100	Flam. Liq. 2 (H225)

2-Butanone Revision Date 29-Sep-2023

		Eye Irrit. 2 (H319) STOT SE 3 (H336)
		(EUH066)

REACH registration number -

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

symptoms occur.

Ingestion Do NOT induce vomiting. Get medical attention.

Inhalation Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial

respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2).

5.3. Advice for firefighters

2-Butanone Revision Date 29-Sep-2023

As in any fire, wear self-contained breething apparatus processes demand MCLIA/NIOCLI (approved or equivalent) and full

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

2-Butanone

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl ethyl ketone	STEL: 300 ppm 15 min	TWA: 200 ppm (8h)	TWA: 200 ppm 8 hr.
	STEL: 899 mg/m ³ 15 min	TWA: 600 mg/m ³ (8h)	TWA: 600 mg/m ³ 8 hr.
	TWA: 200 ppm 8 hr	STEL: 300 ppm (15min)	STEL: 300 ppm 15 min
	TWA: 600 mg/m ³ 8 hr	STEL: 900 mg/m ³ (15min)	STEL: 900 mg/m ³ 15 min
	Skin		Skin

Biological limit values

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

Component	United Kingdom	European Union
Methyl ethyl ketone	Butan-2-one: 70 µmol/L urine post shift	

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

Workers; See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methyl ethyl ketone				DNEL = 1161mg/kg
78-93-3 (<=100)				bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methyl ethyl ketone 78-93-3 (<=100)				DNEL = 600mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Methyl ethyl ketone	PNEC = 55.8mg/L	PNEC =	PNEC = 55.8mg/L	PNEC = 709mg/L	PNEC = 22.5 mg/kg
78-93-3 (<=100)		284.74mg/kg			soil dw
·		sediment dw			

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl ethyl ketone 78-93-3 (<=100)	PNEC = 55.8mg/L	PNEC = 284.7mg/kg sediment dw		PNEC = 1000mg/kg food	

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Revision Date 29-Sep-2023

2-Butanone Revision Date 29-Sep-2023

Hand Protection Protective gloves

Glove materialBreakthrough timeGlove thicknessEU standardGlove commentsButyl rubber< 60 minutes</td>0.5 mmLevel 4Permeation rate 36 μg/cm2/minEN 374As tested under EN374-3 Determination of Resistance to Permeation by Chemicals

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Type A Organic gases and vapours filter Brown conforming to

EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless

Odor Characteristic - sweet
Odor Threshold No data available
Melting Point/Range -87 °C / -124.6 °F
Softening Point No data available
Boiling Point/Range 80 °C / 176 °F
Flammability (liquid) Highly flammable

Flammability (liquid) Highly flammable On basis of test data
Flammability (solid,gas) Not applicable Liquid

Flammability (solid,gas) Not applicable Liver 1.8 Vol%

Upper 11.5 Vol%

Flash Point -7 °C / 19.4 °F Method - CC (closed cup)

Autoignition Temperature
Decomposition Temperature
pH
Viscosity
Viscosity
Viscosity
Viscosity
404 °C / 759.2 °F
No data available
No information available
0.42 mPa.s @ 15°C
290 g/L (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow Methyl ethyl ketone 0.29

2-Butanone Revision Date 29-Sep-2023

Vapor Pressure 105 mbar @ 20 °C

Density / Specific Gravity 0.806

Bulk DensityNot applicableLiquidVapor Density2.41(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular FormulaC4 H8 OMolecular Weight72.11

Explosive PropertiesNot explosive Vapors may form explosive mixtures with air

Oxidizing Properties Not oxidising

Evaporation Rate 3.7 - (Butyl Acetate = 1.0)

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Hygroscopic.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to moist air or water.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Strong reducing agents. Ammonia.

copper. Amines.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl ethyl ketone	LD50 = 2483 mg/kg (Rat)	LD50 = 5000 mg/kg (Rabbit)	LC50 = 11700 ppm (Rat) 4 h

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

2-Butanone Revision Date 29-Sep-2023

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory Skin

Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met (e) germ cell mutagenicity;

Not mutagenic in AMES Test

Based on available data, the classification criteria are not met (f) carcinogenicity;

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Central nervous system (CNS). Results / Target organs

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

None known. **Target Organs**

(j) aspiration hazard; Based on available data, the classification criteria are not met

delayed

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health

Contains a substance on the National Authorities Endocrine Disruptor Lists

Component	EU National Authorities Endocrine Disruptor Lists - Health
Methyl ethyl ketone	List II
78-93-3 (<=100)	

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methyl ethyl ketone	Lepomis macrochirus: LC50=3,22 g/L 96 h	EC50: = 5091 mg/L, 48h (Daphnia magna) EC50: 4025 - 6440 mg/L, 48h Static (Daphnia magna) EC50: > 520 mg/L, 48h (Daphnia magna)	

2-Butanone

Component	Microtox	M-Factor
Methyl ethyl ketone	EC50 = 3403 mg/L 30 min	
	EC50 = 3426 mg/L 5 min	

12.2. Persistence and degradability Readily biodegradable

Persistence Persistence is unlikely, based on information available.

Component	Degradability
Methyl ethyl ketone	98% (28d)
78-93-3 (<=100)	

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl ethyl ketone	0.29	No data available

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

Revision Date 29-Sep-2023

aır

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

2-Butanone Revision Date 29-Sep-2023

14.1. UN number UN1193

14.2. UN proper shipping name Ethyl methyl ketone (Methyl ethyl ketone)

14.3. Transport hazard class(es) 3 14.4. Packing group II

<u>ADR</u>

14.1. UN number UN1193

14.2. UN proper shipping name Ethyl methyl ketone (Methyl ethyl ketone)

14.3. Transport hazard class(es) 3 14.4. Packing group II

IATA

14.1. UN number UN1193

14.2. UN proper shipping name Methyl ethyl ketone

14.3. Transport hazard class(es) 3 14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk

Not applicable, packaged goods

according to IMO instruments

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl ethyl ketone	78-93-3	201-159-0	-	1	X	X	KE-24094	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl ethyl ketone	78-93-3	Х	ACTIVE	X	-	X	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		Candidate List of Substances of Very High
				Concern (SVHC)
Methyl ethyl ketone	78-93-3	-	Use restricted. See item	-
			75.	
			(see link for restriction	
			details)	

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Page 10/12

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
·		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report
		Notification	Requirements
Methyl ethyl ketone	78-93-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl ethyl ketone	WGK1	

Component	France - INRS (Tables of occupational diseases)
Methyl ethyl ketone	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methyl ethyl ketone 78-93-3 (<=100)		Group I	

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

ACR32791

Revision Date 29-Sep-2023

2-Butanone Revision Date 29-Sep-2023

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances Substances List

ENCS - Japanese Existing and New Chemical Substances **AICS** - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

TWA - Time Weighted Average

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development **BCF** - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hvaiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 13-Apr-2009 **Revision Date** 29-Sep-2023 **Revision Summary** Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet