

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 22-Sep-2009 Revision Date 09-Feb-2024 Revision Number 10

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: 4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Cat No. : 377251000; 377258000; 377250000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals. Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name

Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids Category 2 (H225) Substances/mixtures which, in contact with water, emit flammable gases Category 1 (H260)

Health hazards

Aspiration Toxicity

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Category 1 (H304)

Category 1 B (H314)

Category 1 (H318)

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Revision Date 09-Feb-2024

Carcinogenicity

Reproductive Toxicity

Specific target organ toxicity - (single exposure)

Specific target organ toxicity - (repeated exposure)

Category 2 (H351) Category 2 (H361d) Category 3 (H335) (H336) Category 2 (H373)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H260 - In contact with water releases flammable gases which may ignite spontaneously

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eve damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

EUH014 - Reacts violently with water

EUH019 - May form explosive peroxides

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P231 + P232 - Handle and store contents under inert gas. Protect from moisture

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

Reacts violently with water

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

I	Component	CAS No	EC No	Weight %	CLP Classification - According to
1					GB-CLP Regulations UK SI 2019/720 and
					UK SI 2020/1567

Revision Date 09-Feb-2024

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Tetrahydrofuran	109-99-9	203-726-8	40	Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT SE 3 (H336) Carc. 2 (H351) (EUH019)
Toluene	108-88-3	203-625-9	40	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361d) STOT RE 2 (H373)
Bromo(p-chlorophenyl)magnesium	873-77-8	EEC No. 212-853-8	20	Water React. 1 (H260) Skin Corr. 1B (H314) Eye Dam. 1 (H318) (EUH014)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Tetrahydrofuran	Acute Tox. 4 :: C>82.5% Eye Irrit. 2 :: C>=25% STOT SE 3 :: C>=25%	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye ContactRinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

Ingestion Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately. Call a physician or poison control center

immediately. If vomiting occurs naturally, have victim lean forward.

Inhalation If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by

aspiration).

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Revision Date 09-Feb-2024

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Dry chemical. Dry sand. Limestone powder, dry clay, approved class D extinguishers. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water. Carbon dioxide (CO₂). Foam.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen halides, Chlorine, Magnesium oxides, Bromine, Benzene, Hydrogen chloride gas.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Revision Date 09-Feb-2024

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Flammables area. Keep under nitrogen. Keep away from heat, sparks and flame. Protect from direct sunlight. Store at room temperature. Keep from any possible contact with water. Shelf life 12 months. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany) Class 4.3

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Tetrahydrofuran	STEL: 100 ppm 15 min	TWA: 50 ppm (8h)	TWA: 50 ppm 8 hr.
	STEL: 300 mg/m ³ 15 min	TWA: 150 mg/m ³ (8h)	TWA: 150 mg/m ³ 8 hr.
	TWA: 50 ppm 8 hr	STEL: 100 ppm (15min)	STEL: 100 ppm 15 min
	TWA: 150 mg/m ³ 8 hr	STEL: 300 mg/m ³ (15min)	STEL: 300 mg/m ³ 15 min
	Skin	Skin	Skin
Toluene	STEL: 100 ppm 15 min	TWA: 50 ppm (8hr)	TWA: 192 mg/m ³ 8 hr.
	STEL: 384 mg/m ³ 15 min	TWA: 192 mg/m ³ (8hr)	TWA: 50 ppm 8 hr.
	TWA: 50 ppm 8 hr	STEL: 100 ppm (15min)	STEL: 384 mg/m ³ 15 min
	TWA: 191 mg/m ³ 8 hr	STEL: 384 mg/m ³ (15min)	STEL: 100 ppm 15 min
	Skin	Skin	Skin

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

	Component	Acute effects local	Acute effects	Chronic effects local	Chronic effects
L		(Dermal)	systemic (Dermal)	(Dermal)	systemic (Dermal)
	Tetrahydrofuran				DNEL = 12.6mg/kg
	109-99-9 (40)				bw/day
Ī	Toluene				DNEL = 384mg/kg
	108-88-3 (40)				bw/day

	Component	Acute effects local	Acute effects	Chronic effects local	Chronic effects
١		(Inhalation)	systemic (Inhalation)	(Inhalation)	systemic (Inhalation)

Revision Date 09-Feb-2024

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Tetrahydrofuran 109-99-9 (40)	DNEL = 300mg/m ³	DNEL = 96mg/m ³	DNEL = 150mg/m ³	DNEL = 72.4mg/m ³
Toluene 108-88-3 (40)	DNEL = 384mg/m ³	DNEL = 384mg/m ³	DNEL = 192mg/m ³	DNEL = 192mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

	Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
			sediment		sewage treatment	
	Tetrahydrofuran	PNEC = 4.32mg/L	PNEC = 23.3 mg/kg	PNEC = 21.6mg/L	PNEC = 4.6mg/L	PNEC = 2.13mg/kg
	109-99-9 (40)		sediment dw	-	-	soil dw
Г	Toluene	PNEC = 0.68mg/L	PNEC =	PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg
	108-88-3 (40)		16.39mg/kg		_	soil dw
			sediment dw			

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Tetrahydrofuran 109-99-9 (40)	PNEC = 0.432mg/L	PNEC = 2.33mg/kg sediment dw		PNEC = 67mg/kg food	
Toluene 108-88-3 (40)	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	See manufacturers	-	EN 374	(minimum requirement)
Nitrile rubber	recommendations			
Viton (R)				
Neoprene gloves				

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Revision Date 09-Feb-2024

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure Small scale/Laboratory use

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Dark brown **Appearance** Odor Irritating

Odor Threshold No data available Melting Point/Range No data available **Softening Point** No data available **Boiling Point/Range** No information available

Flammability (liquid) Highly flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Flash Point -21 °C / -5.8 °F Method - No information available

Autoignition Temperature No data available **Decomposition Temperature** No data available

pН

No data available **Viscosity**

Reacts violently with water **Water Solubility** Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

log Pow Component Tetrahvdrofuran 0.45 Toluene 2.73

Vapor Pressure No data available

Density / Specific Gravity 1.000

Bulk Density Not applicable Liquid No data available **Vapor Density** (Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

Substances/mixtures which, in Emitted gas ignites spontaneously contact with water, emit flammable

gases

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity Yes. Reacts violently with water. Contact with water liberates extremely flammable gases.

10.2. Chemical stability

May form explosive peroxides. Moisture sensitive. Light sensitive. Reacts violently with

water, liberating extremely flammable gases. Air sensitive.

10.3. Possibility of hazardous reactions

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Handaus Balanceinting Handaus advantage days at any

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing. Reacts violently with water.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Exposure to light. Incompatible products. Exposure to air or moisture over prolonged periods. Exposure to

Revision Date 09-Feb-2024

moist air or water. Exposure to moisture.

10.5. Incompatible materials

Acids. Water. Alcohols.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen halides. Chlorine. Magnesium

oxides. Bromine. Benzene. Hydrogen chloride gas.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product InformationNo acute toxicity information is available for this product

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met Dermal Based on available data, the classification criteria are not met Inhalation Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h
-			53.9 mg/L (Rat) 4 h
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

Component	Test method	Test species	Study result
Tetrahydrofuran	Local Lymph Node Assay	mouse	non-sensitising
109-99-9 (40)	OECD Test Guideline 429		

(e) germ cell mutagenicity; No data available

Component	Test method	Test species	Study result	
Tetrahydrofuran 109-99-9 (40)	OECD Test Guideline 476 Gene cell mutation	in vivo Mammalian	negative	
	OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative	

(f) carcinogenicity; Category 2

Limited evidence of a carcinogenic effect The table below indicates whether each agency

has listed any ingredient as a carcinogen

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B

Category 2 (a) reproductive toxicity:

Component	Test method	Test species / Duration	Study result
Tetrahydrofuran	OECD Test Guideline 416	Rat	NOAEL = 3,000 ppm
109-99-9 (40)		2 Generation	

Reproductive Effects

SUSPECT REPRODUCTIVE HAZARD - CONTAINS MATERIAL WHICH MAY INJURE

Revision Date 09-Feb-2024

UNBORN CHILD (CAUSE BIRTH DEFECTS) (BASED ON ANIMAL DATA).

Teratogenicity

Teratogenic effects have occurred in experimental animals.

(h) STOT-single exposure;

Category 3

Results / Target organs

Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure;

Category 2

Target Organs

Central nervous system (CNS), Eyes, Respiratory system, Kidney, Liver, Skin,

Neuropsychological effects, Ears.

(j) aspiration hazard;

Category 1

Other Adverse Effects

The toxicological properties have not been fully investigated.

delayed

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Causes central nervous system depression.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity **Ecotoxicity effects**

Do not empty into drains. Contains a substance which is:. Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Toxic to aquatic organisms. Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Fish	Water Flea	Freshwater Algae	
Tetrahydrofuran	2160 mg/l LC50 = 96 h	EC50 48 h 3485 mg/l		
	Pimephales promelas	EC50: >10000 mg/L/24h		
	Leuciscus idus: LC50: 2820			
	mg/L/48h			
Toluene	50-70 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h	EC50: = 12.5 mg/L, 72h static	
	5-7 mg/L LC50 96 h	(Daphnia magna)	(Pseudokirchneriella subcapitata)	
	15-19 mg/L LC50 96 h	EC50: 5.46 - 9.83 mg/L, 48h	EC50: > 433 mg/L, 96h	
	28 mg/L LC50 96 h	Static (Daphnia magna)	(Pseudokirchneriella subcapitata)	
	12 mg/L LC50 96 h			

Component	Microtox	M-Factor
Toluene	EC50 = 19.7 mg/L 30 min	

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Revision Date 09-Feb-2024

12.2. Persistence and degradability

Persistence Soluble in water, Persistence is unlikely, based on information available.

Degradability Reacts with water.

Component	Degradability		
Toluene	86% (20d)		
108-88-3 (40)			

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants. Reacts violently with water.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely; Product does not bioaccumulate due to reaction with water

Component	log Pow	Bioconcentration factor (BCF)
Tetrahydrofuran	0.45	No data available
Toluene	2.73	90

12.4. Mobility in soil

The product is water soluble, and may spread in water systems Reacts violently with water . Will likely be mobile in the environment due to its water solubility. Is not likely mobile in the environment. Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

Reacts violently with water.

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

Zilacollilo Diciaptor illiorillation		
Component	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated
	-	Substances
Tetrahydrofuran	Group III Chemical	

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

SECTION 14: TRANSPORT INFORMATION

Revision Date 09-Feb-2024

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

AAA IIN saarbar

14.1. UN number UN3399

14.2. UN proper shipping name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

Technical Shipping Name 4-Chlorophenylmagnesium bromide, Tetrahydrofuran, Toluene

14.3. Transport hazard class(es)4.3Subsidiary Hazard Class314.4. Packing groupI

ADR

14.1. UN number UN3399

14.2. UN proper shipping name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

Technical Shipping Name 4-Chlorophenylmagnesium bromide, Tetrahydrofuran, Toluene

14.3. Transport hazard class(es)4.3Subsidiary Hazard Class314.4. Packing groupI

IATA

14.1. UN number UN3399

<u>14.2. UN proper shipping name</u> Organometallic substance, liquid, water-reactive, flammable 4-Chlorophenylmagnesium bromide, Tetrahydrofuran, Toluene

14.3. Transport hazard class(es)
Subsidiary Hazard Class

14.4. Packing group

Subsidiary Hazard Class

1

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Tetrahydrofuran	109-99-9	203-726-8	ı	ı	X	X	KE-33454	Χ	X
Toluene	108-88-3	203-625-9	-	-	Х	X	KE-33936	Χ	X
Bromo(p-chlorophenyl)magnesium	873-77-8	212-853-8	-	-	-	X	-	-	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Tetrahydrofuran	109-99-9	X	ACTIVE	X	ı	X	X	X
Toluene	108-88-3	X	ACTIVE	Х	-	X	X	Х
Bromo(p-chlorophenyl)magnesium	873-77-8	-	=	-	-	=	X	-

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component		REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	9	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Tetrahydrofuran	109-99-9	-	Use restricted. See item	-

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Revision Date 09-Feb-2024

			75. (see link for restriction details)	
Toluene	108-88-3	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Bromo(p-chlorophenyl)magnesium	873-77-8	-	-	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Tetrahydrofuran	109-99-9	Not applicable	Not applicable
Toluene	ene 108-88-3 Not appli		Not applicable
Bromo(p-chlorophenyl)magn esium	873-77-8	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Tetrahydrofuran	WGK1	
Toluene	WGK3	

Component	France - INRS (Tables of occupational diseases)	
Tetrahydrofuran	Tableaux des maladies professionnelles (TMP) - RG 84	
Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis,RG 84	

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Tetrahydrofuran		Group I	

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

109-99-9 (40) Toluene Prohibited and Restricted Group I 108-88-3 (40) Substances

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H260 - In contact with water releases flammable gases which may ignite spontaneously

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

EUH014 - Reacts violently with water EUH019 - May form explosive peroxides

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

Revision Date 09-Feb-2024

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

Inventory

ENCS - Japanese Existing and New Chemical Substances

Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

On basis of test data Physical hazards **Health Hazards** Calculation method **Environmental hazards** Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

4-Chlorophenylmagnesium bromide, 1M solution in THF/toluene

Revision Date 09-Feb-2024

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Creation Date 22-Sep-2009 **Revision Date** 09-Feb-2024 Not applicable. **Revision Summary**

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet