

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 24-Aug-2009

Revision Date 09-Feb-2024

Revision Number 6

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Cat No. : Synonyms Molecular Formula Ethyl glyoxalate, ca 50% in toluene 425760000; 425760010; 425765000 Ethyl oxoacetate C4 H6 O3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

#### 1.3. Details of the supplier of the safety data sheet

Company

**UK entity/business name** Fisher Scientific UK Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name** Thermo Fisher Scientific Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

begel.sdsdesk@thermofisher.com

E-mail address

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe:** +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe:**001-703-527-3887

### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

 CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

 Physical hazards

 Flammable liquids
 Category 2 (H225)

 Health hazards

 Aspiration Toxicity
 Category 1 (H304)

#### Ethyl glyoxalate, ca 50% in toluene

Skin Corrosion/Irritation Skin Sensitization Reproductive Toxicity Specific target organ toxicity - (single exposure) Specific target organ toxicity - (repeated exposure)

#### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



#### Signal Word

Danger

#### **Hazard Statements**

- H225 Highly flammable liquid and vapor
- H317 May cause an allergic skin reaction
- H304 May be fatal if swallowed and enters airways
- H336 May cause drowsiness or dizziness
- H373 May cause damage to organs through prolonged or repeated exposure
- H315 Causes skin irritation
- H361d Suspected of damaging the unborn child

#### **Precautionary Statements**

- P280 Wear eye protection/ face protection
- P240 Ground and bond container and receiving equipment
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray

#### 2.3. Other hazards

Toxic to terrestrial vertebrates This product does not contain any known or suspected endocrine disruptors

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Toluene	108-88-3	203-625-9	50	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336)

Revision Date 09-Feb-2024

Category 2 (H315) Category 1 (H317) Category 2 (H361d) Category 3 (H336) Category 2 (H373)

#### Ethyl glyoxalate, ca 50% in toluene

#### Revision Date 09-Feb-2024

				Repr. 2 (H361d) STOT RE 2 (H373)
Acetic acid, oxo-, ethyl ester	924-44-7	EEC No. 213-105-3	50	Skin Irrit. 2 (H315) Skin Sens. 1 (H317)

Full text of Hazard Statements: see section 16

### **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If not breathing, give artificial respiration. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Remove all sources of ignition. Use personal protective equipment as required.
4.2. Most important symptoms and	effects, both acute and delayed
	Difficulty in breathing. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** May cause sensitization of susceptible persons. Use of epinephrine may be indicated. Treat symptomatically.

## **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons No information available.

#### 5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. In the event of fire and/or explosion do not breathe fumes. Contact with metals may evolve flammable gas. Thermal decomposition can lead to release of irritating gases and vapors.

#### Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Do not breathe mist/vapors/spray. Keep container tightly closed. Take precautionary measures against static discharges. Pay attention to flashback. Do not take internally. Wear personal protective equipment/face protection. Use only under a chemical fume hood. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

#### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and flame. Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep container tightly closed in a dry and well-ventilated place.

#### Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

#### 7.3. Specific end use(s)

Use in laboratories

#### Ethyl glyoxalate, ca 50% in toluene

#### 8.1. Control parameters

#### **Exposure limits**

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Toluene	STEL: 100 ppm 15 min	TWA: 50 ppm (8hr)	TWA: 192 mg/m <sup>3</sup> 8 hr.
	STEL: 384 mg/m <sup>3</sup> 15 min	TWA: 192 mg/m <sup>3</sup> (8hr)	TWA: 50 ppm 8 hr.
	TWA: 50 ppm 8 hr	STEL: 100 ppm (15min)	STEL: 384 mg/m <sup>3</sup> 15 min
	TWA: 191 mg/m <sup>3</sup> 8 hr	STEL: 384 mg/m <sup>3</sup> (15min)	STEL: 100 ppm 15 min
	Skin	Skin	Skin

#### **Biological limit values**

List source(s):

# Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Toluene 108-88-3 ( 50 )				DNEL = 384mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Toluene 108-88-3(50)	DNEL = 384mg/m <sup>3</sup>	DNEL = 384mg/m <sup>3</sup>	DNEL = 192mg/m <sup>3</sup>	DNEL = 192mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Toluene	PNEC = 0.68mg/L	PNEC =	PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg
108-88-3 ( 50 )		16.39mg/kg			soil dw
		sediment dw			

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Toluene	PNEC = 0.68mg/L	PNEC =			
108-88-3 ( 50 )	_	16.39mg/kg			
		sediment dw			

#### 8.2. Exposure controls

#### **Engineering Measures**

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

## Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

**Hand Protection** 

Protective gloves

#### Revision Date 09-Feb-2024

Glove material Natural rubber Butyl rubber Nitrile rubber	Breakthrough time See manufacturers recommendations	Glove thickness -	EU standard EN 374	Glove comments (minimum requirement)
Neoprene PVC				
Skin and body prot	tection Long sle	eved clothing.		
(Refer to manufacturer/s Ensure gloves are suital	ructions regarding permisupplier for information) ble for the task: Chemic o take into consideration	al compatability, Dex the specific local co	terity, Operational con	ovided by the supplier of the gloves. ditions, User susceptibility, e.g. he product is used, such as the danger
Respiratory Protec	appropri To prote	ate certified respirato	ors.	exposure limit they must use nent must be the correct fit and be used
Large scale/emergenc	are exce Recom	eded or if irritation of	other symptoms are e Particulates filter conf	6 approved respirator if exposure limits experienced forming to EN 143 Acid gases filter Typ
Small scale/Laboratory	limits are <b>Recom</b> r 141	e exceeded or if irrita nended half mask:-	tion or other symptoms	5; or; Half mask: EN140; plus filter, EN

# **Environmental exposure controls** Do not allow material to contaminate ground water system. Prevent product from entering drains.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

Ethyl glyoxalate, ca 50% in toluene

Physical State	Liquid	
Appearance Odor Odor Threshold Melting Point/Range Softening Point Boiling Point/Range Flammability (liquid) Flammability (solid,gas) Explosion Limits	Yellow aromatic No data available No data available No data available 110 °C / 230 °F Highly flammable Not applicable No data available	On basis of test data Liquid
Flash Point Autoignition Temperature Decomposition Temperature pH Viscosity Water Solubility Solubility in other solvents Partition Coefficient (n-octanol/w Component Toluene Vapor Pressure Density / Specific Gravity Bulk Density	7 °C / 44.6 °F No data available No data available No information available No information available No information available <b>ater)</b> <b>log Pow</b> 2.73 No data available 1.032 Not applicable	<b>Method -</b> No information available

Revision Date 09-Feb-2024

No data available Not applicable (liquid)	(Air = 1.0)	
C4 H6 O3		
102.09		
50		
Vapors may form explosive n	nixtures with air	
	Not applicable (liquid) C4 H6 O3 102.09 50	Not applicable (liquid) C4 H6 O3 102.09

### **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity	None known, based on information available	
10.2. Chemical stability	Stable under normal conditions.	
10.3. Possibility of hazardous reactions		
Hazardous Polymerization Hazardous Reactions	Hazardous polymerization may occur. None under normal processing.	
10.4. Conditions to avoid	Heating in air. Keep away from open flames, hot surfaces and sources of ignition.	
10.5. Incompatible materials	Strong oxidizing agents. Acids. Halogens. Metals.	

#### 10.6. Hazardous decomposition products

Ethyl glyoxalate, ca 50% in toluene

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information	See actual entry in RTECS for complete information.
(a) acute toxicity;	
Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

#### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat)1 h

(b) skin corrosion/irritation; Category 2

- (c) serious eye damage/irritation; No data available
- (d) respiratory or skin sensitization;<br/>RespiratoryNo data available<br/>Category 1SkinCategory 1

	No information available
(e) germ cell mutagenicity;	No data available
(f) carcinogenicity;	No data available
	There are no known carcinogenic chemicals in this product
(g) reproductive toxicity; Reproductive Effects	Category 2 SUSPECT REPRODUCTIVE HAZARD - CONTAINS MATERIAL WHICH MAY INJURE UNBORN CHILD (CAUSE BIRTH DEFECTS) (BASED ON ANIMAL DATA).
(h) STOT-single exposure;	Category 3
Results / Target organs	Central nervous system (CNS).
(i) STOT-repeated exposure;	Category 2
Target Organs	Eyes, Skin, Respiratory system, Central nervous system (CNS), Kidney, Liver, Neuropsychological effects, Ears.
(j) aspiration hazard;	Category 1
Other Adverse Effects	The toxicological properties have not been fully investigated.
Symptoms / effects,both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, ches pain, muscle pain or flushing.

### 11.2. Information on other hazards

Ethyl glyoxalate, ca 50% in toluene

Endocrine Disrupting Properties	Assess endocrine disrupting properties for human health.	This product does not contain any
	known or suspected endocrine disruptors.	

# SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity	
Ecotoxicity effects	

The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Toluene	50-70 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h	EC50: = 12.5 mg/L, 72h static
	5-7 mg/L LC50 96 h	(Daphnia magna)	(Pseudokirchneriella subcapitata)
	15-19 mg/L LC50 96 h	EC50: 5.46 - 9.83 mg/L, 48h	EC50: > 433 mg/L, 96h
	28 mg/L LC50 96 h	Static (Daphnia magna)	(Pseudokirchneriella subcapitata)
	12 mg/L LC50 96 h		,

Component	Microtox	M-Factor
Toluene	EC50 = 19.7 mg/L 30 min	

#### 12.2. Persistence and degradability No information available

Com	ponent	Degradability
Tol	luene	86% (20d)
108-8	8-3 ( 50 )	
Degradation in sewage	Contains substances known to be	e hazardous to the environment or not degradable in waste
treatment plant	water treatment plants.	

#### Ethyl glyoxalate, ca 50% in toluene

Revision Date 09-Feb-2024

### 12.3. Bioaccumulative potential No information available

Component	log Pow	Bioconcentration factor (BCF)
Toluene	2.73	90
<u>12.4. Mobility in soil</u>	No information available .	
12.5. Results of PBT and vPvB assessment	No data available for assessment.	
<u>12.6. Endocrine disrupting</u> properties Endocrine Disruptor Information	This product does not contain any known or s	uspected endocrine disruptors
12.7. Other adverse effects Persistent Organic Pollutant Ozone Depletion Potential	This product does not contain any known or so This product does not contain any known or so	uspected substance
SE	ECTION 13: DISPOSAL CONSIDER	RATIONS

13.1. Waste treatment methods	
Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

# **SECTION 14: TRANSPORT INFORMATION**

#### IMDG/IMO

<u>14.1. UN number</u>	UN1294
14.2. UN proper shipping name	Toluene (Mixture)
14.3. Transport hazard class(es)	3
14.4. Packing group	II

#### <u>ADR</u>

<u>14.1. UN number</u>	UN1294
14.2. UN proper shipping name	Toluene (Mixture)
14.3. Transport hazard class(es)	3
14.4. Packing group	II

Ethyl glyoxalate, ca 50% in toluene

<u>14.1. UN number</u> <u>14.2. UN proper shipping name</u> <u>14.3. Transport hazard class(es)</u> <u>14.4. Packing group</u>	UN1294 Toluene (Mixture) 3 II
14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

. .. . . . .

### **SECTION 15: REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Toluene	108-88-3	203-625-9	-	-	Х	Х	KE-33936	Х	Х
Acetic acid, oxo-, ethyl ester	924-44-7	213-105-3	-	-	-	Х	KE-27559	-	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Toluene	108-88-3	Х	ACTIVE	Х	-	Х	Х	Х
Acetic acid, oxo-, ethyl ester	924-44-7	Х	ACTIVE	-	Х	-	-	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	108-88-3	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Acetic acid, oxo-, ethyl ester	924-44-7	-	-	-

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Toluene	108-88-3	Not applicable	Not applicable
Acetic acid, oxo-, ethyl ester	924-44-7	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

#### Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

#### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

#### **WGK Classification**

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Toluene	WGK3	

Component	France - INRS (Tables of occupational diseases)
Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis,RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Toluene 108-88-3 ( 50 )	Prohibited and Restricted Substances	Group I	

#### 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

### **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

- H225 Highly flammable liquid and vapor
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

#### Legend

CAS - Chemical Abstracts ServiceTSCA - United States Toxic Substances Control Act Section 8(b)<br/>InventoryEINECS/ELINCS - European Inventory of Existing Commercial ChemicalDSL/NDSL - Canadian Domestic Substances List/Non-Domestic<br/>Substances/EU List of Notified Chemical SubstancesPICCS - Philippines Inventory of Chemicals and Chemical Substances<br/>IECSC - Chinese Inventory of Existing Chemical Substances<br/>KECL - Korean Existing and Evaluated Chemical SubstancesENCS - Japanese Existing and New Chemical Substances<br/>AICS - Australian Inventory of Chemical Substances<br/>NZIOC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit ACGIH - American Conference of Governmental Industrial Hygienists DNEL - Derived No Effect Level TWA - Time Weighted Average IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

RPE - Respiratory Protective Equipment	LD50 - Lethal Dose 50%
LC50 - Lethal Concentration 50%	EC50 - Effective Concentration 50%
NOEC - No Observed Effect Concentration	POW - Partition coefficient Octanol:Water
PBT - Persistent, Bioaccumulative, Toxic	vPvB - very Persistent, very Bioaccumulative
ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road	ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code	MARPOL - International Convention for the Prevention of Pollution from Ships
OECD - Organisation for Economic Co-operation and Development	ATE - Acute Toxicity Estimate
BCF - Bioconcentration factor	VOC - (Volatile Organic Compound)
Key literature references and sources for data https://echa.europa.eu/information-on-chemicals	
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index,	RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:			
Physical hazards	On basis of test data		
Health Hazards	Calculation method		
Environmental hazards	Calculation method		

#### **Training Advice**

Ethyl glyoxalate, ca 50% in toluene

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Creation Date	24-Aug-2009
Revision Date	09-Feb-2024
Revision Summary	Not applicable.

# This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**