

Creation Date 26-Sep-2009

Revision Date 21-Sep-2023

Revision Number 10

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

| | |
|---------------------------|--|
| Product Description: | m-Xylene |
| Cat No. : | 158930000; 158930010; 158931000 |
| Synonyms | 1,3-Dimethylbenzene |
| Index No | 601-022-00-9 |
| CAS No | 108-38-3 |
| EC No | 203-576-3 |
| Molecular Formula | C8 H10 |
| REACH registration number | 01-2119484621-37-0007 |

1.2. Relevant identified uses of the substance or mixture and uses advised against

| | |
|----------------------|--------------------------|
| Recommended Use | Laboratory chemicals. |
| Uses advised against | No Information available |

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road,
Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids

Category 3 (H226)

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

Health hazards

Aspiration Toxicity
Acute dermal toxicity
Acute Inhalation Toxicity - Vapors
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Specific target organ toxicity - (single exposure)

Category 1 (H304)
Category 4 (H312)
Category 4 (H332)
Category 2 (H315)
Category 2 (H319)
Category 3 (H335)

Environmental hazards

Chronic aquatic toxicity

Category 3 (H412)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H312 + H332 - Harmful in contact with skin or if inhaled
H335 - May cause respiratory irritation
H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P280 - Wear protective gloves/protective clothing/eye protection/face protection

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

3.1. Substances

| Component | CAS No | EC No | Weight % | CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567 |
|-----------|----------|-------------------|----------|---|
| m-Xylene | 108-38-3 | EEC No. 203-576-3 | >95 | Flam. Liq. 3 (H226) Asp. Tox. 1 (H304) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (335) Aquatic Chronic 3 (H412) |

| | |
|---------------------------|-----------------------|
| REACH registration number | 01-2119484621-37-0007 |
|---------------------------|-----------------------|

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

| | |
|---|---|
| General Advice | If symptoms persist, call a physician. |
| Eye Contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention. |
| Skin Contact | Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician. |
| Ingestion | Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward. |
| Inhalation | Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration). |
| Self-Protection of the First Aider | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. |

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|---|
| Notes to Physician | Treat symptomatically. Symptoms may be delayed. |
|---------------------------|---|

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

Water may be ineffective. Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

| Component | The United Kingdom | European Union | Ireland |
|-----------|---|---|---|
| m-Xylene | STEL: 100 ppm 15 min STEL: 441 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 220 mg/m ³ 8 hr Skin | TWA: 50 ppm (8h) TWA: 221 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 442 mg/m ³ (15min) Skin | TWA: 50 ppm 8 hr. TWA: 221 mg/m ³ 8 hr. STEL: 100 ppm 15 min STEL: 442 mg/m ³ 15 min Skin |

Biological limit values

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

| Component | United Kingdom | European Union |
|-----------|--|----------------|
| m-Xylene | Methyl hippuric acid: 650 mmol/mol creatinine urine post shift | |

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

Workers; See table for values

| Component | Acute effects local (Dermal) | Acute effects systemic (Dermal) | Chronic effects local (Dermal) | Chronic effects systemic (Dermal) |
|------------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| m-Xylene 108-38-3 (>95) | | | | DNEL = 212mg/kg bw/day |

| Component | Acute effects local (Inhalation) | Acute effects systemic (Inhalation) | Chronic effects local (Inhalation) | Chronic effects systemic (Inhalation) |
|------------------------------|----------------------------------|-------------------------------------|------------------------------------|---------------------------------------|
| m-Xylene 108-38-3 (>95) | DNEL = 442mg/m ³ | DNEL = 442mg/m ³ | DNEL = 221mg/m ³ | DNEL = 221mg/m ³ |

Predicted No Effect Concentration (PNEC)

See values below.

| Component | Fresh water | Fresh water sediment | Water Intermittent | Microorganisms in sewage treatment | Soil (Agriculture) |
|------------------------------|--------------------------------------|---|-------------------------------------|------------------------------------|---|
| m-Xylene 108-38-3 (>95) | PNEC = 0.044mg/L PNEC = 0.327mg/L | PNEC = 2.52mg/kg sediment dw PNEC = 12.46mg/kg sediment dw | PNEC = 0.01mg/L PNEC = 0.327mg/L | PNEC = 1.6mg/L PNEC = 6.58mg/L | PNEC = 0.852mg/kg soil dw PNEC = 2.31mg/kg soil dw |

| Component | Marine water | Marine water sediment | Marine water intermittent | Food chain | Air |
|------------------------------|---------------------------------------|-------------------------------|---------------------------|------------|-----|
| m-Xylene 108-38-3 (>95) | PNEC = 0.0044mg/L PNEC = 0.327mg/L | PNEC = 0.252mg/kg sediment dw | PNEC = 0.001mg/L | | |

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

| | | | | | |
|--|--|-------------------------------------|--|--|--|
| | | PNEC = 12.46mg/kg sediment dw | | | |
|--|--|-------------------------------------|--|--|--|

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

| Glove material | Breakthrough time | Glove thickness | EU standard | Glove comments |
|----------------|-------------------|-----------------|-------------|--|
| Viton (R) | > 480 minutes | 0.3 mm | EN 374 | As tested under EN374-3 Determination of Resistance to Permeation by Chemicals |
| PVA | > 360 minutes | 0.3 mm | | |
| Nitrile rubber | < 40 minutes | 0.38 mm | | |
| Neoprene | < 37 minutes | 0.45 mm | | |

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State

Liquid

Appearance Odor

Colorless
aromatic

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

| | | |
|---|--|--|
| Odor Threshold | No data available | |
| Melting Point/Range | -48 °C / -54.4 °F | |
| Softening Point | No data available | |
| Boiling Point/Range | 138 - 139 °C / 280.4 - 282.2 °F | |
| Flammability (liquid) | Flammable | On basis of test data |
| Flammability (solid,gas) | Not applicable | Liquid |
| Explosion Limits | Lower 1.7 Vol% Upper 7.6 Vol% | |
| Flash Point | 25 °C / 77 °F | Method - No information available |
| Autoignition Temperature | 465 °C / 869 °F | |
| Decomposition Temperature | No data available | |
| pH | No information available | |
| Viscosity | 0.62 mPa.s at 20 °C | |
| Water Solubility | Insoluble | |
| Solubility in other solvents | No information available | |
| Partition Coefficient (n-octanol/water) | | |
| Component | log Pow | |
| m-Xylene | 3.2 | |
| Vapor Pressure | 8 mbar @ 20 °C | |
| Density / Specific Gravity | 0.864 | |
| Bulk Density | Not applicable | Liquid |
| Vapor Density | 3.66 | (Air = 1.0) |
| Particle characteristics | (liquid) Not applicable | |

9.2. Other information

| | |
|----------------------|--|
| Molecular Formula | C8 H10 |
| Molecular Weight | 106.17 |
| Explosive Properties | explosive air/vapour mixtures possible |
| Evaporation Rate | 0.7 - (Ether = 1.0) |

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

| | |
|--------------------------|--|
| Hazardous Polymerization | Hazardous polymerization does not occur. |
| Hazardous Reactions | None under normal processing. |

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

Product Information

- (a) acute toxicity;
Oral Based on available data, the classification criteria are not met
Dermal Category 4
Inhalation Category 4

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-----------|-----------------------|------------------------------|--|
| m-Xylene | LD50 = 5 g/kg (Rat) | LD50 = 12.18 g/kg (Rabbit) | LC50 = 27124 mg/m ³ (Rat) 4 h |

- (b) skin corrosion/irritation; Category 2

- (c) serious eye damage/irritation; Category 2

- (d) respiratory or skin sensitization;
Respiratory No data available
Skin No data available

- (e) germ cell mutagenicity; No data available

- (f) carcinogenicity; No data available
There are no known carcinogenic chemicals in this product

- (g) reproductive toxicity; No data available

- (h) STOT-single exposure; Category 2
Results / Target organs Respiratory system.

- (i) STOT-repeated exposure; No data available
Target Organs None known.

- (j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects The product contains following substances which are hazardous for the environment.
Contains a substance which is: Toxic to aquatic organisms.

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

| Component | Freshwater Fish | Water Flea | Freshwater Algae |
|-----------|--|--|---|
| m-Xylene | LC50: = 12.9 mg/L, 96h semi-static (Poecilia reticulata) LC50: 14.3 - 18 mg/L, 96h flow-through (Pimephales promelas) LC50: = 8.4 mg/L, 96h semi-static (Oncorhynchus mykiss) | EC50: 2.81 - 5.0 mg/L, 48h Static (Daphnia magna) | EC50: = 4.9 mg/L, 72h static (Pseudokirchneriella subcapitata) |

| Component | Microtox | M-Factor |
|-----------|-------------------------|----------|
| m-Xylene | EC50 = 0.0084 mg/L 24 h | |

12.2. Persistence and degradability Expected to be biodegradable
Persistence Persistence is unlikely.
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

| Component | log Pow | Bioconcentration factor (BCF) |
|-----------|---------|-------------------------------|
| m-Xylene | 3.2 | No data available |

12.4. Mobility in soil The product is insoluble and floats on water The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces Spillage unlikely to penetrate soil Will likely be mobile in the environment due to its volatility. Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1307
14.2. UN proper shipping name XYLENES
14.3. Transport hazard class(es) 3
14.4. Packing group III

ADR

14.1. UN number UN1307
14.2. UN proper shipping name XYLENES
14.3. Transport hazard class(es) 3
14.4. Packing group III

IATA

14.1. UN number UN1307
14.2. UN proper shipping name XYLENES
14.3. Transport hazard class(es) 3
14.4. Packing group III

14.5. Environmental hazards No hazards identified
14.6. Special precautions for user No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component | CAS No | EINECS | ELINCS | NLP | IECSC | TCSI | KECL | ENCS | ISHL |
|-----------|----------|-----------|--------|-----|-------|------|----------|------|------|
| m-Xylene | 108-38-3 | 203-576-3 | - | - | X | X | KE-35428 | X | X |

| Component | CAS No | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|-----------|----------|------|---|-----|------|------|-------|-------|
| m-Xylene | 108-38-3 | X | ACTIVE | X | - | X | X | X |

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

| Component | CAS No | REACH (1907/2006) - | REACH (1907/2006) - | REACH Regulation (EC) |
|-----------|--------|---------------------|---------------------|-----------------------|
|-----------|--------|---------------------|---------------------|-----------------------|

ACR15893

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

| | | Annex XIV - Substances Subject to Authorization | Annex XVII - Restrictions on Certain Dangerous Substances | 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|----------|----------|---|--|--|
| m-Xylene | 108-38-3 | - | Use restricted. See item 75. (see link for restriction details) | - |

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

| Component | CAS No | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|-----------|----------|---|--|
| m-Xylene | 108-38-3 | Not applicable | Not applicable |

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

| Component | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|-----------|---------------------------------------|-------------------------|
| m-Xylene | WGK2 | |

| Component | France - INRS (Tables of occupational diseases) |
|-----------|---|
| m-Xylene | Tableaux des maladies professionnelles (TMP) - RG 4bis, RG 84 |

| Component | Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81) | Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC) | Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure |
|------------------------------|--|---|---|
| m-Xylene 108-38-3 (>95) | Prohibited and Restricted Substances | Group I | |

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways
H312 - Harmful in contact with skin
H332 - Harmful if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H412 - Harmful to aquatic life with long lasting effects
H335 - May cause respiratory irritation
H226 - Flammable liquid and vapor

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 26-Sep-2009
Revision Date 21-Sep-2023
Revision Summary Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage,

SAFETY DATA SHEET

m-Xylene

Revision Date 21-Sep-2023

transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet