

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: Potassium hydroxide 1M alcoholic  
Cat No. : J/6610/15, J/6610/17, J/6610/24

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.  
Uses advised against No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

**UK entity/business name**  
Fisher Scientific UK  
Bishop Meadow Road, Loughborough,  
Leicestershire LE11 5RG, United Kingdom

**EU entity/business name**  
Thermo Fisher Scientific  
Janssen Pharmaceuticaaan 3a  
2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

Tel: 01509 231166  
Chemtrec US: (800) 424-9300  
Chemtrec EU: 001-703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

##### Physical hazards

Flammable liquids	Category 2 (H225)
Substances/mixtures corrosive to metal	Category 1 (H290)

##### Health hazards

Acute oral toxicity	Category 4 (H302)
Acute dermal toxicity	Category 4 (H312)

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

Acute Inhalation Toxicity - Vapors  
Skin Corrosion/Irritation  
Serious Eye Damage/Eye Irritation  
Specific target organ toxicity - (single exposure)

Category 4 (H332)  
Category 1 A (H314)  
Category 1 (H318)  
Category 2 (H371)

## Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

## 2.2. Label elements

Contains METHANOL; Potassium hydroxide



Signal Word

Danger

## Hazard Statements

H225 - Highly flammable liquid and vapor  
H290 - May be corrosive to metals  
H314 - Causes severe skin burns and eye damage  
H371 - May cause damage to organs  
Optic nerve  
H302 + H312 + H332 - Harmful if swallowed, in contact with skin or if inhaled  
EUH071 - Corrosive to the respiratory tract

## Precautionary Statements

P260 - Do not breathe dust/fume/gas/mist/vapors/spray  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor/physician  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

## 2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Ethyl alcohol	64-17-5	200-578-6	84.4	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

Potassium hydroxide	1310-58-3	215-181-3	5.6	Met. Corr. 1 (H290) Acute Tox. 4 (H302) Skin Corr. 1A (H314) Eye Dam. 1 (H318)
Methyl alcohol	67-56-1	200-659-6	3.54	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Water	7732-18-5	231-791-2	6.46	-

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Ethyl alcohol	Eye Irrit. 2 :: C>=50%	-	-
Potassium hydroxide	Skin Corr. 1A (H314) :: C>=5% Skin Corr. 1B (H314) :: 2%<=C<5% Skin Irrit. 2 (H315) :: 0.5%<=C<2% Eye Irrit. 2 (H319) :: 0.5%<=C<2%	-	-
Methyl alcohol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-

Components	Reach Registration Number
Ethanol	01-2119457610-43
Potassium hydroxide	01-2119487136-33
Methanol	01-2119433307-44

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required. Do not rub affected area.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
<b>Ingestion</b>	Do NOT induce vomiting. Call a physician or poison control center immediately.
<b>Inhalation</b>	Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically. Symptoms may be delayed.
---------------------------	---

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water spray. Water mist may be used to cool closed containers.

#### **Extinguishing media which must not be used for safety reasons**

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Thermal decomposition can lead to release of irritating gases and vapors.

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

### 6.2. Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance. Take precautionary measures against static discharges. Wash hands before breaks and immediately after handling the product. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Flammables area. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510  
Storage Class (LGK) (Germany)

Class 3

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Ethyl alcohol	TWA: 1000 ppm TWA; 1920 mg/m <sup>3</sup> TWA WEL - STEL: 3000 ppm STEL; 5760 mg/m <sup>3</sup> STEL		STEL: 1000 ppm 15 min
Potassium hydroxide	WEL - 2 mg/m <sup>3</sup> STEL		STEL: 2 mg/m <sup>3</sup> 15 min
Methyl alcohol	WEL - TWA: 200 ppm TWA; 266 mg/m <sup>3</sup> TWA WEL - STEL: 250 ppm STEL; 333 mg/m <sup>3</sup> STEL	TWA: 200 ppm 8 hr TWA: 260 mg/m <sup>3</sup> 8 hr Skin	TWA: 200 ppm 8 hr. TWA: 260 mg/m <sup>3</sup> 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m <sup>3</sup> 15 min Skin

#### Biological limit values

List source(s):

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Ethyl alcohol 64-17-5 ( 84.4 )		DNEL = 87 mg/kg bw/d		

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl alcohol 64-17-5 ( 84.4 )				DNEL = 343mg/kg bw/day
Methyl alcohol 67-56-1 ( 3.54 )		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethyl alcohol 64-17-5 ( 84.4 )	DNEL = 1900mg/m <sup>3</sup>			DNEL = 950mg/m <sup>3</sup>
Potassium hydroxide 1310-58-3 ( 5.6 )			DNEL = 1mg/m <sup>3</sup>	
Methyl alcohol 67-56-1 ( 3.54 )	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

## Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methyl alcohol 67-56-1 ( 3.54 )	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl alcohol 67-56-1 ( 3.54 )	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			

## 8.2. Exposure controls

### Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	> 480 minutes	0.7mm	EN 374	(minimum requirement)

#### Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure; Impervious clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

#### Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

#### Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141; Type AX

When RPE is used a face piece Fit Test should be conducted

#### Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

## 9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless - Light yellow	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	78 - 80 °C / 172.4 - 176 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	<b>Lower</b> 3.3 vol% <b>Upper</b> 19 vol%	
Flash Point	15 °C / 59 °F	<b>Method</b> - No information available
Autoignition Temperature	363 °C / 685.4 °F	
Decomposition Temperature	No data available	
pH	> 12	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	<b>log Pow</b>	
Ethyl alcohol	-0.32	
Potassium hydroxide	0.83	
Methyl alcohol	-0.74	
Vapor Pressure	No data available	
Density / Specific Gravity	0.8	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

## 9.2. Other information

**Explosive Properties** Vapors may form explosive mixtures with air

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None known, based on information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization does not occur.  
**Hazardous Reactions** None under normal processing.

### 10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents. Acids.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Thermal decomposition can lead to release of irritating gases and vapors.

## SECTION 11: TOXICOLOGICAL INFORMATION

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Product Information

#### (a) acute toxicity;

Oral	Category 4
Dermal	Category 4
Inhalation	Category 4

### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg OECD 401 (Rat) 3450 mg/kg ( Mouse )	-	LC50 = 117-125 mg/l (4h) OECD 403 (rat) 20000 ppm/10H (rat)
Potassium hydroxide	LD50 = 333-384 mg/kg (Rat)	-	-
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L ( Rat ) 4 h
Water	-	-	-

(b) skin corrosion/irritation; Category 1 A

(c) serious eye damage/irritation; Category 1

#### (d) respiratory or skin sensitization;

Respiratory	No data available
Skin	No data available

Component	Test method	Test species	Study result
Ethyl alcohol 64-17-5 ( 84.4 )	Mouse Ear Swelling Test (MEST)	mouse	non-sensitising
	OECD Test Guideline 429 Local Lymph Node Assay	mouse	non-sensitising
Methyl alcohol 67-56-1 ( 3.54 )	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity; No data available

Component	Test method	Test species	Study result
Ethyl alcohol 64-17-5 ( 84.4 )	AMES test OECD Test Guideline 471	in vitro Bacteria	negative
	Gene cell mutation OECD Test Guideline 476	in vitro Mammalian	negative

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Ethyl alcohol 64-17-5 ( 84.4 )	OECD Test Guideline 416	Oral / mouse 2 Generation	NOAEL = 13.8 g/kg/day
	OECD Test Guideline 414	Inhalation / Rat	NOAEC = 16000 ppm
Methyl alcohol 67-56-1 ( 3.54 )	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)



# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

(h) STOT-single exposure; Category 2  
Results / Target organs Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available  
Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecotoxicity effects Contains no substances known to be hazardous to the environment or that are not degradable in waste water treatment plants.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethyl alcohol	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/L/96h	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h	EC50 (72h) = 275 mg/l (Chlorella vulgaris)
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	

Component	Microtox	M-Factor
Ethyl alcohol	Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min	
Methyl alcohol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

### 12.2. Persistence and degradability

Persistence Soluble in water, Persistence is unlikely, based on information available.

Component	Degradability
Ethyl alcohol 64-17-5 ( 84.4 )	OECD 301E = 94%
Methyl alcohol 67-56-1 ( 3.54 )	DT50 ~ 17.2d >94% after 20d

### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available
Potassium hydroxide	0.83	No data available
Methyl alcohol	-0.74	<10 dimensionless

### 12.4. Mobility in soil

The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

**12.5. Results of PBT and vPvB assessment** No data available for assessment.

**12.6. Endocrine disrupting properties**

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

**12.7. Other adverse effects**  
**Persistent Organic Pollutant**  
**Ozone Depletion Potential**

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

**13.1. Waste treatment methods**

**Waste from Residues/Unused Products** Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

**European Waste Catalogue (EWC)** According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

**Other Information** Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

## SECTION 14: TRANSPORT INFORMATION

**IMDG/IMO**

**14.1. UN number** UN2924  
**14.2. UN proper shipping name** Flammable liquid, corrosive, n.o.s.  
**Technical Shipping Name** Contains ethanol and potassium hydroxide  
**14.3. Transport hazard class(es)** 3  
**Subsidiary Hazard Class** 8  
**14.4. Packing group** II

**ADR**

**14.1. UN number** UN2924  
**14.2. UN proper shipping name** Flammable liquid, corrosive, n.o.s.  
**Technical Shipping Name** Contains ethanol and potassium hydroxide  
**14.3. Transport hazard class(es)** 3  
**Subsidiary Hazard Class** 8  
**14.4. Packing group** II

**IATA**

**14.1. UN number** UN2924  
**14.2. UN proper shipping name** Flammable liquid, corrosive, n.o.s.  
**Technical Shipping Name** Contains ethanol and potassium hydroxide  
**14.3. Transport hazard class(es)** 3

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

<b>Subsidiary Hazard Class</b>	8
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	No hazards identified
<b>14.6. Special precautions for user</b>	No special precautions required.
<b>14.7. Maritime transport in bulk according to IMO instruments</b>	Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl alcohol	64-17-5	200-578-6	-	-	X	X	KE-13217	X	X
Potassium hydroxide	1310-58-3	215-181-3	-	-	X	X	KE-29139	X	X
Methyl alcohol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl alcohol	64-17-5	X	ACTIVE	X	-	X	X	X
Potassium hydroxide	1310-58-3	X	ACTIVE	X	-	X	X	X
Methyl alcohol	67-56-1	X	ACTIVE	X	-	X	X	X
Water	7732-18-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl alcohol	64-17-5	-	-	-
Potassium hydroxide	1310-58-3	-	Use restricted. See item 75. (see link for restriction details)	-
Methyl alcohol	67-56-1	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Water	7732-18-5	-	-	-

#### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

Ethyl alcohol	64-17-5	Not applicable	Not applicable
Potassium hydroxide	1310-58-3	Not applicable	Not applicable
Methyl alcohol	67-56-1	500 tonne	5000 tonne
Water	7732-18-5	Not applicable	Not applicable

**Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals**

Not applicable

**Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?**

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Ethyl alcohol	WGK1	
Potassium hydroxide	WGK1	
Methyl alcohol	WGK 2	Class I : 20 mg/m <sup>3</sup> (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl alcohol 64-17-5 ( 84.4 )		Group I	
Potassium hydroxide 1310-58-3 ( 5.6 )	Prohibited and Restricted Substances		
Methyl alcohol 67-56-1 ( 3.54 )	Prohibited and Restricted Substances	Group I	

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

# SAFETY DATA SHEET

Potassium hydroxide 1M alcoholic

Revision Date 09-Feb-2024

H331 - Toxic if inhaled  
H370 - Causes damage to organs

## Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer  
Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/MDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**Key literature references and sources for data**

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**

**Physical hazards** On basis of test data

**Health Hazards** Calculation method

**Environmental hazards** Calculation method

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

**Creation Date** 09-Jun-2010

**Revision Date** 09-Feb-2024

**Revision Summary** Not applicable.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**